



TIRES
CATALOGUE
PASSENGER
CAR TIRE



*Reaching new heights
in the tire industry
through relentless
pursuit*

Wang Xicheng



CONTENTS

Summer

e.A52	15
AM520	17
SPORT GREEN	19
GREEN	21
A2	25
X7 _{RFT}	27
SPORT GREEN SUV	29
GREENVAN	31
R772	33
AT R781	34

All Season (M+S)

FORCE UHP	37
FORCE PLUS	43
AC300	44
FORCE HP	45
AS350	47
WONDER HP	49
AE130	50
PARALLER 4X4 HP	51
A51	53
PARALLER H/T	55
HT601	56
PARALLER A/T	57
AT760	60
AT Z5 PLUS	62
PARALLER M/T	63
SHARP	66
AR939	67

All WEATHER (3PMS)

GREEN2 4S	68
-----------------	----

Winter

AW31	73
I5	75
I3	77

ATLAS
TIRE
S

COMPANY INTRODUCTION

ATLAS TIRE

FORCE UHP-0

MT-0

AM520-0

Shandong Linglong Tyre Co., Ltd. is a technical tire manufacturer integrating tire design, development, manufacturing and sales.

Founded in 1975, the company has seven R&D centers, seven manufacturing bases across the world currently and over 17,783 employees, with its products widely used on passenger vehicles, commercial vehicles, and engineering machinery vehicles. It has built diversified brand system for different markets.

Including **LINGLONG**, **ATLAS**, **LEAO** and **EVOLUXX** etc. Linglong Tire had successful access to the A share market on July 6, 2016.



In the future, the company will fully implement its global layout, fully improve its core competitiveness, and strive to achieve its annual production and sales volume reaching 160 million units, sales revenue of over RMB 80 billion and production capacity among global top five tire manufacturers by 2030, becoming a technology-oriented enterprise with world-class technology, management and brand influence.

en.linglong.cn

BRAND VALUE

It strengthens the retail network construction, with nearly

200,000

Marketing outlets globally, promoting its brand reputation and customer loyalty through reliable product quality and excellent service.

The company's products are exported to 173 countries across the world, covering Europe, Middle East, Americas, Asia Pacific, and Africa, and provides OE service for over 100 manufacturing bases of 60 global well-known automakers.

Linglong's brand value reached

98.137

Billion RMB in 2024

Linglong has sponsored over

100

Sports events and teams worldwide

Abundant sports marketing sponsorship

such as Real Madrid CF and Chelsea FC, to enhance its brand awareness and influence.



GLOBAL LAYOUT

Linglong collects global extraordinary wisdom to demonstrate intelligent Linglong with technological innovation. The company has established R&D institutions in Germany, America, Beijing, Shanghai, Jinan, Yantai and Zhaoyuan, owning national enterprise design center, national recognized testing laboratory and national industrial design center, to form global integrative R&D pattern.



R&D Center in America

R&D Center in Germany

Serbia



Linglong International Europe d.o.o.Zrenjanin

R&D Center

- R&D Center in Zhaoyuan and Yantai
- R&D Center in Beijing
- R&D Center in Shanghai
- R&D Center in Jinan

Linglong Tyre Co.,Ltd.

- Jilin Linglong Tyre Co.,Ltd.
- Shandong Linglong Tyre Co.,Ltd.
- Dezhou Linglong Tyre Co.,Ltd.
- Shaanxi Linglong Tyre Co., Ltd.
- Hubei Linglong Tyre Co.,Ltd.
- Guangxi Linglong Tyre Co.,Ltd.
- Anhui Linglong Tyre Co.,Ltd.



Linglong International Tyre(Thailand)Co.,Ltd

7+5 STRATEGIC GLOBAL POSITIONING

In June 2021, Linglong plans to change its 6+6 global layout into 7+5 global layout to build seven Chinese manufacturing bases as well as five overseas manufacturing bases. At present, the company has five Chinese manufacturing bases in Zhaoyuan, Dezhou, Liuzhou, Jingmen, Changchun and two overseas manufacturing bases in Thailand and Serbia. Meanwhile, Linglong will carry out active inspection of its new factory's location, aiming at completing the full completion of 7+5 global layout, and fully utilizing global resources and expanding its global tire market.

90° N
On August 7th, 2016, Linglong Tire reaching North Pole

Europe

Ads on ten clubs of Europe five major league matches

GLOBAL PARTNER

Global Club of Champions Partner and Official Jersey Sleeve Sponsor of VfL Wolfsburg

Sponsor of Serbian SuperLiga from 2019 to 2022

Title sponsor of Linglong Tire Cup Sino-European Chess Elite Tournament

Asia

Senior sponsor for the China Pavilion at Expo 2020 Dubai UAE

Set up ATLAS Tire Drift Team for DCGP Set up Linglong Tire Drift Team for D1GRAND PRIX in Japan

Sponsor China Truck Racing Championship from 2015 to 2017

Sponsor the Ratchaburi Mitr Phol FC

Sponsor Chinese Volleyball League of 2017-2020 season

Official Partner of Formula Drift Japan

North America

Official Automotive Tire of the NHL Tampa Bay Lightning

Official Automotive Tire of USF Athletics

Official Partner of NBA China Games

Africa

Sponsor the Uganda National Basketball Team

Sponsor Zimbabwe Cricket

Oceania

Sponsor Brisbane Roar FC

Sponsor Australia Queensland Football Team

South America

Sponsor Brazilian football club to improve its brand awareness in South America

90° S
On December 3, 2016, Linglong Tire reaching South Pole

PROFESSIONAL AUTHORITATIVE LARGE OUTDOOR COMPREHENSIVE TIRE PROVING GROUND



Professional Authoritative Large Outdoor Comprehensive Tire Proving Ground

The Sino-Asia Tire Proving Ground is invested by Linglong Group, designed and constructed by a top international professional team. The total investment is nearly RMB 1.3 billion yuan. It builds 17 kinds of tire test tracks including wet handling road, wet ring, fatigue endurance road, NVH and comfort road, multi-functional platform and test mountain, off-road road, etc., covering the tire test of passenger vehicle, light trucks, heavy-duty trucks and buses, it can conduct field monitoring and indoor tests on more than 40 performance indicators such as tire handling, economy and comfort.



Automobile Testing Center

The second phase of the automobile testing center project plans to invest 1.314 billion yuan, including indoor laboratories such as the vehicle performance laboratory, parts laboratory, vehicle energy consumption/new energy laboratory, dynamics laboratory, intelligent networking laboratory, NVH laboratory, dynamic imprint laboratory, and intelligent networking testing field.

The project also includes 43 customer workshops of different specifications, 3 warehousing centers, and Huizhi Hotel. After completion, it will become a third-party testing platform for the automotive industry to gather innovation and service innovation.



Virtual simulation technology

In 2021, virtual simulation technology has made another breakthrough, promoting the application of whole vehicle driving simulator technology, virtualizing the whole vehicle and tires, adopting the VI grade DIM250 model, and achieving a 9-degree-of-freedom driving experience.

At that time, this technology will be the first in the industry and currently the largest and most advanced tire simulation technology in China.



T1, the asphalt concrete high-speed runway with the largest inclination in the world



T9, the first wet control road in China



T10, wet circular loop

SUMMER

ALL SEASON (M+S)

4S (3PMST)

WINTER

SUMMER

• Summer

e.A52	PAGE 15	AM520	PAGE 17
SPORT GREEN	PAGE 19	GREEN	PAGE 21
A2	PAGE 25	X7 _{RFT}	PAGE 27
SPORT GREEN SUV	PAGE 29	GREENVAN	PAGE 31
R772	PAGE 33	AT R781	PAGE 34

e.A52

Electrical Vehicle ULTRA HIGH PERFORMANCE
Short braking distance,excellent grip



- ▼ S-AC adaptive contact technology evenly distributes the perssure of the tire brought by instantaneous accele-tion,braking and turning of the vehicle,and distributes the bending pressure evenly on the tire contact surface to obtain better grip and control,making the tire more durable.
- ▼ The unique self-guiding pattern design of the tread effective-ly improves the grip,and design of the groove bottoms can break the water film and increase the safety of the wetland.
- ▼ Low RR compound design,has excellent long mileage perfor-mance,alleviates the journey anxiety and improves the driving experience of car owners.



e.A52

 PCR-NEVs/UHP

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
18									
	215/50R18	-	92	W	7J	630	1389	300	44
	235/45R18 XL	-	98	V	8J	750	1653	340	50
19									
	235/40R19 XL	-	96	W	8 1/2J	710	1565	340	50
	245/45R19 XL	-	102	W	8J	850	1874	340	50
	255/45R19 XL	-	104	W	8 1/2J	900	1984	340	50
	255/50R19 XL	-	107	W	8J	975	2149	340	50
	255/55R19 XL	-	111	W	8J	1090	2403	340	50
20									
	245/45R20 XL	-	103	W	8J	875	1929	340	50
	255/45R20 XL	-	105	Y	8 1/2J	925	2039	340	50
	255/50R20 XL	-	109	V	8J	1030	2271	340	50
	275/45R20 XL	-	110	W	9J	1060	2337	340	50

AM520

High handling performance
Super ability Run-Flat tire dedicated for luxury brand Car



AM520

- ▼ Open shoulder groove design to lower noise.
- ▼ 4 longitudinal groove design for superior driving stability and comfortable ride.

AM520 RFT

- ▼ Open shoulder groove design to lower noise.
- ▼ Asymmetric tread pattern design for better handling performance and fashionable appearance.
- ▼ Run-Flat technology used for driving safety.



AM520



RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
16									
	205/55R16	-	91	W	6 1/2J	615	1356	300	44
	215/55R16 XL	-	97	W	7J	730	1609	340	50
	225/55R16 XL	-	99	W	7J	775	1709	340	50
17									
	205/50R17 XL	-	93	W	6 1/2J	650	1433	340	50
	215/45R17 XL	-	91	W	7J	615	1356	340	50
	215/50R17 XL	-	95	W	7J	690	1521	340	50
	215/55R17	-	94	W	7J	670	1477	300	44
	225/45R17 XL	-	94	W	7 1/2J	670	1477	340	50
	225/50R17 XL	-	98	W	7J	750	1653	340	50
	225/55R17 XL	-	101	W	7J	825	1819	340	50
	235/45R17 XL	-	97	W	8J	730	1609	340	50
	235/50R17	-	96	W	7 1/2J	710	1565	300	44
	245/45R17 XL	-	99	W	8J	775	1709	340	50
	255/45R17	-	98	W	8 1/2J	750	1653	300	44
18									
	225/40R18 XL	-	92	W	8J	630	1389	340	50
	225/45R18 XL	-	95	W	7 1/2J	690	1521	340	50
	235/45R18 XL	-	98	W	8J	750	1653	340	50
	245/40R18 XL	-	97	W	8 1/2J	730	1609	340	50
	245/45R18 XL	-	100	W	8J	800	1764	340	50
	245/50R18 XL	-	104	W	7 1/2J	900	1984	340	50
	255/45R18 XL	-	103	W	8 1/2J	875	1929	340	50
19									
	225/45R19 XL	-	96	W	7 1/2J	710	1565	340	50
	245/45R19 XL	-	102	Y	8J	850	1874	340	50

AM520 RFT



RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
18									
	225/45R18	-	91	W	7 1/2J	615	1356	350	51

SPORT GREEN

High handling performance

- ▼ Superior grip and handling performance.
- ▼ Excellent stability.



 **PCR/UHP**

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
15									
	195/45R15	-	78	V	6 1/2J	425	937	300	44
	195/50R15	-	82	H	6J	475	1047	300	44
	195/50R15	-	82	V	6J	475	1047	300	44
16									
	185/50R16	-	81	V	6J	462	1019	300	44
	185/55R16 XL	-	87	V	6J	545	1201	340	50
	195/45R16 XL	-	84	V	6 1/2J	500	1102	340	50
	195/50R16	-	84	V	6J	500	1102	300	44
	205/45R16	-	83	W	7J	487	1074	300	44
	205/50R16	-	87	V	6 1/2J	545	1201	300	44
	205/50R16	-	87	W	6 1/2J	545	1201	300	44
	205/55R16	-	91	W	6 1/2J	615	1356	300	44
	215/55R16 XL	-	97	W	7J	730	1609	340	50
	215/55R16 XL	-	97	V	7J	730	1609	340	50
	225/50R16	-	92	V	7J	630	1389	300	44
	225/55R16	-	95	V	7J	690	1521	300	44
	225/55R16 XL	-	99	W	7J	775	1709	340	50

SPORT GREEN

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
17									
	205/45R17 XL	-	88	W	7J	560	1235	340	50
	205/50R17 XL	-	93	W	6 1/2J	650	1433	340	50
	215/40R17 XL	-	87	W	7 1/2J	545	1201	340	50
	215/45R17 XL	-	91	W	7J	615	1356	340	50
	215/50R17 XL	-	95	W	7J	690	1521	340	50
	215/55R17	-	94	W	7J	670	1477	300	44
	225/45R17 XL	-	94	W	7 1/2J	670	1477	340	50
	225/50R17 XL	-	98	W	7J	750	1653	340	50
	225/55R17 XL	-	101	W	7J	825	1819	340	50
	235/45R17 XL	-	97	W	8J	730	1609	340	50
	235/55R17 XL	-	103	W	7 1/2J	875	1929	340	50
	245/40ZR17	-	91	W	8 1/2J	615	1356	300	44
	245/45R17 XL	-	99	W	8J	775	1709	340	50
	255/40ZR17	-	94	W	9J	670	1477	300	44
18									
	215/35ZR18 XL	-	84	W	7 1/2J	500	1102	340	50
	215/40R18 XL	-	89	W	7 1/2J	580	1279	340	50
	215/45R18 XL	-	93	W	7J	650	1433	340	50
	225/40R18 XL	-	92	W	8J	630	1389	340	50
	225/45R18 XL	-	95	W	7 1/2J	690	1521	340	50
	235/40R18 XL	-	95	W	8 1/2J	690	1521	340	50
	235/50R18 XL	-	101	Y	7 1/2J	825	1819	340	50
	245/40R18 XL	-	97	W	8 1/2J	730	1609	340	50
	245/45R18 XL	-	100	W	8J	800	1764	340	50
	255/45R18 XL	-	103	W	8 1/2J	875	1929	340	50
19									
	225/35ZR19 XL	-	88	W	8J	560	1235	340	50
	225/40R19 XL	-	93	W	8J	650	1433	340	50
	235/35R19 XL	-	91	W	8 1/2J	615	1356	340	50
	245/35R19 XL	-	93	W	8 1/2J	650	1433	340	50
	245/40R19 XL	-	98	W	8 1/2J	750	1653	340	50
	255/30R19 XL	-	91	W	9J	615	1356	340	50
	255/35R19 XL	-	96	W	9J	710	1565	340	50
	265/30ZR19 XL	-	93	W	9 1/2J	650	1433	340	50
	275/30R19 XL	-	96	W	9 1/2J	710	1565	340	50
	275/35R19 XL	-	100	W	9 1/2J	800	1764	340	50
20									
	225/30R20 XL	-	85	W	8J	515	1135	340	50
	245/40R20 XL	-	99	W	8 1/2J	775	1709	340	50
	245/45R20 XL	-	103	Y	8J	875	1929	340	50

GREEN

Low fuel consumption

- ▼ Good straight driving stability.
- ▼ More comfortable and quiet ride.
- ▼ Low rolling resistance for better fuel efficiency.
- ▼ Excellent wet grip to effectively reduce risk of hydroplaning.



PCR/GP/HP

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
13									
	135/80R13	-	70	T	3 1/2J	335	739	300	44
	145/70R13	-	71	T	4 1/2J	345	761	300	44
	145/80R13	-	75	T	4J	387	853	300	44
	155/70R13	-	75	T	4 1/2J	387	853	300	44
	155/80R13	-	79	T	4 1/2J	437	963	300	44
	155/65R13	-	73	T	4 1/2J	365	805	300	44
	165/65R13	-	77	T	5J	412	908	300	44
	165/70R13	-	79	T	5J	437	963	300	44
	165/80R13	-	83	T	4 1/2J	487	1074	300	44

GREEN

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
13									
	175/65R13	-	80	T	5J	450	992	300	44
	175/70R13	-	82	T	5J	475	1047	300	44
	175/75R13	-	84	T	5J	500	1102	300	44
	185/70R13	-	86	T	5 1/2J	530	1168	300	44
14									
	155/65R14	-	75	T	4 1/2J	387	853	300	44
	165/60R14	-	75	H	5J	387	853	300	44
	165/65R14	-	79	T	5J	437	963	300	44
	165/70R14	-	81	T	5J	462	1019	300	44
	165/70R14 XL	-	85	T	5J	515	1135	340	50
	175/60R14	-	79	H	5J	437	963	300	44
	175/65R14	-	82	T	5J	475	1047	300	44
	175/65R14	-	82	H	5J	475	1047	300	44
	175/65R14 XL	-	86	T	5J	530	1168	340	50
	175/70R14	-	84	T	5J	500	1102	300	44
	175/70R14 XL	-	88	T	5J	560	1235	340	50
	175/75R14	-	86	T	5J	530	1168	300	44
	175/80R14	-	88	T	5J	560	1235	300	44
	185/55R14	-	80	H	6J	450	992	300	44
	185/60R14	-	82	H	5 1/2J	475	1047	300	44
	185/65R14	-	86	T	5 1/2J	530	1168	300	44
	185/65R14	-	86	H	5 1/2J	530	1168	300	44
	185/70R14	-	88	T	5 1/2J	560	1235	300	44
	185/70R14	-	88	H	5 1/2J	560	1235	300	44
	195/60R14	-	86	H	6J	530	1168	300	44

SUMMER

ALL SEASON (M+S)

4S (3PM5F)

WINTER

GREEN

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
14									
	195/65R14	-	89	H	6J	580	1297	300	44
	195/70R14	-	91	T	6J	615	1356	300	44
	195/70R14	-	91	H	6J	615	1356	300	44
15									
	175/60R15	-	81	V	5J	462	1019	300	44
	175/65R15	-	84	T	5J	500	1102	300	44
	175/65R15	-	84	H	5J	500	1102	300	44
	185/55R15	-	82	H	6J	475	1047	300	44
	185/55R15	-	82	V	6J	475	1047	300	44
	185/60R15	-	84	H	5 1/2J	500	1102	300	44
	185/60R15 XL	-	88	H	5 1/2J	560	1235	340	50
	185/65R15	-	88	T	5 1/2J	560	1235	300	44
	185/65R15	-	88	H	5 1/2J	560	1235	300	44
	185/65R15 XL	-	92	T	5 1/2J	630	1389	340	50
	195/50R15	-	82	H	6J	475	1047	300	44
	195/50R15	-	82	V	6J	475	1047	300	44
	195/55R15	-	85	H	6J	515	1135	300	44
	195/55R15	-	85	V	6J	515	1135	300	44
	195/60R15	-	88	H	6J	560	1235	300	44
	195/60R15	-	88	V	6J	560	1235	300	44
	195/65R15	-	91	H	6J	615	1356	300	44
	195/65R15	-	91	T	6J	615	1356	300	44
	195/65R15	-	91	V	6J	615	1356	300	44
	195/65R15 XL	-	95	T	6J	690	1521	340	50

GREEN

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
15									
	195/70R15 XL	-	97	T	6J	730	1609	340	50
	205/55R15	-	88	V	6 1/2J	560	1235	300	44
	205/60R15	-	91	H	6J	615	1356	300	44
	205/60R15	-	91	V	6J	615	1356	300	44
	205/65R15	-	94	H	6J	670	1477	300	44
	205/65R15	-	94	V	6J	670	1477	300	44
	205/70R15	-	96	H	6J	710	1565	300	44
	215/65R15 XL	-	100	H	6 1/2J	800	1764	340	50
	225/60R15	-	96	V	6 1/2J	710	1565	300	44
16									
	195/50R16	-	84	V	6J	500	1102	300	44
	195/50R16 XL	-	88	V	6J	560	1235	340	50
	195/55R16	-	87	H	6J	545	1201	300	44
	195/55R16	-	87	V	6J	545	1201	300	44
	205/55R16	-	91	H	6 1/2J	615	1356	300	44
	205/55R16	-	91	V	6 1/2J	615	1356	300	44
	205/55R16 XL	-	94	V	6 1/2J	670	1477	340	50
	205/60R16	-	92	H	6J	630	1389	300	44
	205/60R16	-	92	V	6J	630	1389	300	44
	215/60R16 XL	-	99	V	6 1/2J	775	1709	340	50
	215/65R16	-	98	H	6 1/2J	750	1653	300	44
	225/60R16 XL	-	102	V	6 1/2J	850	1874	340	50
17									
	205/40R17 XL	-	84	W	7 1/2J	500	1102	340	50

A2

Dry/wet handling performance and drainage performance
Super ability Run-Flat tire dedicated for luxury brand SUV

A2

- ▼ Asymmetric tread pattern design for better drainage performance inside and grip performance outside.
- ▼ Big shoulder blocks to effectively improve handling performance.

A2_{RFT}

- ▼ Asymmetric tread pattern design for better drainage performance inside and grip performance outside.
- ▼ Big shoulder blocks to effectively improve handling performance.
- ▼ Run-Flat technology used for driving safety.



SUV/UHP

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
18									
	235/50R18	-	97	V	7 1/2J	730	1609	300	44
	235/60R18	-	103	V	7J	875	1929	300	44
	255/55R18 XL	-	109	W	8J	1030	2271	340	50
19									
	225/55R19	-	99	V	7J	775	1709	300	44
	235/50R19	-	99	W	7 1/2J	775	1709	300	44
	235/55R19 XL	-	105	W	7 1/2J	925	2039	340	50
	245/55R19	-	103	V	7 1/2J	875	1929	300	44
	255/45R19	-	100	Y	8 1/2J	800	1764	300	44

A2

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
19									
	255/50R19 XL	-	107	W	8J	975	2149	340	50
	255/55R19 XL	-	111	W	8J	1090	2403	340	50
	265/50R19	-	106	W	8 1/2J	950	2094	300	44
	275/45R19 XL	-	108	Y	9J	1000	2205	340	50
20									
	245/45R20 XL	-	103	W	8J	875	1929	340	50
	255/45R20	-	101	W	8 1/2J	825	1819	300	44
	255/50R20 XL	-	109	Y	8J	1030	2271	340	50
	275/40R20 XL	-	106	Y	9 1/2J	950	2094	340	50
	275/45R20 XL	-	110	W	9J	1060	2337	340	50
	295/40R20	-	106	Y	10 1/2J	950	2094	300	44
22									
	275/50R22	-	111	W	8 1/2J	1090	2403	300	44

A2_{RFT}

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
18									
	235/50R18	-	97	W	7 1/2J	730	1609	300	44
	255/55R18 XL	-	109	V	8J	1030	2271	340	50
	235/60R18	-	103	W	7 J	875	1929	300	44
19									
	255/50R19 XL	-	107	W	8J	975	2149	340	50

X7_{RFT}

Super ability Run-Flat tire dedicated for luxury brand SUV

- ▼ Asymmetric tread pattern design for better drainage performance inside and grip performance outside.
- ▼ Big shoulder blocks to effectively improve handling performance.
- ▼ Run-Flat technology used for driving safety.



SUV/UHP (explosion-proof)

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
18									
	225/50R18	–	95	W	7J	690	1521	300	44
	235/50R18	–	97	W	7 1/2J	730	1609	300	44
	245/40R18	–	93	W	8 1/2J	650	1433	300	44
	255/45R18	–	99	W	8 1/2J	775	1709	300	44
19									
	225/45R19	–	92	W	7 1/2J	630	1389	300	44
	245/50R19	–	101	W	7 1/2J	825	1819	300	44
	255/40R19	–	96	W	9J	710	1565	300	44
	255/45R19	–	100	W	8 1/2J	800	1764	300	44
	285/45R19	–	107	W	9 1/2J	975	2149	300	44

X7_{RFT}

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
20									
	245/45R20	-	99	W	8J	775	1709	300	44
	255/35R20	-	93	W	9J	650	1433	300	44
	255/45R20	-	101	W	8 1/2J	825	1819	300	44
	275/45R20	-	106	W	9J	950	2094	300	44
	275/50R20	-	109	W	8 1/2J	1030	2271	300	44
	285/45R20	-	108	W	9 1/2J	1000	2205	300	44
	295/45R20	-	110	W	10J	1060	2337	300	44
	305/40R20 XL	-	112	W	11J	1120	2469	340	50
21									
	255/50R21	-	106	W	8J	950	2094	300	44
	285/35R21	-	101	W	10J	825	1819	300	44
	285/45R21	-	109	W	9 1/2J	1030	2271	300	44

SPORT GREEN SUV

High handling performance

- ▼ Excellent steering and handling performance.
- ▼ Superior drainage performance.
- ▼ Lower noise.



SUV/HP

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
16									
	215/65R16	-	98	H	6 1/2J	750	1653	300	44
	215/70R16	-	100	H	6 1/2J	800	1764	300	44
	225/70R16	-	103	H	6 1/2J	875	1929	300	44
	235/60R16	-	100	H	7J	800	1764	300	44
	235/70R16	-	106	H	7J	950	2094	300	44
	245/70R16	-	107	H	7J	975	2149	300	44
	255/65R16	-	109	H	7 1/2J	1030	2271	300	44
	265/70R16	-	112	H	8J	1120	2469	300	44

SPORT GREEN SUV

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
17									
	215/60R17	-	96	H	6 1/2J	710	1565	300	44
	225/65R17	-	102	H	6 1/2J	850	1874	300	44
	235/55R17	-	99	V	7 1/2J	775	1709	300	44
	235/65R17 XL	-	108	V	7J	1000	2205	340	50
	245/65R17	-	107	H	7J	975	2149	300	44
	265/65R17	-	112	H	8J	1120	2469	300	44
18									
	225/55R18	-	98	V	7J	750	1653	300	44
	235/50R18	-	97	W	7 1/2J	730	1609	300	44
	235/55R18	-	100	V	7 1/2J	800	1764	300	44
	235/60R18 XL	-	107	W	7J	975	2149	340	50
	255/55R18 XL	-	109	W	8J	1030	2271	340	50
	255/70R18	-	113	H	7 1/2J	1150	2535	300	44
19									
	255/50R19 XL	-	107	W	8J	975	2149	340	50
20									
	275/40R20 XL	-	106	W	9 1/2J	950	2094	340	50
	275/45R20 XL	-	110	W	9J	1060	2337	340	50
21									
	295/35R21 XL	-	107	Y	101/2J	975	2149	340	50

GREENVAN

High wear performance

- ▼ Excellent grip and handling performance.
- ▼ Better grip performance on slippery road together with high safety coefficient.
- ▼ Suitable for commercial vehicles.



RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
10									
	195/55R10C	-	98/96	P	6.00I	D710 S750	D1565 S1653	250	36
12									
	155R12C	8PR	88/86	N	4.50B	D530 S560	D1168 S1235	450	65
13									
	155R13C	8PR	91/89	N	4.50B	D580 S615	D1280 S1355	450	65
	165R13C	8PR	94/93	R	4.50B	D650 S670	D1433 S1477	450	65
	175R13C	8PR	97/95	R	5.00B	D690 S730	D1521S1609	450	65
	195/50R13C	-	104/101	N	6J	D825 S900	D1819 S1984	650	95

GREENVAN

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
14									
	165/70R14C	6PR	89/87	R	5J	D545 S580	D1201 S1279	350	51
	175R14C	8PR	99/98	R	5J	D750 S775	D1653 S1709	450	65
	175/65R14C	6PR	90/88	T	5J	D560 S600	D1235 S1323	375	54
	185R14C	8PR	102/100	Q	5 1/2J	D800 S850	D1764 S1874	450	65
	195R14C	8PR	106/104	Q	5 1/2J	D900 S950	D1984 S2094	450	65
	205R14C	8PR	109/107	Q	6J	D975 S1030	D2149 S2271	450	65
	215R14C	8PR	112/110	Q	6J	D1060 S1120	D2337 S2469	450	65
15									
	185R15C	8PR	103/102	Q	5 1/2J	D850 S875	D1874 S1929	450	65
	195/70R15C	8PR	104/102	S	6J	D850 S900	D1874 S1984	450	65
	195R15C	8PR	106/104	R	5 1/2J	D900 S950	D1984 S2094	450	65
	205/65R15C	6PR	102/100	T	6J	D800 S850	D1764 S1874	350	51
	205/70R15C	8PR	106/104	S	6J	D900 S950	D1984 S2094	450	65
	215/70R15C	8PR	109/107	S	6 1/2J	D975 S1030	D2149 S2271	450	65
	225/70R15C	8PR	112/110	S	6 1/2J	D1060 S1120	D2337 S2469	450	65
16									
	175/75R16C	8PR	101/99	S	5J	D775 S825	D1710 S1820	475	69
	185/75R16C	8PR	104/102	S	5J	D850 S900	D1874 S1984	475	69
	195/60R16C	6PR	99/97	H	6J	D730 S775	D1609 S1709	375	54
	195/65R16C	8PR	104/102	S	6J	D850 S900	D1874 S1984	475	69
	195/75R16C	8PR	107/105	S	5 1/2J	D925 S975	D2039 S2149	475	69
	205/65R16C	8PR	107/105	T	6J	D925 S975	D2039 S2149	475	69
	205/75R16C	8PR	110/108	S	5 1/2J	D1000 S1060	D2205 S2337	475	69
	205/80R16	-	104	S	5 1/2J	900	1984	280	41
	205R16C	8PR	110/108	T	6J	D1000 S1060	D2205 S2337	450	65
	215/60R16C	6PR	103/101	T	6 1/2J	D825 S875	D1819 S1929	375	54
	215/65R16C	8PR	109/107	S	6 1/2J	D975 S1030	D2149 S2271	475	69
	215/70R16C	6PR	108/106	T	6 1/2J	D950 S1000	D2094 S2205	350	51
	215/75R16C	8PR	113/111	S	6J	D1090 S1150	D2403 S2535	475	69
	225/65R16C	8PR	112/110	S	6 1/2J	D1060 S1120	D2337 S2469	475	69
	235/65R16C	8PR	115/113	S	7J	D1150 S1215	D2535 S2679	475	69

R772

Commercial Tire With High Mileage

- ▼ Wide tread surface for superior wear resistance performance.
- ▼ Big shoulder blocks to enhance tire traction and stiffness performance.
- ▼ Optimized pattern pitches distribution to offer more comfortable and quiet ride.



RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
14									
	195R14CWR	8PR	106/104	P	5 1/2J	D900 S950	D1984 S2094	450	65
	205/75R14CWR	8PR	109/107	S	5 1/2J	D975 S1030	D2149 S2271	475	69
15									
	195R15C WR	8PR	106/104	R	5 1/2J	D900 S950	D1984 S2094	450	65
	205/70R15C	8PR	106/104	S	6J	D900 S950	D1985 S2095	450	65
	205/70R15C WR	8PR	106/104	S	6J	D900 S950	D1985 S2095	450	65
	215/70R15C WR	8PR	109/107	R	6 1/2J	D975 S1030	D2150 S2270	450	65
	225/70R15CWR	8PR	112/110	R	6 1/2J	D1060 S1120	D2335 S2470	450	65

AT R781

Trailer Tire

- ▼ Low fuel consumption.
- ▼ Specially designed for trailer.



RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
13									
	ST175/80R13	6PR	91/87	M	5J	D 545 S 615	D 1200 S 1360	350	50
14									
	ST205/75R14	6PR	100/96	M	5 1/2J	D 710 S 800	D 1570 S 1760	350	50
	ST205/75R14	8PR	105/101	M	5 1/2J	D 825 S 925	D 1820 S 2040	450	65
	ST215/75R14	6PR	102/98	M	6J	D 750 S 850	D 1650 S 1870	350	50
15									
	ST205/75R15	8PR	107/102	M	5 1/2J	D 850 S 975	D 1870 S 2150	450	65
	ST205/75R15	6PR	101/97	M	5 1/2J	D 730 S 825	D 1610 S 1820	350	50
	ST225/75R15	8PR	113/108	M	6J	D 1000 S 1150	D 2200 S 2540	450	65
	ST225/75R15	10PR	117/112	M	6J	D 1120 S 1285	D 2470 S 2830	550	80
16									
	ST235/80R16	10PR	123/119	M	6 1/2J	D 1360 S 1550	D 3000 S 3420	550	80
	ST235/80R16	12PR	126/122	M	6 1/2J	D 1500 S 1700	D 3305 S 3750	650	95
	ST235/85R16	10PR	125/121	M	6 1/2J	D 1450 S 1650	D 3200 S 3640	550	80



► *All Season (M+S)*

FORCE UHP PAGE 37

AC300 PAGE 44

AS350 PAGE 47

AE130 PAGE 50

A51 PAGE 53

FORCE PLUS PAGE 43

FORCE HP PAGE 45

WONDER HP PAGE 49

PARALLER 4X4 HP PAGE 51

PARALLER H/T PAGE 55

HT601 PAGE 56

AT760 PAGE 60

PARALLER M/T PAGE 63

AR939 PAGE 67

PARALLER A/T PAGE 57

AT Z5 PLUS PAGE 62

SHARP PAGE 66

GREEN2 4S PAGE 68

FORCE UHP

High handling performance UHP tire



- ▼ Excellent dry and wet handling performance.
- ▼ Asymmetric tread pattern design for better drainage performance inside and grip performance outside,excellent steering performance.
- ▼ Wide tread surface for superior comfortable ride.

FORCE UHP

 PCR/UHP

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
16									
	195/45R16 XL	-	84	V	6 1/2J	500	1102	340	50
	205/50R16	-	87	W	6 1/2J	545	1201	300	44
	205/55R16	-	91	W	6 1/2J	615	1356	300	44
	215/50R16 XL	-	94	W	7J	670	1477	340	50
	215/55R16 XL	-	97	W	7J	730	1609	340	50
	225/50R16	-	92	W	7J	630	1389	300	44
	225/55R16	-	95	W	7J	690	1521	300	44
17									
	195/40R17 XL	-	81	V	7J	462	1019	340	50
	195/45R17 XL	-	85	W	6 1/2J	515	1135	340	50
	205/40R17 XL	-	84	W	7 1/2J	500	1102	340	50
	205/45R17 XL	-	88	W	7J	560	1235	340	50
	205/50R17 XL	-	93	W	6 1/2J	650	1433	340	50
	205/55R17	-	91	V	6 1/2J	615	1356	350	51
	215/45R17 XL	-	91	W	7J	615	1356	340	50
	215/50R17 XL	-	95	W	7J	690	1521	340	50
	215/55R17	-	94	W	7J	670	1477	300	44
	225/45R17 XL	-	94	W	7 1/2J	670	1477	340	50
	225/50R17 XL	-	98	W	7J	750	1653	340	50
	225/55R17	-	97	W	7J	730	1609	300	44
	235/45R17 XL	-	97	W	8J	730	1609	340	50
	235/50R17	-	96	W	7 1/2J	710	1565	300	44
	235/55R17	-	99	W	7 1/2J	775	1709	300	44
	245/40R17	-	91	W	8 1/2J	615	1356	300	44
	245/45R17 XL	-	99	W	8J	775	1709	340	50
	245/65R17 XL	-	111	H	7J	1090	2403	340	50
	255/40R17 XL	-	98	W	9J	750	1653	340	50
	275/40R17	-	98	W	9 1/2J	750	1653	300	44

SUMMER

ALL SEASON (M+S)

4S (3PM5F)

WINTER

FORCE UHP

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
18									
	195/35R18 XL	-	79	W	7J	437	963	340	50
	205/35R18 XL	-	81	W	7 1/2J	462	1019	340	50
	205/40R18 XL	-	86	W	7 1/2J	530	1168	340	50
	215/35R18 XL	-	84	W	7 1/2J	500	1102	340	50
	215/40R18 XL	-	89	Y	7 1/2J	580	1279	340	50
	215/45R18 XL	-	93	Y	7J	650	1433	340	50
	225/35R18 XL	-	87	W	8J	545	1201	340	50
	225/40R18 XL	-	92	Y	8J	630	1389	340	50
	225/45R18 XL	-	95	Y	7 1/2J	690	1521	340	50
	225/50R18	-	95	W	7J	690	1521	300	44
	235/40R18 XL	-	95	Y	8 1/2J	690	1521	340	50
	235/45R18 XL	-	98	Y	8J	750	1653	340	50
	235/50R18	-	97	Y	7 1/2J	730	1609	300	44
	245/40R18 XL	-	97	Y	8 1/2J	730	1609	340	50
	245/45R18 XL	-	100	Y	8J	800	1764	340	50
	245/50R18	-	100	Y	7 1/2J	800	1764	300	44
	255/35R18 XL	-	94	Y	9J	670	1477	340	50
	255/40R18 XL	-	99	Y	9J	775	1709	340	50
	255/45R18 XL	-	103	W	8 1/2J	875	1929	340	50
	255/55R18 XL	-	109	W	8J	1030	2271	340	50
	265/35R18 XL	-	97	W	9 1/2J	730	1609	340	50
	265/40R18 XL	-	101	Y	9 1/2J	825	1819	340	50
	275/35R18	-	95	Y	9 1/2J	690	1521	300	44
	275/40R18 XL	-	103	Y	9 1/2J	875	1929	340	50
	305/30R18	-	97	W	11J	730	1609	300	44

FORCE UHP

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
19									
	215/35R19 XL	-	85	V	7 1/2J	515	1135	340	50
	225/35R19 XL	-	88	W	8J	560	1235	340	50
	225/40R19 XL	-	93	Y	8J	650	1433	340	50
	225/45R19 XL	-	96	Y	7 1/2J	710	1565	340	50
	235/35R19 XL	-	91	Y	8 1/2J	615	1356	340	50
	235/40R19 XL	-	96	Y	8 1/2J	710	1565	340	50
	235/50R19	-	99	V	7 1/2J	775	1709	350	51
	235/55R19 XL	-	105	Y	7 1/2J	925	2039	340	50
	245/35R19 XL	-	93	W	8 1/2J	650	1433	340	50
	245/40R19 XL	-	98	Y	8 1/2J	750	1653	340	50
	245/45R19 XL	-	102	W	8J	850	1874	340	50
	245/50R19 XL	-	105	W	7 1/2J	925	2039	340	50
	245/55R19	-	103	V	7 1/2J	875	1929	300	44
	255/35R19 XL	-	96	Y	9J	710	1565	340	50
	255/40R19 XL	-	100	Y	9J	800	1764	340	50
	255/45R19 XL	-	104	Y	8 1/2J	900	1984	340	50
	255/50R19 XL	-	107	Y	8J	975	2149	340	50
	255/60R19	-	109	H	7 1/2J	1030	2271	300	44
	265/30R19 XL	-	93	W	9 1/2J	650	1433	340	50
	265/35R19 XL	-	98	Y	9 1/2J	750	1653	340	50
	265/40R19 XL	-	102	Y	9 1/2J	850	1874	340	50
	265/50R19 XL	-	110	W	8 1/2J	1060	2337	340	50
	275/30R19 XL	-	96	W	9 1/2J	710	1565	340	50
	275/35R19 XL	-	100	Y	9 1/2J	800	1764	340	50
	275/40R19 XL	-	105	Y	9 1/2J	925	2039	340	50
	275/45R19 XL	-	108	W	9J	1000	2205	340	50
	275/55R19	-	111	W	8 1/2J	1090	2403	300	44
	285/35R19 XL	-	103	Y	10J	875	1929	340	50
	285/45R19 XL	-	111	W	9 1/2J	1090	2403	340	50
	295/30R19 XL	-	100	W	10 1/2J	800	1764	340	50

SUMMER

ALL SEASON (M+S)

4S (3PM5F)

WINTER

FORCE UHP

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
20									
	295/40R20 XL	-	110	W	10 1/2J	1060	2337	340	50
	305/40R20 XL	-	112	Y	11J	1120	2469	340	50
	215/30R20 XL	-	82	W	7 1/2J	475	1047	340	50
	225/30R20 XL	-	85	W	8J	515	1135	340	50
	225/35R20 XL	-	90	W	8J	600	1323	340	50
	235/30R20 XL	-	88	W	8 1/2J	560	1235	340	50
	235/35R20 XL	-	92	W	8 1/2J	630	1389	340	50
	235/55R20	-	102	V	7 1/2J	850	1874	350	51
	245/30R20 XL	-	90	W	8 1/2J	600	1323	340	50
	245/35R20 XL	-	95	W	8 1/2J	690	1521	340	50
	245/40R20 XL	-	99	Y	8 1/2J	775	1709	340	50
	245/45R20 XL	-	103	Y	8J	875	1929	340	50
	245/50R20	-	102	V	7 1/2J	850	1874	300	44
	255/30R20 XL	-	92	W	9J	630	1389	340	50
	255/35R20 XL	-	97	Y	9J	730	1609	340	50
	255/40R20 XL	-	101	W	9J	825	1819	340	50
	255/45R20 XL	-	105	Y	8 1/2J	925	2039	340	50
	255/50R20 XL	-	109	Y	8J	1030	2271	340	50
	265/35R20 XL	-	99	Y	9 1/2J	775	1709	340	50
	265/45R20 XL	-	108	Y	9J	1000	2205	340	50
	265/50R20 XL	-	111	V	8 1/2J	1090	2403	340	50
	275/30R20 XL	-	97	Y	9 1/2J	730	1609	340	50
	275/35R20 XL	-	102	Y	9 1/2J	850	1874	340	50
	275/40R20 XL	-	106	Y	9 1/2J	950	2094	340	50
	275/45R20 XL	-	110	W	9J	1060	2337	340	50
	285/25R20 XL	-	93	W	10 1/2J	650	1433	340	50
	285/50R20	-	112	V	9J	1120	2469	300	44
	295/25R20 XL	-	95	Y	10 1/2J	690	1521	340	50
	305/25R20 XL	-	97	Y	11J	730	1609	340	50
	315/35R20 XL	-	110	W	11J	1060	2337	340	50
21									
	235/35R21	-	89	W	8 1/2J	580	1279	300	44
	245/30R21 XL	-	91	W	8 1/2J	615	1356	340	50
	245/35R21 XL	-	96	W	8 1/2J	710	1565	340	50
	255/30R21 XL	-	93	W	9J	650	1433	340	50
	HL255/35R21	-	101	Y	9J	825	1819	340	50
	265/40R21 XL	-	105	V	9 1/2J	925	2039	340	50
	275/35R21	-	99	W	9 1/2J	775	1709	300	44
	285/30R21 XL	-	100	Y	10J	800	1764	340	50
	295/35R21 XL	-	107	Y	10 1/2J	975	2149	340	50
	275/45R21 XL	-	110	W	9J	1060	2337	340	50
	285/40R21 XL	-	109	W	10J	1030	2271	340	50
	315/35R21 XL	-	111	W	11J	1090	2403	340	50
	315/40R21 XL	-	115	Y	11J	1215	2679	340	50

FORCE UHP

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
22									
	315/30R22 XL	-	107	Y	11J	975	2149	340	50
	235/30R22 XL	-	90	W	8 1/2J	600	1323	340	50
	245/30R22 XL	-	92	W	8 1/2J	630	1389	340	50
	255/30R22 XL	-	95	W	9J	690	1521	340	50
	265/30R22 XL	-	97	W	9 1/2J	730	1609	340	50
	265/35R22 XL	-	102	V	9 1/2J	850	1874	340	50
	265/40R22 XL	-	106	V	9 1/2J	950	2094	340	50
	285/25R22 XL	-	95	Y	10 1/2J	690	1521	340	50
	285/35R22 XL	-	106	W	10J	950	2094	340	50
	285/40R22 XL	-	110	V	10J	1060	2337	340	50
	285/45R22 XL	-	114	V	9 1/2J	1180	2601	340	50
	295/25R22 XL	-	97	W	10 1/2J	730	1609	340	50
	295/30R22 XL	-	103	V	10 1/2J	875	1929	340	50
	305/25R22 XL	-	99	Y	11J	775	1709	340	50
	305/40R22 XL	-	114	V	11J	1180	2601	340	50
	305/45R22 XL	-	118	V	10J	1320	2910	340	50
24									
	245/30R24 XL	-	94	W	8 1/2J	670	1477	340	50
	255/30R24 XL	-	97	W	9J	730	1609	340	50
	275/25R24 XL	-	96	W	10J	710	1565	340	50
	275/30R24 XL	-	101	W	9 1/2J	825	1819	340	50
	295/30R24 XL	-	104	V	10 1/2J	900	1984	340	50
	295/35R24 XL	-	110	V	10 1/2J	1060	2337	340	50
	305/35R24 XL	-	112	V	11J	1120	2469	340	50
26									
	255/30R26 XL	-	99	W	9J	775	1709	340	50
	275/25R26 XL	-	98	W	10J	750	1653	340	50
	295/30R26 XL	-	107	W	10 1/2J	975	2149	340	50
	305/30R26 XL	-	109	W	11J	1030	2271	340	50
28									
	275/25R28 XL	-	99	W	10J	775	1709	340	50
	295/25R28 XL	-	103	V	10 1/2J	875	1929	340	50
30									
	275/25R30 XL	-	101	W	10J	825	1819	340	50

FORCE PLUS

High handling performance UHP tire

- ▼ Excellent dry and wet handling performance.
- ▼ Asymmetric tread pattern design for better drainage performance inside and grip performance outside,excellent steering performance.



PCR/UHP

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
17	165/40R17 XL	-	72	V	6J	355	783	340	50
	185/35R17 XL	-	74	V	6 1/2J	375	827	340	50
	195/40R17 XL	-	81	V	7J	462	1019	340	50
18	165/40R18 XL	-	73	V	6J	365	805	340	50
	185/35R18 XL	-	76	H	6 1/2J	400	882	340	50
	195/35R18 XL	-	79	W	7J	437	963	340	50
	205/35R18 XL	-	81	H	7 1/2J	462	1019	340	50
20	205/30R20 XL	-	80	W	7 1/2J	450	992	340	50
	215/30R20 XL	-	82	W	7 1/2J	475	1047	340	50

AC300

Low-noise comfort tire

- ▼ The multi-level reinforcing rib design ensures the stiffness of the tire tread,thereby guaranteeing the handling performance of the tire.
- ▼ Four main grooves are designed to enhance the tire's water drainage performance.
- ▼ Highly dispersed silica,combined with a reticular misaligned sipe design,shortens the wet braking distance and enhances wet-weather safety.
- ▼ Five different pitch design,combined with intelligent simulation analysis, reduces the noise caused by tire vibration.



PCR/UHP

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
17									
	205/55R17 XL	-	95	W	6 1/2J	690	1521	340	50
	215/45R17 XL	-	91	V	7J	615	1356	340	50
	215/50R17 XL	-	95	V	7J	690	1521	340	50
	215/55R17	-	94	V	7J	670	1477	300	44
	225/45R17 XL	-	94	V	7 1/2J	670	1477	340	50
	225/50R17 XL	-	98	V	7J	750	1653	340	50
	225/55R17 XL	-	101	V	7J	825	1819	340	50
	235/45R17 XL	-	97	V	8J	730	1609	340	50
	235/50R17	-	96	V	7 1/2J	710	1565	300	44
	245/45R17 XL	-	99	V	8J	775	1709	340	50
	255/45R17	-	98	V	8 1/2J	750	1653	300	44
18									
	225/45R18 XL	-	95	V	7 1/2J	690	1521	340	50
	235/45R18	-	94	V	8J	670	1477	300	44
	245/45R18 XL	-	100	V	8J	800	1764	340	50

FORCE HP

All-season Tire

- ▼ Open shoulder groove design for superior safety and quiet ride.
- ▼ Straight center pattern blocks for more comfortable ride.



 PCR/HP

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
13									
	175/70R13 WR	-	82	H	5.00B	475	1047	300	44
	185/60R13 WR	-	80	H	5 1/2J	450	992	300	44
14									
	175/65R14	-	82	H	5J	475	1047	300	44
	185/60R14	-	82	H	5 1/2J	475	1047	300	44
	185/65R14	-	86	H	5 1/2J	530	1168	300	44
15									
	175/65R15	-	84	H	5J	500	1102	300	44
	185/55R15	-	82	V	6J	475	1047	300	44
	185/60R15	-	84	H	5 1/2J	500	1102	300	44
	185/65R15	-	88	H	5 1/2J	560	1235	300	44
	195/50R15	-	82	H	6J	475	1047	300	44
	195/55R15	-	85	V	6J	515	1135	300	44
	195/60R15	-	88	H	6J	560	1235	300	44
	195/65R15	-	91	H	6J	615	1356	300	44
16									
	185/60R16	-	86	H	5 1/2J	530	1168	350	51
	195/50R16	-	84	V	6J	500	1102	300	44
	195/55R16	-	87	V	6J	545	1201	300	44
	195/60R16	-	89	H	6J	580	1279	350	51

Three Grooves

FORCE HP

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
15									
	205/60R15	-	91	H	6J	615	1356	300	44
	205/65R15	-	94	H	6J	670	1477	300	44
	215/60R15	-	94	H	6 1/2J	670	1477	300	44
	215/75R15	-	100	S	6J	800	1764	300	44
	235/75R15	-	105	S	6 1/2J	925	2039	300	44
16									
	205/50R16	-	87	V	6 1/2J	545	1201	300	44
	205/55R16	-	91	V	6 1/2J	615	1356	300	44
	205/60R16	-	92	V	6J	630	1389	300	44
	205/65R16	-	95	H	6J	690	1521	300	44
	215/55R16 XL	-	97	H	7J	730	1609	340	50
	215/60R16	-	95	V	6 1/2J	690	1521	300	44
	215/65R16	-	98	H	6 1/2J	750	1653	300	44
	225/55R16	-	95	V	7J	690	1521	300	44
	225/60R16	-	98	H	6 1/2J	750	1653	300	44
	225/65R16	-	100	H	6 1/2J	800	1764	300	44
	225/70R16 XL	-	107	H	6 1/2J	975	2149	340	50
	235/60R16	-	100	H	7J	800	1764	300	44
	235/65R16	-	103	H	7J	875	1929	300	44
17									
	205/50R17 XL	-	93	V	6 1/2J	650	1433	340	50
	215/45R17 XL	-	91	V	7J	615	1356	340	50
	215/50R17 XL	-	95	V	7J	690	1521	340	50
	215/55R17	-	94	V	7J	670	1477	300	44
	215/60R17	-	96	H	6 1/2J	710	1565	300	44
	215/65R17	-	99	H	6 1/2J	775	1709	300	44
	225/45R17 XL	-	94	V	7 1/2J	670	1477	340	50
	225/50R17 XL	-	98	V	7J	750	1653	340	50
	225/55R17	-	97	V	7J	730	1609	300	44
	225/60R17	-	99	H	6 1/2J	775	1709	300	44
	225/65R17	-	102	H	6 1/2J	850	1874	300	44
	235/45R17 XL	-	97	V	8J	730	1609	340	50
	235/55R17	-	99	V	7 1/2J	775	1709	300	44
	235/60R17	-	102	H	7J	850	1874	300	44
	235/65R17	-	104	H	7J	900	1984	300	44
	245/45R17 XL	-	99	V	8J	775	1709	340	50
	245/50R17	-	99	V	7 1/2J	775	1709	300	44
18									
	225/40R18 XL	-	92	V	8J	630	1389	340	50
	225/45R18 XL	-	95	V	7 1/2J	690	1521	340	50
	225/50R18 XL	-	99	V	7J	775	1709	340	50
	225/55R18	-	98	V	7J	750	1653	300	44
	225/60R18	-	100	H	6 1/2J	800	1764	300	44
	235/40R18 XL	-	95	V	8 1/2J	690	1521	340	50
	235/45R18	-	94	V	8J	670	1477	300	44
	235/50R18	-	97	V	7 1/2J	730	1609	300	44
	235/55R18	-	100	V	7 1/2J	800	1764	300	44
	235/60R18	-	103	V	7J	875	1929	300	44
	245/40R18 XL	-	97	V	8 1/2J	730	1609	340	50
	245/45R18 XL	-	100	V	8J	800	1764	340	50
19									
	235/55R19	-	101	V	7 1/2J	825	1819	300	44
	245/40R19 XL	-	98	V	8 1/2J	750	1653	340	50
	255/50R19 XL	-	107	V	8J	975	2149	340	50
20									
	245/45R20	-	99	V	8J	775	1709	300	44
	245/50R20	-	102	V	7 1/2J	850	1874	300	44

Four Grooves

AS350

Comfort and Safety

- ▼ Open shoulder groove design for superior safety and quiet ride.
- ▼ Straight center pattern blocks for more comfortable ride.



PCR/HP

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
	175/65R15	-	84	H	5J	500	1102	300	44
	195/50R16 XL	-	88	V	6J	560	1235	340	50
	195/55R16	-	87	V	6J	545	1201	300	44

Three Grooves

AS350

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
15									
	185/55R15	-	82	V	6J	475	1047	300	44
	185/60R15	-	84	H	5 1/2J	500	1102	300	44
	185/65R15	-	88	H	5 1/2J	560	1235	300	44
	195/55R15	-	85	V	6J	515	1135	300	44
	195/60R15	-	88	V	6J	560	1235	300	44
	195/65R15	-	91	V	6J	615	1356	300	44
	205/65R15	-	94	V	6J	670	1477	300	44
	205/70R15	-	96	H	6J	710	1565	300	44
	215/70R15	-	98	S	6 1/2J	750	1653	300	44
16									
	195/60R16	-	89	H	6J	580	1279	300	44
	205/50R16 XL	-	91	V	6 1/2J	615	1356	340	50
	205/55R16	-	91	V	6 1/2J	615	1356	300	44
	205/60R16	-	92	V	6J	630	1389	300	44
	215/55R16	-	93	V	7J	650	1433	300	44
	215/60R16	-	95	H	6 1/2J	690	1521	300	44
	225/60R16	-	98	H	6 1/2J	750	1653	300	44

Four Grooves

WONDER HP

Low noise

- ▼ Low noise.
- ▼ Excellent wet performance.



PCR/HP

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
12									
	175/70R12	-	80	H	5.00B	450	992	300	44
13									
	185/60R13	-	80	V	5.50B	450	992	300	44
14									
	185/80R14	-	91	T	5J	615	1356	300	44

AE130

Economy and Long-mileage Tire

- ▼ Wider tread design--increases the tire wear performance.
- ▼ Three main groove design--Meets the drainage requirements of wet road.
- ▼ Big shoulder pattern block--improves abrasability and grip performance.



PCR/TAXI

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
14									
	175/65R14	-	82	H	5J	475	1047	300	44
	175/70R14	-	84	H	5J	500	1102	300	44
	185/65R14	-	86	H	5 1/2J	530	1168	300	44
	185/70R14	-	88	H	5 1/2J	560	1235	300	44
15									
	185/60R15	-	84	H	5 1/2J	500	1102	300	44
	185/65R15	-	88	H	5 1/2J	560	1235	300	44
	195/55R15 XL	-	89	H	6J	580	1279	340	50
	195/60R15	-	88	H	6J	560	1235	300	44
	195/65R15	-	91	H	6J	615	1356	300	44
	205/65R15	-	94	H	6J	670	1477	300	44
	205/70R15	-	96	H	6J	800	1764	300	44
	215/65R15 XL	-	100	H	6 1/2J	800	1764	340	50
16									
	195/55R16 XL	-	91	H	6J	615	1356	340	50

PARALLER 4X4 HP

Balanced Performance
Asymmetric Design

- ▼ Four circumferential grooves help channel water to resist hydroplaning and help maintain wet traction.
- ▼ Solid center-rib tread design provides continuous tread contact with the road to enhance steering response and handling.



SUV/HP/UHP

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
15									
	215/75R15	-	100	S	6J	800	1764	300	44
	235/70R15 XL	-	106	H	7J	950	2094	340	50
16									
	205/70R16	-	97	V	6J	730	1609	300	44
	215/65R16 XL	-	102	H	6 1/2J	850	1874	340	50
	215/70R16	-	100	H	6 1/2J	800	1764	300	44
	225/75R16	-	104	H	6J	900	1984	300	44
	235/70R16	-	106	H	7J	950	2094	300	44
	245/70R16 XL	-	111	H	7J	1090	2403	340	50
	265/70R16	-	112	H	8J	1120	2469	300	44
	275/70R16	-	114	H	8J	1180	2601	300	44

PARALLER 4X4 HP

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
17									
	215/60R17	-	96	H	6 1/2J	710	1565	300	44
	225/55R17 XL	-	101	V	7J	825	1819	340	50
	225/60R17	-	99	H	6 1/2J	775	1709	300	44
	225/65R17	-	102	H	6 1/2J	850	1874	300	44
	235/55R17 XL	-	103	W	7 1/2J	875	1929	340	50
	235/60R17 XL	-	106	V	7J	950	2094	340	50
	235/65R17 XL	-	108	V	7J	1000	2205	340	50
	235/70R17 XL	-	109	T	7J	1030	2271	340	50
	245/65R17 XL	-	111	H	7J	1090	2403	340	50
	255/60R17	-	106	H	7 1/2J	950	2094	300	44
	255/65R17	-	110	H	7 1/2J	1060	2337	300	44
	255/70R17	-	112	T	7 1/2J	1120	2469	300	44
	265/65R17	-	112	H	8J	1120	2469	300	44
18									
	225/60R18	-	100	H	6 1/2J	800	1764	300	44
	235/55R18 XL	-	104	V	7 1/2J	900	1984	340	50
	235/60R18 XL	-	107	V	7J	975	2149	340	50
	235/65R18	-	106	H	7J	950	2094	300	44
	245/60R18	-	105	V	7J	925	2039	300	44
	255/55R18 XL	-	109	V	8J	1030	2271	340	50
	255/65R18	-	111	H	7 1/2J	1090	2403	300	44
	255/70R18	-	113	T	7 1/2J	1150	2535	300	44
	265/60R18	-	110	H	8J	1060	2337	300	44
	265/65R18	-	114	H	8J	1180	2601	300	44
	265/70R18	-	116	T	8J	1250	2756	300	44
	275/65R18	-	116	H	8J	1250	2756	300	44
19									
	225/55R19	-	99	V	7J	775	1709	300	44
	255/55R19 XL	-	111	V	8J	1090	2403	340	50

A51

Comfortable SUV tire



- ▼ Low noise to offer a quiet ride.
- ▼ Wide tread surface for superior comfortable ride.



SUV/HP/UHP (OE)

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
16									
	205/60R16 XL	-	96	V	6J	710	1565	340	50
	215/65R16	-	98	V	6 1/2J	750	1653	300	44
17									
	215/60R17	-	96	V	6 1/2J	710	1565	300	44
	225/60R17	-	99	H	6 1/2J	775	1709	300	44
	225/65R17	-	102	V	6 1/2J	850	1874	300	44
	235/55R17	-	99	V	7 1/2J	775	1709	300	44
	235/65R17 XL	-	108	H	7J	1000	2205	340	50
	245/65R17	-	107	H	7J	975	2149	300	44
	235/60R17	-	102	V	7J	850	1874	300	44
	285/65R17	-	116	H	8 1/2J	1250	2756	300	44

A51

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
18									
	215/50R18 XL	-	96	V	7J	710	1565	340	50
	215/55R18	-	95	V	7J	690	1521	300	44
	225/55R18	-	98	V	7J	750	1653	300	44
	225/60R18	-	100	H	6 1/2J	800	1764	300	44
	235/50R18	-	97	V	7 1/2J	730	1609	300	44
	235/55R18	-	100	V	7 1/2J	800	1764	300	44
	235/60R18 XL	-	107	V	7J	975	2149	340	50
	235/65R18	-	106	H	7J	950	2094	300	44
	245/60R18	-	105	H	7J	925	2039	300	44
	275/45R18 XL	-	107	W	9J	975	2149	340	50
20									
	235/55R20 XL	-	105	W	7 1/2J	925	2039	340	50
	255/55R20 XL	-	110	V	8J	1060	2337	340	50
	265/40R20 XL	-	104	W	9 1/2J	900	1984	340	50
	275/50R20 XL	-	113	V	8 1/2J	1150	2535	340	50
	285/45R20 XL	-	112	W	9 1/2J	1120	2469	340	50
21									
	275/40R21 XL	-	107	W	9 1/2J	975	2149	340	50
	275/45R21 XL	-	110	W	9J	1060	2337	340	50
	295/40R21 XL	-	111	W	10 1/2J	1090	2403	340	50
22									
	275/40R22	-	107	W	9 1/2J	975	2149	340	50

PARALLER H/T

All-season Performance
Long&Regular Wear

- ▼ Noise reduction, handling performance.
- ▼ Braking & Traction Performance:
Long interlocking center rib and wide shoulder blocks maximize the traction and provide short braking distances.



CROSS-COUNTRY/HT

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
15									
	235/75R15 XL	-	109	T	6 1/2J	1030	2271	340	50
16									
	215/70R16	-	100	T	6 1/2J	800	1764	300	44
	225/70R16	-	103	T	6 1/2J	875	1929	300	44
	235/70R16	-	106	T	7J	950	2094	300	44
	235/80R16	-	109	T	6 1/2J	1030	2271	300	44
	245/70R16	-	107	T	7J	975	2149	300	44
	245/75R16	-	111	T	7J	1090	2403	300	44
	255/70R16	-	111	T	7 1/2J	1090	2403	300	44
	265/70R16	-	112	T	8J	1120	2469	300	44
	265/75R16	-	116	T	7 1/2J	1250	2756	300	44
	LT215/85R16	10PR	115/112	S	6J	D 1120 S 1215	D 2470 S 2680	550	80
	LT225/75R16	10PR	115/112	S	6J	D 1120 S 1215	D 2470 S 2680	550	80
	LT235/65R16	10PR	121/119	R	7J	D 1360 S 1450	D 3000 S 3195	550	80
	LT235/85R16	10PR	120/116	R	6 1/2J	D 1285 S 1400	D 2835 S 3085	550	80
	LT245/75R16	10PR	120/116	R	7J	D 1260 S 1380	D 2778 S 3042	550	80
	LT265/75R16	10PR	123/120	R	7 1/2J	D 1400 S 1550	D 3085 S 3415	550	80
17									
	235/65R17	-	104	T	7J	900	1984	300	44
	245/65R17	-	107	T	7J	975	2149	300	44
	245/70R17	-	110	T	7J	1060	2337	300	44
	265/65R17	-	112	T	8J	1120	2469	300	44
	265/70R17	-	115	T	8J	1215	2679	300	44
	LT265/70R17	10PR	121/118	R	8J	D 1320 S 1450	D 2910 S 3195	550	80
19									
	275/50R19 XL	-	112	V	8 1/2J	1120	2469	340	50
20									
	265/50R20 XL	-	111	V	8 1/2J	1090	2403	340	50
	275/55R20 XL	-	117	T	8 1/2J	1285	2833	340	50
	275/60R20	-	115	T	8J	1215	2679	300	44

HT601

SUV Tire for Urban Road Use,with
Low Noise and Good Dry/wet Performance

- ▼ Optimized pattern pitches to offer more comfortable and quiet ride.
- ▼ Big pattern blocks design to improve wear resistance ability.



CROSS-COUNTRY/HT

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
16									
	245/70R16 XL	-	111	H	7J	1090	2403	340	50
	265/70R16	-	112	H	8J	1120	2469	300	44
17									
	225/60R17 XL	-	103	H	6 1/2J	875	1929	340	50
	225/65R17	-	102	H	6 1/2J	850	1874	300	44

PARALLER A/T

On & Off Performance
Snow /Ice Traction

- ▼ Excellent traction off-road and wet performance.
- ▼ Closed shoulder design ensures long tread life and resists uneven wear.
- ▼ Designed to combine a quiet highway ride and long tread life with all-terrain performance.



CROSS-COUNTRY/AT

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
14									
	175/80R14	-	88	T	5J	560	1235	300	44
15									
	205/60R15	-	91	H	6J	615	1356	300	44
	205/65R15	-	94	H	6J	670	1477	300	44
	205/70R15	-	96	T	6J	710	1565	300	44
	235/75R15XLOWL	-	109	T	6 1/2J	1030	2271	340	50
	265/70R15OWL	-	112	T	8J	1120	2469	300	44
	31X10.50R15LTOWL 6PR		109	R	8 1/2J	1030	2270	350	51
	31X10.50R15LTOWL 6PR		109	Q	8 1/2J	1030	2270	350	51
	LT235/75R15OWL 6PR		104/101	R	6 1/2J	D 825 S 900	D 1820 S 1985	350	50
	LT235/75R15OWL 6PR		104/101	Q	6 1/2J	D 825 S 900	D 1820 S 1985	350	50

PARALLER A/T

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
16									
	205/60R16	-	92	H	6J	630	1389	300	44
	215/65R16	-	98	T	6 1/2J	750	1653	300	44
	235/70R16OWL	-	106	T	7J	950	2094	300	44
	245/70R16XLOWL	-	111	T	7J	1090	2403	340	50
	245/75R16OWL	-	111	T	7J	1090	2403	300	44
	255/70R16OWL	-	111	S	7 1/2J	1090	2403	300	44
	265/70R16OWL	-	112	T	8J	1120	2469	300	44
	265/75R16OWL	-	116	T	7 1/2J	1250	2756	300	44
	LT215/85R16OWL 10PR	115/112	Q	6J	D 1120 S 1215 D 2470 S 2680	550	80		
	LT225/75R16OWL 10PR	115/112	Q	6J	D 1120 S 1215 D 2470 S 2680	550	80		
	LT235/85R16OWL 10PR	120/116	S	6 1/2J	D 1260 S 1380 D 2778 S 3042	550	80		
	LT235/85R16OWL 10PR	120/116	Q	6 1/2J	D 1260 S 1380 D 2778 S 3042	550	80		
	LT245/75R16OWL 10PR	120/116	Q	7J	D 1260 S 1380 D 2778 S 3042	550	80		
	LT265/75R16OWL 10PR	123/120	R	7 1/2J	D 1400 S 1550 D 3086 S 3417	550	80		
	LT285/75R16OWL 10PR	126/123	R	8J	D 1550 S 1700 D 3415 S 3750	550	80		
	LT305/70R16OWL 10PR	124/121	R	9J	D 1450 S 1600 D 3195 S 3525	450	65		
17									
	245/65R17OWLXL	-	111	T	7J	1090	2403	340	50
	245/70R17OWL	-	110	S	7J	1060	2337	300	44
	265/65R17OWL	-	112	T	8J	1120	2469	300	44
	265/70R17OWL	-	115	T	8J	1215	2679	300	44
	285/70R17OWL	-	116	T	8 1/2J	1250	2756	300	44
	LT235/80R17OWL 10PR	120/117	R	6 1/2J	D 1285 S 1400 D 2835 S 3085	550	80		
	LT235/80R17OWL 10PR	120/117	Q	6 1/2J	D 1285 S 1400 D 2835 S 3085	550	80		
	LT245/70R17OWL 10PR	119/116	Q	7J	D 1250 S 1360 D 2755 S 3000	550	80		
	LT245/75R17OWL 10PR	121/118	R	7J	D 1320 S 1450 D 2910 S 3195	550	80		
	LT265/70R17OWL 10PR	121/118	R	8J	D 1320 S 1450 D 2910 S 3195	550	80		
	LT265/70R17OWL 10PR	121/118	Q	8J	D 1320 S 1450 D 2910 S 3195	550	80		
	LT285/70R17OWL 8PR	121/118	S	8 1/2J	D 1320 S 1450 D 2910 S 3195	450	65		
	LT285/70R17OWL 10PR	121/118	S	8 1/2J	D 1320 S 1450 D 2910 S 3195	450	65		
	LT305/70R17OWL 8PR	119/116	R	9J	D 1250 S 1360 D 2755 S 3000	350	50		

PARALLER A/T

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
18									
	225/60R18	-	104	H	6 1/2J	900	1984	300	44
	255/70R18 OWL	-	113	S	7 1/2J	1150	2535	300	44
	265/70R18 OWL	-	116	T	8J	1250	2756	300	44
	275/65R18 OWL	-	116	T	8J	1250	2756	300	44
	LT265/65R18 OWL 10PR	122/119	Q	8J	D 1360 S 1500	D 3000 S 3305	550	80	
	LT265/70R18 OWL 10PR	124/121	S	8J	D 1450 S 1600	D 3195 S 3525	550	80	
	LT275/65R18 OWL 10PR	123/120	S	8J	D 1400 S 1550	D 3085 S 3415	550	80	
	LT275/70R18 OWL 10PR	125/122	S	8J	D 1500 S 1650	D 3305 S 3640	550	80	
	LT305/60R18 OWL 10PR	121/118	R	9J	D 1320 S 1450	D 2910 S 3195	450	65	
19									
	255/55R19	-	107	H	8J	975	2149	300	44
20									
	275/55R20 OWL	-	113	S	8 1/2J	1150	2535	300	44
	275/60R20 OWL	-	115	T	8J	1215	2679	300	44
	LT275/55R20 OWL 10PR	120/117	Q	8 1/2J	D 1285 S 1400	D 2835 S 3085	550	80	
	LT275/60R20 OWL 10PR	123/120	Q	8J	D 1400 S 1550	D 3085 S 3415	550	80	
	LT275/65R20 OWL 10PR	126/123	R	8J	D 1550 S 1700	D 3415 S 3750	550	80	
	LT285/55R20 OWL 10PR	122/119	S	9J	D 1360 S 1500	D 3000 S 3305	550	80	
	LT305/55R20 OWL 10PR	121/118	R	9 1/2J	D 1320 S 1450	D 2910 S 3195	450	65	

AT760

All-terrain tire

- ▼ Open pattern groove design to provide superior off-road traction ability.
- ▼ Deep pattern groove design to improve wear resistance and off-road performance.



CROSS-COUNTRY/AT

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
15									
	LT215/75R15OWL 8PR		106/103 S		6J	D875 S950	D1930 S2095	450	65
	LT235/75R15OWL 8PR		110/107 S		6 1/2J	D975 S1060	D2149 S2337	450	65

SUMMER

ALL SEASON (M+S)

4S (GPMSE)

WINTER

AT760

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
16									
	235/70R16OWL	-	106	T	7J	950	2094	300	44
	245/70R16OWL	-	107	T	7J	975	2149	300	44
	LT265/70R16OWL	8PR	117/114	S	8J	D1180 S1285	D2600 S2835	450	65
17									
	LT265/65R17OWL	10PR	120/117	S	8J	D1285 S1400	D2835 S3085	550	80
	235/65R17OWL	-	104	T	7J	900	1984	300	44
18									
	265/60R18XLOWL	-	114	H	8J	1180	2601	340	50
	285/60R18OWL	-	116	T	8 12J	1250	2756	300	44
19									
	255/50R19		107	H	8J	975	2149	340	50

AT Z5 PLUS

Excellent wet traction,and mud traction performance
Tearing and abrasions resistance

- ▼ Continuous pattern block design to maximize tread contact with the ground.
- ▼ The unique pattern improves the vehicle stability and handling ability.
- ▼ Large groove volumes to maximize hydroplaning resistance,wet traction,and mud traction performance.
- ▼ High sipe density for excellent handling,snow,and wet traction.
- ▼ Tread shoulder not only enhances traction but protects against cutting,tearing and abrasions.



CROSS-COUNTRY/AT

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
17									
	265/65R17	-	112	S	8J	1120	2469	300	44

PARALLER M/T

Mud Terrain

Muddy ruts for additional off-road traction



- ▼ Advanced tread compound as well as muddy ruts for additional off-road traction.
- ▼ Large & Strong block and deep tread enhance grip in tough terrains.



PARALLER M/T



CROSS-COUNTRY/MT

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
15									
	265/70R15	-	112	Q	8J	1120	2469	300	44
	265/75R15	-	112	Q	7 1/2J	1120	2469	300	44
	LT215/75R15	6PR	100/97	Q	6J	D 730 S 800	D 1610 S 1765	350	50
	LT235/75R15	6PR	104/101	Q	6 1/2J	D 825 S 900	D 1820 S 1985	350	50
	30X9.50R15LT	6PR	104	Q	7 1/2J	900	1985	350	50
	31X10.50R15LT	6PR	109	Q	8 1/2J	1030	2270	350	51
	33X12.50R15LT	6PR	108	Q	10J	1000	2205	300	44
	35X12.50R15LT	6PR	113	Q	10J	1150	2535	300	35
16									
	205R16LT	8PR	110/108	Q	6J	D 1000 S 1060	D 2205 S 2335	450	65
	LT225/75R16	8PR	110/107	Q	6J	D 975 S 1060	D 2150 S 2335	450	65
	LT235/85R16 OWL	10PR	120/116	S	6 1/2J	D 1260 S 1380	D 2778 S 3042	550	80
	LT245/75R16	10PR	120/116Q	Q	7J	D 1260 S 1380	D 2778 S 3042	550	80
	LT255/70R16	8PR	115/112	Q	7 1/2J	D 1120 S 1215	D 2470 S 2680	450	65
	LT265/70R16	6PR	110/107	Q	8J	D 975 S 1060	D 2150 S 2335	350	50
	LT265/75R16	10PR	123/120	Q	7 1/2J	D 1400 S 1550	D 3085 S 3415	550	80
	LT285/75R16	10PR	126/123	Q	8J	D 1550 S 1700	D 3415 S 3750	550	80
	LT305/70R16	10PR	124/121	Q	9J	D 1450 S 1600	D 3195 S 3525	450	65
	LT315/75R16	10PR	127/124	Q	8 1/2J	D 1600 S 1750	D 3525 S 3860	450	65
	LT375/65R16	8PR	126/123	Q	11J	D 1550 S 1700	D 3415 S 3750	350	50
17									
	LT235/80R17	10PR	120/117	Q	6 1/2J	D 1285 S 1400	D 2835 S 3085	550	80
	LT265/65R17	10PR	120/117	Q	8J	D 1285 S 1400	D 2835 S 3085	550	80
	LT265/70R17	10PR	121/118	Q	8J	D 1320 S 1450	D 2910 S 3195	550	80
	LT285/70R17	10PR	121/118	Q	8 1/2J	D 1320 S 1450	D 2910 S 3195	550	80
	LT295/70R17	10PR	121/118	Q	8 1/2J	D 1320 S 1450	D 2910 S 3195	550	80
	LT305/65R17	10PR	121/118	Q	9J	D 1320 S 1450	D 2910 S 3195	450	65
	LT305/70R17	8PR	119/116	Q	9J	D 1250 S 1360	D 2755 S 3000	350	50
	LT315/70R17	10PR	121/118	Q	9 1/2J	D 1320 S 1450	D 2910 S 3195	450	65
	33X12.50R17LT	10PR	120	Q	10J	1400	3085	450	65
	35X12.50R17LT	10PR	121	Q	10J	1450	3195	450	65
	37X12.50R17LT	8PR	124	Q	10J	1600	3525	350	50
	37X13.50R17LT	10PR	121	Q	11J	1450	3195	450	65
	37X13.50R17LT	14PR	137	M	11J	2300	5070	650	95
	40X13.50R17LT	8PR	121	Q	11J	1450	3195	350	50

PARALLER M/T

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
18									
	LT275/70R18	10PR	125/122	Q	8J	D 1500S 1650	D 3305S 3640	550	80
	LT295/70R18	10PR	129/126	Q	8 1/2J	D 1700S 1850	D 3750S 4080	550	80
	LT305/60R18	10PR	121/118	Q	9J	D 1320S 1450	D 2910S 3195	450	65
	LT305/70R18	10PR	126/123	Q	9J	D 1550S 1700	D 3415S 3750	450	65
	33X12.50R18LT	10PR	118	Q	10J	1320	2910	450	65
	33X12.50R18LT	12PR	122	Q	10J	1500	3305	550	80
	35X12.50R18LT	8PR	118	Q	10J	1320	2910	350	50
	35X12.50R18LT	10PR	123	Q	10J	1550	3415	450	65
	35X12.50R18LT	12PR	128	Q	10J	1800	3970	550	80
	37X13.50R18LT	8PR	124	Q	11J	1600	3525	350	50
20									
	LT285/55R20	8PR	117/114	Q	9J	D 1180S 1285	D 2600S 2835	450	65
	LT285/55R20	10PR	122/119	Q	9J	D 1360S 1500	D 3000S 3305	550	80
	LT285/65R20	10PR	127/124	Q	8 1/2J	D 1600S 1750	D 3525S 3860	550	80
	LT295/60R20	10PR	126/123	Q	8 1/2J	D 1550S 1700	D 3415S 3750	550	80
	LT305/55R20	10PR	121/118	Q	9 1/2J	D 1320S 1450	D 2910S 3195	450	65
	33X12.50R20LT	10PR	114	Q	10J	1180	2600	450	65
	33X12.50R20LT	12PR	119	Q	10J	1360	3000	550	80
	35X12.50R20LT	10PR	121	Q	10J	1450	3195	450	65
	35X12.50R20LT	12PR	125	Q	10J	1650	3640	550	80
	36X15.50R20LT	10PR	126	Q	12 1/2J	1700	3750	450	65
	37X13.50R20LT	10PR	127	Q	11J	1750	3860	450	65
	37X13.50R20LT	12PR	128	Q	11J	1800	3970	550	80
	38X15.50R20LT	8PR	125	Q	12 1/2J	1650	3640	350	50
	40X14.50R20LT	8PR	128	Q	11 1/2J	1800	3970	350	50
22									
	33X12.50R22LT	10PR	109	Q	10J	1030	2270	450	65
	33X12.50R22LT	12PR	114	Q	10J	1180	2600	550	80
	35X12.50R22LT	10PR	117	Q	10J	1285	2835	450	65
	35X12.50R22LT	12PR	121	Q	10J	1450	3195	550	80
	37X13.50R22LT	10PR	123	Q	11J	1550	3415	450	65
	37X13.50R22LT	12PR	128	Q	11J	1800	3970	550	80
24									
	33X12.50R24LT	10PR	101	Q	11 1/2J	825	1820	450	65
	37X13.50R24LT	10PR	120	Q	11J	1400	3085	450	65
26									
	37X13.50R26LT	10PR	114	Q	11J	1180	2600	450	65

SHARP

Mud-Terrain Tire

- ▼ Aggressive tread pattern design for superior mud shedding and desilting ability.
- ▼ Wide horizontal groove design for better off-road performance and more traction.



CROSS-COUNTRY/MT

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
15									
	LT215/75R15OWL	6PR	100/97	Q	6J	D730S800	D1610 S1765	350	51
	LT235/75R15OWL	6PR	104/101	Q	6 1/2J	D825S900	D1820 S1985	350	51
16									
	LT265/75R16OWL	10PR	123/120	Q	7 1/2J	D1400S1550	D3085 S3415	550	80
17									
	LT265/70R17OWL	10PR	121/118	Q	8J	D1320S1450	D2910 S3195	550	80

AR939

Commercial tire with high endurance and wear performance

- ▼ Effectively improve the endurance of the tyre with the new construction design.
- ▼ Excellent stability.
- ▼ Great grip performance and driving force of turning.



RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
14									
	175/70R14LT	8PR	93/90	Q	5J	D600 S650	D1325 S1435	450	65
	185R14LT	8PR	102/100	Q	5 1/2J	D800 S850	D1765 S1875	450	65
15									
	195/70R15LT	8PR	99/96	S	6J	D710 S775	D1565 S1710	450	65
	195R15LT	8PR	106/104	R	5 1/2J	D900 S950	D1985 S2095	450	65
	215/70R15LT	8PR	104/101	Q	6 1/2J	D825 S900	D1820 S1985	450	65
	225/70R15LT	8PR	107/103	Q	6 1/2J	D875 S975	D1930 S2150	450	65

GREEN2 4S

All Season High Performance

- ▼ All weather(3PMS).
- ▼ Excellent handling.
- ▼ Low rolling resistance for better fuel efficiency.
- ▼ All season tire which is applicable to different weather and road conditions.



PCR/HP

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
13									
	155/65R13	-	73	T	4.50B	365	805	300	44
	155/80R13	-	79	T	4.50B	437	963	300	44
14									
	165/70R14	-	81	T	5J	462	1019	300	44
	175/65R14	-	82	T	5J	475	1047	300	44
	185/60R14 XL	-	86	H	5 1/2J	530	1168	340	50
	185/65R14	-	86	H	5 1/2J	530	1168	300	44

SUMMER

ALL SEASON (M+S)

4S (3PM/5F)

WINTER

GREEN2 4S

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
15									
	175/65R15	–	84	H	5J	500	1102	300	44
	185/55R15 XL	–	86	H	6J	530	1168	340	50
	185/60R15 XL	–	88	V	5 1/2J	560	1235	340	50
	185/65R15 XL	–	92	V	5 1/2J	630	1389	340	50
	195/55R15 XL	–	89	V	6J	580	1279	340	50
	195/60R15 XL	–	92	V	6J	630	1389	340	50
	195/65R15 XL	–	95	V	6J	690	1521	340	50
	205/65R15 XL	–	99	V	6J	775	1709	340	50
16									
	195/55R16 XL	–	91	H	6J	615	1356	340	50
	205/55R16 XL	–	94	V	6 1/2J	670	1477	340	50
	205/60R16 XL	–	96	V	6J	710	1565	340	50
	215/55R16 XL	–	97	V	7J	730	1609	340	50
	215/60R16 XL	–	99	V	6 1/2J	775	1709	340	50
	215/65R16 XL	–	102	V	6 1/2J	850	1874	340	50
17									
	205/50R17 XL	–	93	V	6 1/2J	650	1433	340	50
	215/50R17 XL	–	95	V	7J	690	1521	340	50
	215/55R17 XL	–	98	V	7J	750	1653	340	50
	215/60R17 XL	–	100	V	6 1/2J	800	1764	340	50
	225/50R17 XL	–	98	V	7J	750	1653	340	50
	225/45R17 XL	–	94	V	7 1/2J	670	1477	340	50
	225/55R17 XL	–	101	V	7J	825	1819	340	50
	235/55R17 XL	–	103	V	7 1/2J	875	1929	340	50
18									
	235/55R18 XL	–	104	V	7 1/2J	900	1984	340	50
19									
	225/55R19	–	99	V	7J	775	1709	300	44



WINTER



► *Winter*

AW31..... PAGE 73

I5..... PAGE 75

I3..... PAGE 77

AW31

Tire dedicated for car on ice-snow ground
Super ability Run-Flat Winter tire dedicated
for luxury brand

AW31

- ▼ Outstanding grip and traction performance on ice and snow surface with asymmetric tread pattern design.
- ▼ Special suction and drainage line design,fast water film guide,providing excellent grip.
- ▼ Complex soft tread compound and 3D sipes technology to promote handling performance on ice and snow condition.

AW31RFT

- ▼ Special suction and drainage line design,fast water film guide,providing excellent grip.
- ▼ Complex soft tread compound and 3D sipes technology to promote handling performance on ice and snow condition.
- ▼ Carry linglong LRS run-flat technology,for driving safety in winter.



PCR/UHP

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
15									
	175/65R15 XL	-	84	S	5J	500	1102	300	44
	185/60R15	-	84	S	5 1/2J	500	1102	300	44
	185/65R15	-	88	S	5 1/2J	560	1235	300	44
	195/60R15	-	88	S	6J	560	1235	300	44
	195/65R15	-	91	S	6J	615	1356	300	44
	215/65R15 XL	-	100	S	6 1/2J	800	1764	340	50
	215/70R15	-	98	S	6 1/2J	750	1653	300	44
16									
	185/55R16 XL	-	87	S	6J	545	1201	340	50
	205/50R16 XL	-	91	S	6 1/2J	615	1356	340	50
	205/55R16	-	91	S	6 1/2J	615	1356	300	44
	205/60R16	-	92	S	6J	630	1389	300	44
	215/60R16	-	95	S	6 1/2J	690	1521	300	44

AW31

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
17									
	205/50R17 XL	-	93	S	6 1/2J	650	1433	340	50
	215/45R17 XL	-	91	S	7J	615	1356	340	50
	215/55R17	-	94	S	7J	670	1477	300	44
	225/50R17	-	94	S	7J	670	1477	300	44
	225/55R17	-	97	S	7J	730	1609	300	44
18									
	225/40R18	-	92	S	8J	630	1389	300	44
	235/45R18 XL	-	98	S	8J	750	1653	340	50
	245/40R18 XL	-	97	S	8 1/2J	730	1609	340	50
	245/50R18 XL	-	104	S	7 1/2J	900	1984	340	50
	255/45R18 XL	-	103	S	8 1/2J	875	1929	340	50
19									
	225/45R19 XL	-	96	S	7 1/2J	710	1565	340	50
	245/40R19 XL	-	98	S	8 1/2J	750	1653	340	50
	245/45R19	-	98	S	8J	750	1653	300	44
	245/45R19 XL	-	102	S	8J	850	1874	340	50
	255/40R19 XL	-	100	S	9J	800	1764	340	50
	255/45R19 XL	-	104	S	8 1/2J	900	1984	340	50
	275/35R19	-	96	S	9 1/2J	710	1565	300	44
	275/35R19 XL	-	100	S	9 1/2J	800	1764	340	50
	275/40R19 XL	-	105	S	9 1/2J	925	2039	340	50
20									
	245/40R20 XL	-	99	S	8 1/2J	775	1709	340	50
	275/35R20 XL	-	102	S	9 1/2J	850	1874	340	50

AW31RFT

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
19									
	245/40R19	–	94	S	8 1/2J	670	1477	350	51
	245/45R19	–	98	S	8J	750	1653	350	51
	275/35R19	–	96	S	9 1/2J	710	1565	350	51
	275/40R19 XL	–	101	S	9 1/2J	825	1819	350	51

I5

Tires for SUV on ice-snow ground specially
RFT technology available

I5

- ▼ Fine lines on the tire surface and densely groove design to provide a strong power for ice and snow road.
- ▼ Outstanding grip performance on ice and snow surface with sput Hole design.
- ▼ Complex soft tread compound and 3D sipes technology to promote handling performance on ice and snow condition.

I5RFT

- ▼ Fine lines on the tire surface and densely groove design to provide a strong power for ice and snow road.
- ▼ Outstanding grip performance on ice and snow surface with sput Hole design.
- ▼ Complex soft tread compound and 3D sipes technology to promote handling performance on ice and snow condition.
- ▼ Carry linglong LRS run-flat technology,for driving safety in winter.



SUV/HP/UHP



RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
15									
	205/70R15	–	96	S	6J	710	1565	300	44
	215/75R15	–	100	S	6J	800	1764	300	44
	235/75R15	–	105	S	6 1/2J	925	2039	300	44
16									
	215/65R16	–	98	S	6 1/2J	750	1653	300	44
	215/70R16	–	100	S	6 1/2J	800	1764	300	44
	225/70R16	–	103	S	6 1/2J	875	1929	300	44
	235/60R16 XL	–	104	S	7J	900	1984	340	50
	235/70R16	–	106	S	7J	950	2094	300	44
	245/70R16	–	107	S	7J	975	2149	300	44
	265/70R16	–	112	S	8J	1120	2469	300	44
	275/70R16	–	114	S	8J	1180	2601	300	44
17									
	205/55R17	–	91	S	6 1/2J	730	1356	300	44
	215/60R17	–	96	S	6 1/2J	710	1565	300	44
	215/65R17	–	99	S	6 1/2J	775	1709	300	44
	225/60R17	–	99	S	6 1/2J	775	1709	300	44
	225/65R17	–	102	S	6 1/2J	850	1874	300	44
	235/65R17	–	104	S	7J	900	1984	300	44
	245/65R17	–	107	S	7J	975	2149	300	44
	255/60R17	–	106	S	7 1/2J	950	2094	300	44
	265/65R17	–	112	S	8J	1120	2469	300	44
	275/65R17	–	115	S	8J	1215	2679	300	44
	285/65R17	–	116	S	8 1/2J	1250	2756	300	44

I5

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
18									
	215/55R18 XL	-	99	S	7J	775	1709	340	50
	225/55R18	-	98	S	7J	750	1653	300	44
	225/60R18	-	100	S	6 1/2J	800	1764	300	44
	235/50R18	-	97	S	7 1/2J	730	1609	300	44
	235/55R18	-	100	S	7 1/2J	800	1764	300	44
	235/60R18	-	103	S	7J	875	1929	300	44
	235/65R18	-	106	S	7J	950	2094	300	44
	245/60R18	-	105	S	7J	925	2039	300	44
	255/55R18 XL	-	109	S	8J	1030	2271	340	50
	265/60R18	-	110	S	8J	1060	2337	300	44
	285/60R18	-	116	S	8 1/2J	1250	2756	300	44
19									
	225/55R19	-	99	S	7J	775	1709	300	44
	235/50R19	-	99	S	7 1/2J	775	1709	300	44
	235/55R19 XL	-	105	S	7 1/2J	925	2039	340	50
	235/60R19	-	103	S	7J	875	1929	300	44
	245/55R19	-	103	S	7 1/2J	875	1929	300	44
	255/50R19 XL	-	107	S	8J	975	2149	340	50
	255/55R19	-	107	S	8J	975	2149	300	44
	275/45R19 XL	-	108	S	9J	1000	2205	340	50
	265/50R19	-	106	S	8 1/2J	950	2094	300	44
20									
	235/55R20	-	102	S	7 1/2J	850	1874	300	44
	245/45R20	-	99	S	8J	775	1709	300	44
	245/50R20	-	102	S	7 1/2J	850	1874	300	44
	255/40R20	-	97	S	9J	730	1609	300	44
	255/45R20	-	101	S	8 1/2J	825	1819	300	44
	255/50R20 XL	-	109	S	8J	1030	2271	340	50
	255/55R20 XL	-	110	S	8J	1060	2337	340	50
	275/40R20	-	102	S	9 1/2J	850	1874	300	44
	275/45R20 XL	-	110	S	9J	1060	2337	340	50
	275/50R20 XL	-	113	S	8 1/2J	1150	2535	340	50
	275/55R20	-	113	S	8 1/2J	1150	2535	300	44
	285/50R20	-	112	S	9J	1120	2469	300	44
	315/35R20	-	106	S	11J	950	2094	300	44
21									
	265/45R21	-	104	S	9J	900	1984	300	44
	275/45R21	-	107	S	9J	975	2149	300	44
22									
	275/40R22 XL	-	107	S	9 1/2J	975	2149	340	50

I5 RFT

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
19									
	255/50R19	–	103	S	8 J	875	1929	350	51

I3

Tire dedicated for car on ice-snow ground
RFT technology available

I3

- ▼ Outstanding grip and traction performance on ice and snow surface with directional tread pattern design.
- ▼ Directional grooves to help evacuate snow and mud.
- ▼ Complex soft tread compound and 3D sipes technology to promote handling performance on ice and snow condition.

I3RFT

- ▼ Outstanding grip and traction performance on ice and snow surface with directional tread pattern design.
- ▼ Directional grooves to help evacuate snow and mud.
- ▼ Carry linglong LRS run-flat technology, for driving safety in winter.



PCR/HP

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
	165/70R14	–	81	S	5J	462	1019	300	44
	175/65R14	–	82	S	5J	475	1047	300	44
	175/70R14	–	84	S	5J	500	1102	300	44
	185/60R14	–	82	S	5 1/2J	475	1047	300	44
	185/65R14	–	86	S	5 1/2J	530	1168	300	44
	185/70R14	–	88	S	5 1/2J	560	1235	300	44
	185/55R15	–	82	S	6J	475	1047	300	44
	185/60R15	–	84	S	5 1/2J	500	1102	300	44
	185/65R15	–	88	S	5 1/2J	560	1235	300	44
	195/55R15	–	85	S	6J	515	1135	300	44
	195/60R15	–	88	S	6J	560	1235	300	44
	195/65R15	–	91	S	6J	615	1356	300	44
	205/65R15	–	94	S	6J	670	1477	300	44

I3

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
16									
	195/55R16 XL	-	91	S	6J	615	1356	340	50
	195/60R16	-	89	S	6J	580	1279	300	44
	205/55R16	-	91	S	6 1/2J	615	1356	300	44
	205/60R16	-	92	S	6J	630	1389	300	44
	215/55R16	-	93	S	7J	650	1433	300	44
	215/60R16	-	95	S	6 1/2J	690	1521	300	44
	225/55R16	-	95	S	7J	690	1521	300	44
	225/60R16	-	98	S	6 1/2J	750	1653	300	44
17									
	215/50R17 XL	-	95	S	7J	690	1521	340	50
	215/55R17	-	94	S	7J	670	1477	300	44
	225/45R17 XL	-	94	S	7 1/2J	670	1477	340	50
	225/50R17	-	94	S	7J	670	1477	300	44
	225/55R17	-	97	S	7J	730	1609	300	44
	235/45R17 XL	-	97	S	8J	730	1609	340	50
	235/50R17	-	96	S	7 1/2J	710	1565	300	44
	235/55R17	-	99	S	7 1/2J	775	1709	300	44
	245/45R17 XL	-	99	S	8J	775	1709	340	50
18									
	225/45R18 XL	-	95	S	7 1/2J	690	1521	340	50
	245/45R18	-	96	S	8J	710	1565	300	44

I3RFT

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
18									
	245/45R18	-	96	S	8J	710	1565	300	44