



PCR TIRE CATALOGUE





CONTENTS

COMPANY INTRODUCTION P 05

Abundant sports marketing sponsorship P 07

Internationalization of Production P 09

Internationalization of R&D P 13

Summer P 15

All Season (M+S)& All Weather(3PMSF) P 37

Winter P 67

COMPANY INTRODUCTION

LINGLONG



Shandong Linglong Tyre Co., Ltd. is a technical tire manufacturer integrating tire design, development, manufacturing and sales.

Founded in 1975, the company has seven R&D centers, seven manufacturing bases across the world currently and over 17,783 employees, with its products widely used on passenger vehicles, commercial vehicles, and engineering machinery vehicles. It has built diversified brand system for different markets.

Including **LINGLONG**, **ATLAS**, **LEAO** and **EVOLUXX** etc. Linglong Tire had successful access to the A share market on July 6, 2016.



In the future, the company will fully implement its global layout, fully improve its core competitiveness, and strive to achieve its annual production and sales volume reaching 160 million units, sales revenue of over RMB 80 billion and production capacity among global top five tire manufacturers by 2030, becoming a technology-oriented enterprise with world-class technology, management and brand influence.

en.linglong.cn

BRAND VALUE

It strengthens the retail network construction, with nearly

200,000

marketing outlets globally, promoting its brand reputation and customer loyalty through reliable product quality and excellent service.

The company's products are exported to 173 countries across the world, covering Europe, Middle East, Americas, Asia Pacific, and Africa, and provides OE service for over 100 manufacturing bases of 60 global well-known automakers.

Linglong's brand value reached

98.137

Billion RMB in 2024.

Linglong has sponsored over

100

sports events and teams worldwide

Abundant sports marketing sponsorship

such as Real Madrid CF and Chelsea FC, to enhance its brand awareness and influence.



GLOBAL LAYOUT

Linglong collects global extraordinary wisdom to demonstrate intelligent Linglong with technological innovation. The company has established R&D institutions in Germany, America, Beijing, Shanghai, Jinan, Yantai and Zhaoyuan, owning national enterprise design center, national recognized testing laboratory and national industrial design center, to form global integrative R&D pattern.



R&D Center in America

R&D Center in Germany

Serbia



Linglong International Europe d.o.o.Zrenjanin

R&D Center

- R&D Center in Zhaoyuan and Yantai
- R&D Center in Beijing
- R&D Center in Shanghai
- R&D Center in Jinan

Linglong Tyre Co.,Ltd.

- Jilin Linglong Tyre Co.,Ltd.
- Shandong Linglong Tyre Co.,Ltd.
- Dezhou Linglong Tyre Co.,Ltd.
- Shaanxi Linglong Tyre Co., Ltd.
- Hubei Linglong Tyre Co.,Ltd.
- Guangxi Linglong Tyre Co.,Ltd.
- Anhui Linglong Tyre Co.,Ltd.

Linglong International Tyre(Thailand)Co.,Ltd

7+5 STRATEGIC GLOBAL POSITIONING

In June 2021, Linglong plans to change its 6+6 global layout into 7+5 global layout to build seven Chinese manufacturing bases as well as five overseas manufacturing bases. At present, the company has five Chinese manufacturing bases in Zhaoyuan, Dezhou, Liuzhou, Jingmen, Changchun and two overseas manufacturing bases in Thailand and Serbia. Meanwhile, Linglong will carry out active inspection of its new factory's location, aiming at completing the full completion of 7+5 global layout, and fully utilizing global resources and expanding its global tire market.



90° N

On August 7th, 2016, Linglong Tire reaching North Pole



90° S

On December 3, 2016, Linglong Tire reaching South Pole

Europe



Ads on ten clubs of Europe five major league matches



GLOBAL PARTNER



Global Club of Champions Partner and Official Jersey Sleeve Sponsor of VfL Wolfsburg



Sponsor of Serbian SuperLiga from 2019 to 2022



Title sponsor of Linglong Tire Cup Sino-European Chess Elite Tournament

Africa



Sponsor the Uganda National Basketball Team



Sponsor Zimbabwe Cricket

Asia



Senior sponsor for the China Pavilion at Expo 2020 Dubai.



Set up ATLAS Tire Drift Team for DCGP Set up Linglong Tire Drift Team for D1 GRAND PRIX in Japan



Sponsor China Truck Racing Championship from 2015 to 2017



Sponsor the Ratchaburi Mitr Phol FC



Sponsor Chinese Volleyball League of 2017-2020 season



Official Partner of Formula Drift Japan

Oceania



Sponsor Brisbane Roar FC



Sponsor Australia Queensland Football Team

North America



Official Automotive Tire of the NHL Tampa Bay Lightning



Official Automotive Tire of USF Athletics



Official Partner of NBA China Games

South America



Sponsor Brazilian football club to improve its brand awareness in South America

PROFESSIONAL AUTHORITATIVE LARGE OUTDOOR COMPREHENSIVE TIRE PROVING GROUND



Professional and Authoritative Large-scale Comprehensive Outdoor Tire Proving Ground

The Sino-Asia Tire Proving Ground is invested by Linglong Group and designed and constructed by top international professional teams, with a total investment of nearly RMB 1.38 billion. The proving ground consists of 18 tire test tracks, including a high-speed ring track, noise testing track, dynamic square, multi-surface braking track, dry handling track, wet handling track, wet circle, fatigue endurance track, NVH and comfort track, multi-functional platform and test ramp, off-road road, etc. It is suitable for both field testing and indoor experiment, covering 40 performance parameters such as tire handling, economy, and comfort for tires mounted on cars, light trucks, heavy trucks, and buses.



Automobile Testing Center

With a planned investment of RMB 1.314 billion, the Phase II project of Automobile Testing Center encompasses indoor laboratories such as vehicle performance laboratory, component laboratory, vehicle energy consumption/new energy laboratory, dynamics laboratory, intelligent connected vehicle (ICV) laboratory, NVH laboratory, dynamic footprint laboratory, as well as an ICV testing field. This project also includes 43 customer workshops, 3 storage centers, and Huizhi Hotel. Upon completion, it will serve as a leading third-party testing platform, aiming to integrate and foster innovation with exceptional service in the automotive industry.



Virtual Simulation Technology


In 2021, Linglong Tire made another breakthrough in virtual simulation technology, advancing the application of driving simulators. By virtualizing the complete vehicle and tires through VGrade DIM250, a 9-degrees-of-freedom driving experience is achieved. This leading-edge technology represents the largest and most advanced tire virtual simulator in China, setting a new industry standard as the first of its kind.



T1: Asphalt concrete high-speed track with the largest inclination in the world



T9: First wet handling track in China



T10: Wet circle

SUMMER



FLASH HERO | **FLASH 188** | **FLASH 288**

P 17 | **P 17** | **P 18**



SPORT MASTER | **SPORT MASTER** | **GREEN-MAX ACRO** | **AR288** | **GREEN-MAX**

P 19 | **P 20** | **P 22** | **P 22** | **P 24**



COMFORT MASTER | **GREEN-MAX HP818** | **GREEN-MAX EP188** | **GREEN-MAX ECOTOURING** | **CROSSWIND R791**

P 25 | **P 27** | **P 28** | **P 29** | **P 30**



GRIP MASTER C/S | **GREEN-MAX 4X4 HP** | **LL788**

P 31 | **P 33** | **P 34**



GREEN-MAX VAN HP | **GREEN-MAX VAN** | **GREEN-MAX VAN PLUS**

P 34 | **P 35** | **P 36**

FLASH HERO



Max performance tire with excellent handling and grip performance.

PERFORMANCE

- 1 Coherent groove design improves the wet grip performance.
- 2 Directional pattern design improves the linear acceleration performance.
- 3 High strength shoulder pattern design improves lateral grip performance for excellent steering performance.

FLASH HERO / RACING



RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
17	235/40ZR17	90	W	8 1/2J	600	1323	300	44
18	225/40ZR18	88	W	8J	560	1235	300	44
	265/35ZR18	93	W	9 1/2J	650	1433	300	44
19	285/35R19 XL	103	V	10J	875	1929	340	50

FLASH 100



Excellent handling and wet grip performance sport tire

PERFORMANCE

- 1 Excellent handling performance and provides precise steering for driving.
- 2 Enhanced performance in wet condition.

FLASH 100 / HP



RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
18	225/40ZR18	88	W	8J	560	1235	300	44
	255/50R18 XL	106	V	8J	950	2094	340	50
	255/55R18	109	V	8J	1030	2271	340	50
	265/35ZR18	93	W	9 1/2J	650	1433	340	50
	265/60R18	110	V	8J	1060	2337	300	44

FLASH 200



KEY PRODUCTS TIRE

Excellent handling performance sport tire

PERFORMANCE

- 1 Continuous design of the center pattern improve acceleration performance.
- 2 Streamlined straw of the tire shoulder improves wet grip performance.

FLASH 200 / UHP



RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
15	195/50R15	82	V	6J	475	1047	300	44
	195/55R15	85	V	6J	515	1135	300	44
17	205/45R17	88	W	7J	560	1235	340	50
	215/45R17	92	W	7J	615	1356	340	50
18	225/40R18	92	W	8J	630	1389	340	50
	225/45R18	95	W	7 1/2J	690	1521	340	50
	245/45R18	100	W	8J	800	1764	340	50

SPORT MASTER^e_{EV}



KEY PRODUCTS TIRE

High endurance mileage ,quiet ride

PERFORMANCE

- 1 BPT technology to slove the irregular treadwear caused by the heavy body of electric vehicle.
- 2 Four longitudinal grooves design of silent water drop to seal the noise caused by the pattern itself,inhibiting the noise from the tire and improving the driving comfort.
- 3 Asymmetrical rib design can provide more stable lateral support ,reduce tire deformation and improve the driving stability of the vehicle during steering.

SPORT MASTER



KEY PRODUCTS TIRE

Ultra high performance

PERFORMANCE

- 1 FBU Technology-Update the Wet performance.
- 2 VSG Technology-improve the handling performance.
- 3 BPT Technology-improve the acture contact area for better the handling performance.

SPORT MASTER^e / UHP



PCR NEW ENERGY

RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
18	215/55R18 XL	99	V	7J	775	1709	340	50
	235/45R18 XL	98	V	8J	750	1653	340	50
	235/60R18 XL	107	V	7J	975	2149	340	50
19	215/50R19	93	V	7J	650	1433	300	44
	225/55R19 XL	103	H	7J	875	1930	340	50
	235/45R19 XL	99	V	8J	775	1710	340	50
	245/45R19 XL	102	W	8J	850	1874	340	50
	245/50R19 XL	105	W	7 1/2J	925	2040	340	50
	255/45R19 XL	104	W	8 1/2J	900	1984	340	50
	255/50R19 XL	107	V	8J	975	2149	340	50
	255/55R19	107	W	8J	975	2149	300	44
	255/55R19	107	W	8J	975	2149	300	44
20	235/50R20 XL	104	V	7 1/2J	900	1984	340	50
	245/45R20 XL	103	W	8J	875	1929	340	50
	255/45R20 XL	105	V	8 1/2J	925	2039	340	50
	255/50R20 XL	109	V	8J	1030	2271	340	50
	255/50R20 XL	109	V	8J	1030	2271	340	50
21	235/45R21 XL	101	V	8J	825	1819	340	50
	255/40R21 XL	102	V	9J	850	1874	340	50

SPORT MASTER / UHP



PCR

RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
16	185/55R16 XL	87	V	6J	545	1201	340	50
	195/45R16 XL	84	V	6 1/2J	500	1102	340	50
	205/45R16 XL	87	Y	7J	545	1201	340	50
	205/50R16 XL	91	Y	6 1/2J	615	1356	340	50
	205/55R16	91	V	6 1/2J	615	1356	300	44
	205/55R16 XL	94	Y	6 1/2J	670	1477	340	50
	215/40R16 XL	86	Y	7 1/2J	530	1168	340	50
	215/45R16 XL	90	Y	7J	600	1323	340	50
	215/55R16 XL	97	Y	7J	730	1609	340	50
	225/55R16 XL	99	Y	7J	775	1709	340	50
	225/55R16 XL	99	Y	7J	775	1709	340	50
17	195/45R17 XL	85	W	6 1/2J	515	1135	340	50
	205/40R17 XL	84	Y	7 1/2J	500	1102	340	50
	205/45R17 XL	88	Y	7J	560	1235	340	50
	205/50R17 XL	93	Y	6 1/2J	650	1433	340	50
	215/40R17 XL	87	Y	7 1/2J	545	1201	340	50
	215/45R17 XL	91	Y	7J	615	1356	340	50
	215/50R17 XL	95	Y	7J	690	1521	340	50
	215/55R17 XL	98	Y	7J	750	1653	340	50
	225/45R17 XL	94	Y	7 1/2J	670	1477	340	50
	225/50R17 XL	98	Y	7J	750	1653	340	50
	225/55R17 XL	101	Y	7J	825	1819	340	50
	235/45R17 XL	97	Y	8J	730	1609	340	50
	235/50R17 XL	100	Y	7 1/2J	800	1764	340	50
	245/40R17 XL	95	Y	8 1/2J	690	1521	340	50
	245/45R17 XL	99	Y	8J	775	1709	340	50
	245/45R17 XL	99	Y	8J	775	1709	340	50
	245/45R17 XL	99	Y	8J	775	1709	340	50

SPORT MASTER / UHP								
PCR								
RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
18	205/40R18 XL	86	Y	7 1/2J	530	1168	340	50
	225/35R18 XL	87	Y	8J	545	1201	340	50
	225/40R18 XL	92	Y	8J	630	1389	340	50
	225/45R18 XL	95	Y	7 1/2J	690	1521	340	50
	235/40R18 XL	95	Y	8 1/2J	690	1521	340	50
	235/45R18 XL	98	Y	8J	750	1653	340	50
	235/50R18 XL	101	Y	7 1/2J	825	1819	340	50
	245/40R18 XL	97	Y	8 1/2J	730	1609	340	50
	245/45R18 XL	100	Y	8J	800	1764	340	50
	255/35R18 XL	94	Y	9J	670	1477	340	50
	255/45R18 XL	103	Y	8 1/2J	875	1929	340	50
	265/35R18 XL	97	Y	9 1/2J	730	1609	340	50
19	225/35R19 XL	88	W	8J	560	1235	340	50
	225/35R19 XL	88	Y	8J	560	1235	340	50
	225/40R19 XL	93	Y	8J	650	1433	340	50
	225/45R19 XL	96	Y	7 1/2J	710	1565	340	50
	235/35R19 XL	91	Y	8 1/2J	615	1356	340	50
	235/40R19 XL	96	Y	8 1/2J	710	1565	340	50
	225/55R19 XL	103	Y	7J	875	1929	340	50
	235/50R19 XL	103	Y	7 1/2J	875	1929	340	50
	245/30R19 XL	89	Y	8 1/2J	580	1279	340	50
	245/35R19 XL	93	Y	8 1/2J	650	1433	340	50
	245/40R19 XL	98	Y	8 1/2J	750	1653	340	50
	245/45R19 XL	102	Y	8J	850	1874	340	50
	255/30R19 XL	91	Y	9J	615	1356	340	50
	255/35R19 XL	96	Y	9J	710	1565	340	50
	275/35R19 XL	100	Y	9 1/2J	800	1764	340	50
	275/40R19 XL	105	Y	9 1/2J	925	2039	340	50
20	215/30R20 XL	82	W	7 1/2J	475	1047	340	50
	245/35R20 XL	95	Y	8 1/2J	690	1521	340	50
	245/40R20 XL	99	Y	8 1/2J	775	1709	340	50
	255/35R20 XL	97	Y	9J	730	1609	340	50
	265/30R20 XL	94	Y	9 1/2J	670	1477	340	50
	275/35R20 XL	102	Y	9 1/2J	850	1874	340	50
	315/35R20 XL	110	Y	11J	1060	2337	340	50
21	245/35R21 XL	96	Y	8 1/2J	710	1565	340	50
	295/35R21 XL	107	Y	10 1/2J	975	2149	340	50
22	255/35R22 XL	99	Y	9J	775	1709	340	50
	265/30R22 XL	97	Y	9 1/2J	730	1609	340	50
	285/35R22 XL	106	Y	10J	950	2094	340	50

GREEN-MAX ACRO



Super ability Run-Flat tire

- PERFORMANCE
- 1

Asymmetric tread pattern design provides more stable driving and riding.
- 2

Big shoulder blocks to effectively improve handling performance.
- 3

Carry linglong LRS run-flat technology, for the safety of the vehicle driving escort.

GREEN-MAX ACRO / UHP								
PCR								
RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
17	225/45RF17	91	W	7 1/2J	615	1356	350	51
	225/50RF17	94	W	7J	670	1477	350	51
	225/55RF17	97	W	7J	730	1609	350	51
18	245/40RF18	93	W	8 1/2J	650	1433	350	51
	245/45RF18	96	W	8J	710	1565	350	51
19	245/40RF19	94	W	8 1/2J	670	1477	350	51
	245/45RF19	98	W	8J	750	1653	350	51
	255/55RF19	107	W	8J	975	2149	350	51
	275/35R19	96	Y	9 1/2J	710	1565	350	51
	275/40R19	101	Y	9 1/2J	825	1819	350	51
20	245/40R20 XL	99	Y	8 1/2J	775	1709	340	50
	275/35R20 XL	102	Y	9 1/2J	850	1874	340	50
	275/45RF20	106	W	9J	950	2094	350	51
	305/40R20 XL	112	Y	11J	1120	2469	340	50
	315/35R20 XL	110	Y	11J	1060	2337	340	50

AR200 RFT



Super ability Run-Flat tire

- PERFORMANCE
- 1

Asymmetric tread pattern design provides more stable driving and riding
- 2

Carry linglong LRS run-flat technology, for the safety of the vehicle driving escort.
- 3

Big shoulder blocks to effectively improve handling performance.

AR200 RFT / UHP								
PCR								
RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
16	225/55RF16	95	W	7J	690	1521	350	51
17	225/45RF17	91	W	7 1/2J	615	1356	350	51
	225/50RF17	94	W	7J	670	1477	350	51
	225/55RF17	97	W	7J	730	1609	350	51
18	245/50R18	100	W	7 1/2J	800	1764	350	51
	255/55RF18	105	W	8J	925	2039	350	51
	245/40RF18	93	W	8 1/2J	650	1433	350	51
	245/45RF18	96	W	8J	710	1565	350	51
	255/55RF18	105	W	8J	925	2039	350	51
19	255/50R19	103	W	8J	875	1929	350	51
	225/40RF19	89	W	8J	580	1279	350	51
	245/40RF19	94	W	8 1/2J	670	1477	350	51
	245/45RF19	98	W	8J	750	1653	350	51
	255/35R19	92	Y	9J	630	1389	350	51
20	275/40RF20	102	W	9 1/2J	850	1874	350	51

AR200



Ultra high performance

PERFORMANCE

- 1 Asymmetric tread pattern design for better handling performance and fashionable appearance.
- 2 Big shoulder blocks design, provide extreme steering performance.
- 3 Enhanced wet grip to effectively reduce risk of hydroplaning.

AR200 / UHP



RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
16	215/55R16 XL	97	W	7J	730	1609	340	50
	185/55R16 XL	87	W	6J	545	1201	340	50
	195/45R16 XL	84	V	6 1/2J	500	1102	340	50
	205/55R16 XL	94	W	6 1/2J	670	1477	340	50
	215/55R16 XL	97	W	7J	730	1609	340	50
	225/55R16	95	Y	7J	690	1521	300	44
17	195/45R17 XL	85	V	6 1/2J	515	1135	340	50
	205/45R17 XL	88	Y	7J	560	1235	340	50
	205/50R17 XL	93	Y	6 1/2J	650	1433	340	50
	215/45R17 XL	91	Y	7J	615	1356	340	50
	215/50R17 XL	95	Y	7J	690	1521	340	50
	215/55R17	94	Y	7J	670	1477	300	44
	225/45R17 XL	94	Y	7 1/2J	670	1477	340	50
	225/50R17 XL	98	Y	7J	750	1653	340	50
	235/50R17 XL	100	W	7 1/2J	800	1764	340	50
	255/45R17 XL	102	W	8 1/2J	850	1874	340	50
18	215/45R18 XL	93	W	7J	650	1433	340	50
	225/40R18 XL	92	Y	8J	630	1389	340	50
	225/45R18 XL	95	Y	7 1/2J	690	1521	340	50
	235/45R18 XL	98	W	8J	750	1653	340	50
	245/40R18 XL	97	Y	8 1/2J	730	1609	340	50
	275/45R18 XL	107	W	9J	975	2149	340	50
19	225/40R19 XL	93	Y	8J	650	1433	340	50
	225/45R19 XL	96	W	7 1/2J	710	1565	340	50
	225/55R19 XL	103	Y	7J	875	1929	340	50
	235/35R19 XL	91	Y	8 1/2J	615	1356	340	50
	235/40R19 XL	96	Y	8 1/2J	710	1565	340	50
	235/50R19 XL	103	Y	7 1/2J	875	1929	340	50
	255/30R19 XL	91	Y	9J	615	1356	340	50
	255/35R19 XL	96	Y	9J	710	1565	340	50
	255/40R19 XL	100	W	9J	800	1764	340	50
	255/45R19 XL	104	W	8 1/2J	900	1984	340	50
	275/40R19 XL	105	Y	9 1/2J	925	2039	340	50
	245/45R20 XL	103	W	8J	875	1929	340	50
20	255/35R20 XL	97	Y	9J	730	1609	340	50
	255/45R20 XL	105	W	8 1/2J	925	2039	340	50
	265/30R20 XL	94	Y	9 1/2J	670	1477	340	50
	275/35R20 XL	102	Y	9 1/2J	850	1874	340	50
	315/35R20 XL	110	W	11J	1060	2337	340	50
	295/35R21 XL	107	W	10 1/2J	975	2149	340	50

GREEN-MAX



UHP Tire with Excellent Wet Grip and Low Noise

PERFORMANCE

- 1 Excellent handling performance.
- 2 Improved drainage performance to effectively reduce risk of hydroplaning.
- 3 Superior driving stability.
- 4 Comfortable ride.
- 5 Designed to fit premium cars and sports cars.

GREEN-MAX / UHP



RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
15	185/45R15	75	V	6J	387	853	300	44
	195/45R15	78	V	6 1/2J	425	937	300	44
16	195/45R16 XL	84	V	6 1/2J	500	1102	340	50
	205/45R16 XL	87	W	7J	545	1201	340	50
	205/50R16	87	W	6 1/2J	545	1201	300	44
	205/50R16	87	V	6 1/2J	545	1201	300	44
	205/55R16 XL	94	W	6 1/2J	670	1477	340	50
	215/40R16 XL	86	W	7 1/2J	530	1168	340	50
	215/45R16 XL	90	V	7J	600	1323	340	50
	215/55R16 XL	97	W	7J	730	1609	340	50
	225/50R16 XL	96	V	7J	710	1565	340	50
	225/55R16	95	V	7J	690	1521	300	44
17	185/35R17 XL	82	V	6 1/2J	475	1047	340	50
	195/40R17 XL	81	V	8J	462	1019	340	50
	205/40R17 XL	84	W	7 1/2J	500	1102	340	50
	205/45R17 XL	88	W	7J	560	1235	340	50
	205/45R17 XL	88	V	7J	560	1235	340	50
	205/50R17 XL	93	W	6 1/2J	650	1433	340	50
	215/40R17 XL	87	W	7 1/2J	545	1201	340	50
	215/45R17 XL	91	W	7J	615	1356	340	50
	215/50R17 XL	95	V	7J	690	1521	340	50
	215/50R17 XL	95	W	7J	690	1521	340	50
	215/55R17	94	V	7J	670	1477	300	44
	215/55R17 XL	98	W	7J	750	1653	340	50
	225/45R17 XL	94	W	7 1/2J	670	1477	340	50
	225/50R17 XL	98	W	7J	750	1653	340	50
	225/55R17	97	W	7J	730	1609	300	44
	225/55R17 XL	101	W	7J	825	1819	340	50
	235/45R17 XL	97	W	8J	730	1609	340	50
	235/50R17	96	Y	7 1/2J	710	1565	300	44
	245/40R17	91	W	8 1/2J	615	1356	300	44
	245/45R17 XL	99	W	8J	775	1709	340	50
18	165/40R18 XL	85	V	6J	515	1135	340	50
	185/35R18	81	H	6 1/2J	462	1019	340	50
	195/35R18 XL	88	W	7J	560	1235	340	50
	205/35R18 XL	81	H	7 1/2J	462	1019	340	50
	205/40R18 XL	86	W	7 1/2J	530	1168	340	50
	215/35R18 XL	84	W	7 1/2J	500	1102	340	50
	215/40R18 XL	89	W	7 1/2J	580	1279	340	50
	215/45R18 XL	93	W	7J	650	1433	340	50
	225/40R18 XL	92	W	8J	630	1389	340	50
	225/45R18 XL	95	W	7 1/2J	690	1521	340	50
	235/40R18 XL	95	W	8 1/2J	690	1521	340	50
	235/45R18 XL	98	Y	8J	750	1653	340	50
	235/50R18 XL	101	W	7 1/2J	825	1819	340	50
	245/40R18 XL	97	W	8 1/2J	730	1609	340	50
	245/45R18 XL	100	W	8J	800	1765	340	50
	255/35R18 XL	94	Y	9J	670	1477	340	50
	255/45R18 XL	103	W	8 1/2J	875	1929	340	50
	265/35R18 XL	97	Y	9 1/2J	730	1609	340	50
19	215/35R19 XL	85	W	7 1/2J	515	1135	340	50
	225/35R19 XL	88	W	8J	560	1235	340	50
	225/45R19 XL	96	W	7 1/2J	710	1565	340	50
	225/50R19 XL	107	V	7J	975	2149	340	50
	225/55R19	99	H	7J	775	1709	300	44
	235/35R19 XL	91	W	8 1/2J	615	1356	340	50
	235/55R19 XL	105	W	7 1/2J	925	2039	340	50
	245/35R19 XL	93	Y	8 1/2J	650	1433	340	50
	245/40R19 XL	98	W	8 1/2J	750	1653	340	50
	245/45R19	98	Y	8J	750	1653	300	44
20	265/30R19 XL	93	W	9 1/2J	650	1433	340	50
	215/30R20 XL	82	W	7 1/2J	475	1047	340	50
	225/30R20 XL	85	W	8J	515	1135	340	50
	225/35R20 XL	90	Y	8J	600	1323	340	50
	235/30R20 XL	88	Y	8 1/2J	560	1235	340	50
	245/35R20 XL	95	Y	8 1/2J	690	1521	340	50
22	245/45R20	99	W	8J	775	1709	300	44
	265/40R22 XL	106	V	9 1/2J	950	2094	340	50
	285/40R22 XL	110	V	10J	1060	2337	340	50

COMFORT MASTER



KEY PRODUCTS TIRE

HP Tire with Good Handling Performance and Low Noise

PERFORMANCE

- 1 Comfortable and quiet ride.
- 2 Low rolling resistance for better fuel efficiency.
- 3 Enhanced wet grip to effectively reduce risk of hydroplaning.

COMFORT MASTER / HP



RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
13	145/70R13	71	T	4.50B	345	761	300	44
	155/70R13	75	T	4.50B	387	853	300	44
	155/80R13	79	T	4.50B	437	963	300	44
	175/70R13	82	T	5.00B	475	1047	300	44
14	155/65R14	75	T	4 1/2J	387	853	300	44
	155/65R14	75	H	4 1/2J	387	853	300	44
	165/60R14	75	H	5J	387	853	300	44
	165/65R14	79	H	5J	437	963	300	44
	165/65R14	79	T	5J	437	963	300	44
	165/70R14	81	T	5J	462	1019	300	44
	165/70R14 XL	85	T	5J	515	1135	340	50
	175/60R14	79	H	5J	437	963	300	44
	175/65R14	82	T	5J	475	1047	300	44
	175/65R14	82	H	5J	475	1047	300	44
	175/65R14 XL	86	T	5J	530	1168	340	50
	175/70R14	84	T	5J	500	1102	300	44
	175/70R14 XL	88	T	5J	560	1235	340	50
	145/65R15	72	T	4 1/2J	355	783	300	44
15	155/60R15	74	T	4 1/2J	375	827	300	44
	165/55R15	75	V	5J	387	853	300	44
	165/60R15	77	H	5J	412	908	300	44
	165/60R15	77	T	5J	412	908	300	44
	165/65R15	81	H	5J	462	1019	300	44
	165/65R15	81	T	5J	462	1019	300	44
	175/55R15	77	T	5 1/2J	412	908	300	44
	175/60R15	81	H	5J	462	1019	300	44
	175/60R15	81	V	5J	462	1019	300	44
	175/65R15	84	H	5J	500	1102	300	44
	175/65R15	84	T	5J	500	1102	300	44
	165/50R16	75	V	5J	387	853	350	51
	175/60R16	82	H	5J	475	1047	300	44
	175/60R16	82	H	5J	475	1047	300	44

Three Grooves

COMFORT MASTER / HP



RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	lbs
14	185/55R14	80	H	6J	450	992	300	44
	185/60R14	82	T	5 1/2J	475	1047	300	44
	185/60R14	82	H	5 1/2J	475	1047	300	44
	185/65R14	86	H	5 1/2J	530	1168	300	44
	185/65R14	86	T	5 1/2J	530	1168	300	44
	185/70R14	88	T	5 1/2J	560	1235	300	44
	195/60R14	86	H	6J	530	1168	300	44
	195/65R14	89	H	6J	580	1279	300	44
	195/70R14	91	T	6J	615	1356	300	44
	205/70R14	94	T	6J	670	1477	300	44
15	185/55R15	82	V	6J	475	1047	300	44
	185/55R15	82	H	6J	475	1047	300	44
	185/60R15	84	H	5 1/2J	500	1102	300	44
	185/60R15	84	T	5 1/2J	500	1102	300	44
	185/60R15 XL	88	H	5 1/2J	560	1235	340	50
	185/65R15	88	H	5 1/2J	560	1235	300	44
	185/65R15	88	T	5 1/2J	560	1235	300	44
	185/65R15 XL	92	T	5 1/2J	630	1389	340	50
	195/50R15	82	V	6J	475	1047	300	44
	195/55R15	85	H	6J	515	1135	300	44
	195/55R15	85	V	6J	515	1135	300	44
	195/60R15	88	H	6J	560	1235	300	44
	195/60R15	88	V	6J	560	1235	300	44
	195/65R15	91	H	6J	615	1356	300	44
	195/65R15	91	T	6J	615	1356	300	44
	195/65R15	91	V	6J	615	1356	300	44
	195/65R15 XL	95	T	6J	615	1356	340	50
	195/65R15 XL	95	H	6J	690	1521	340	50
	205/50R15	86	V	6 1/2J	530	1168	300	44
	205/55R15	88	V	6 1/2J	560	1235	300	44
	205/60R15	91	H	6J	615	1356	300	44
	205/60R15	91	V	6J	615	1356	300	44
	205/65R15	94	H	6J	670	1477	300	44
	205/65R15	94	V	6J	670	1477	300	44
	205/70R15	96	T	6J	710	1565	300	44
	215/60R15	94	H	6 1/2J	670	1477	300	44
	215/65R15 XL	100	H	6 1/2J	800	1764	340	50
	185/50R16	81	V	6J	462	1019	300	44
	185/55R16	83	V	6J	487	1074	300	44
	195/50R16	84	V	6J	500	1102	300	44
	195/50R16 XL	88	V	6J	560	1235	340	50
	195/55R16	87	H	6J	545	1201	300	44
	195/55R16	87	V	6J	545	1201	300	44
	195/55R16 XL	91	V	6J	615	1356	340	50
16	195/60R16	89	H	6J	580	1279	300	44
	195/60R16	89	V	6J	580	1279	300	44
	195/65R16	92	H	6J	630	1389	300	44
	205/50R16	87	H	6 1/2J	545	1201	300	44
	205/50R16	87	V	6 1/2J	545	1201	300	44
	205/55R16	91	V	6 1/2J	615	1356	300	44
	205/55R16	91	H	6 1/2J	615	1356	300	44
	205/60R16	92	H	6J	630	1389	300	44
	205/60R16	92	V	6J	630	1389	300	44
	205/60R16 XL	96	V	6J	710	1565	340	50
	205/65R16	95	H	6J	690	1521	300	44
	215/55R16	93	V	7J	650	1433	300	44
	215/60R16	95	H	6 1/2J	690	1521	300	44
	215/60R16	95	V	6 1/2J	690	1521	300	44
	215/60R16 XL	99	V	6 1/2J	775	1709	340	50
	215/60R16 XL	99	H	6 1/2J	775	1709	340	50
	215/65R16	98	H	6 1/2J	750	1653	300	44
	225/50R16	92	V	7J	630	1389	300	44
	225/55R16 XL	99	H	7J	775	1709	340	50
	225/55R16 XL	99	V	7J	775	1709	340	50
17	225/60R16	98	V	6 1/2J	750	1653	300	44
	225/70R16	103	H	6 1/2J	875	1929	300	44
	235/60R16	100	H	7J	800	1764	300	44
	255/70R16 XL	115	H	7 1/2J	1215	2679	340	50
	195/60R17	90	H	6J	600	1323	300	44
	205/50R17 XL	93	V	6 1/2J	650	1433	340	50
	205/55R17 XL	95	V	6 1/2J	690	1521	340	50
	215/50R17 XL	95	V	7J	690	1521	340	50
	215/55R17	94	V	7J	670	1477	300	44
	215/60R17	96	H	6 1/2J	710	1565	300	44
	225/50R17	94	V	7J	670	1477	300	44
	225/50R17 XL	98	V	7J	750	1653	340	50
	225/60R17	99	H	6 1/2J	775	1709	300	44
	225/60R17	99	V	6 1/2J	775	1709	300	44
	225/65R17	102	H	6 1/2J	850	1874	300	44
	235/55R17	99	V	7 1/2J	775	1709	300	44
	235/60R17	102	H	7J	850	1874	300	44

Four Grooves

GREEN-MAX HP010



HP Tire with Good Handling
Performance and Low Noise

PERFORMANCE

- 1 Comfortable and quiet ride.
- 2 Low rolling resistance for better fuel efficiency.
- 3 Enhanced wet grip to effectively reduce risk of hydroplaning.

GREEN-MAX HP010 / HP



RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
14	165/60R14	75	H	5J	387	853	300	44
	175/65R14	82	H	5J	475	1047	300	44
	175/65R14 XL	86	H	5J	530	1168	340	50
15	165/60R15	77	H	5J	412	908	300	44
	175/60R15	81	H	5J	462	1019	300	44
	175/65R15	84	H	5J	500	1102	300	44

Three Grooves

14	185/55R14	80	H	6J	450	992	300	44
	185/60R14	82	H	5 1/2J	475	1047	300	44
	185/65R14	86	H	5 1/2J	530	1168	300	44
15	185/55R15	82	V	6J	475	1047	300	44
	185/60R15	84	T	5 1/2J	500	1102	300	44
	185/60R15 XL	88	H	5 1/2J	560	1235	340	50
	185/65R15	88	H	5 1/2J	560	1235	300	44
	195/65R15	91	H/V	6J	615	1356	300	44
	195/65R15 WW	91	H	6J	615	1356	300	44
	205/65R15	94	H/V	6J	670	1477	300	44
16	185/50R16	81	H	6J	462	1019	300	44
	195/50R16 XL	88	V	6J	560	1235	340	50
	195/55R16 XL	91	H	6J	615	1356	340	50
	195/60R16	89	H	6J	580	1279	300	44
	205/50R16	87	V	6 1/2J	545	1201	300	44
	205/55R16	91	V	6 1/2J	615	1356	300	44
	205/55R16 XL	94	V	6 1/2J	670	1477	340	50
	205/60R16	92	V	6J	630	1389	300	44
	205/65R16	95	H	6J	690	1521	300	44
	215/60R16	95	H	6 1/2J	690	1521	300	44
	215/60R16 XL	99	H/V	6 1/2J	775	1709	340	50
	215/65R16	98	H	6 1/2J	750	1653	300	44
17	255/65R16	109	H	7 1/2J	1030	2271	300	44
	205/50R17	89	V	6 1/2J	580	1279	300	44
	205/50R17 XL	93	V	6 1/2J	650	1433	340	50
	205/55R17 XL	95	V	6 1/2J	690	1521	340	50
	215/50R17	91	V	7J	615	1356	300	44
	215/50R17 XL	95	V	7J	690	1521	340	50
	215/60R17	96	H	6 1/2J	710	1565	300	44

Four Grooves

GREEN-MAX EP100



HP Tire with Excellent Handling
Perormance, Low rolling resistance
and Low noise

PERFORMANCE

- 1 Low rolling resistance.Increase vehicle range.
- 2 Comfortable and quiet ride.
- 3 Excellent handling performance.
- 4 The good performance of dry braking can effectively reduce the occurrence of accidents.

GREEN-MAX EP100 / ECO



RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
14	165/60R14 XL	79	T	5J	437	963	340	50
	165/65R14 XL	83	H	5J	487	1074	340	50
	175/65R14 XL	86	H	5J	530	1168	340	50
15	165/65R15	81	H	5J	462	1019	350	51
	185/60R15 XL	88	H	5 1/2J	560	1235	340	50
	195/50R15 XL	86	H	6J	530	1168	340	50
	195/65R15 XL	95	H	6J	690	1521	340	50
16	175/55R16	80	H	5 1/2J	450	992	350	51
	195/55R16 XL	91	H	6J	615	1356	340	50

CROSSWIND R701*

PERFORMANCE

- 1 Low fuel consumption.
- 2 Comfortable and quiet ride.
- 3 Excellent stability and drainage performance.
- 4 Excellent handling performance.

CROSSWIND R701* / ECO



RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
12	175/70R12	80	H	5.00B	450	992	300	44
13	165/60R13	73	T	5.00B	365	805	300	44
14	175/65R14	82	T	5J	475	1047	300	44
	185/65R14	86	T	5 1/2J	530	1168	300	44
	185/70R14	88	T	5 1/2J	560	1235	300	44
	195/70R14	91	T	6J	615	1356	300	44
15	195/50R15	82	H	6J	475	1047	300	44
	195/60R15	88	H	6J	560	1235	300	44
	195/65R15	91	H	6J	615	1356	300	44
	205/70R15	96	T	6J	710	1565	300	44
	185/65R15	88	T	5 1/2J	560	1235	300	44
	195/50R15	82	H	6J	475	1047	300	44
	205/60R15	91	H	6J	615	1356	300	44
	205/65R15	94	H	6J	670	1477	300	44
	205/70R15	96	T	6J	710	1565	300	44
	205/75R15	97	S	5 1/2J	730	1609	300	44
16	205/60R16	92	H	6J	630	1389	300	44
	205/55R16	91	H	6 1/2J	615	1356	300	44
	205/65R16	95	H	6J	690	1521	300	44

GREEN-MAX ECOTOURING



PERFORMANCE

- 1 Low resistance.
- 2 Low noise.
- 3 Excellent wet performance.

GREEN-MAX ECOTOURING / ECO



PCR

RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
12	145/70R12	69	S	4.50B	325	716	300	44
	155/70R12	73	S	4.50B	365	805	300	44
13	145/70R13	71	T	4.50B	345	761	300	44
	145/80R13	75	T	4.00B	387	853	300	44
	155/65R13	73	T	4.50B	365	805	300	44
	155/70R13	75	T	4.50B	387	853	300	44
	155/80R13	79	T	4.50B	437	963	300	44
	165/65R13	77	T	5.00B	412	908	300	44
	165/70R13	79	T	5.00B	437	963	300	44
	165/70R13	79	T	5.00B	437	963	300	44
	175/60R13	77	H	5.00B	412	908	300	44
	175/60R13	77	T	5.00B	412	908	300	44
	175/65R13	80	T	5.00B	450	992	300	44
	175/70R13	82	T	5.00B	475	1047	300	44
14	155/65R14	75	T	4 1/2J	387	853	300	44
	165/65R14	79	T	5J	437	963	300	44
	165/70R14	81	T	5J	462	1019	300	44
	175/65R14	82	T	5J	475	1047	300	44
	175/65R14 XL	86	T	5J	530	1168	340	50
	175/70R14	84	T	5J	500	1102	300	44
	175/70R14 XL	88	T	5J	560	1235	340	50

Three Grooves

13	185/70R13	86	T	5.50B	530	1168	300	44
14	185/65R14	86	T	5 1/2J	530	1168	300	44
	185/70R14	88	T	5 1/2J	560	1235	300	44
	195/70R14	91	T	6J	615	1356	300	44
	205/60R14	88	H	6J	560	1235	300	44
15	185/65R15	88	T	5 1/2J	560	1235	300	44
	185/65R15 XL	92	T	5 1/2J	630	1389	340	50
	195/65R15	91	T	6J	615	1356	300	44
	195/65R15 XL	95	T	6J	690	1521	340	50
	205/70R15	96	T	6J	710	1565	300	44
	235/75R15	105	T	6 1/2J	925	2039	300	44

Four Grooves

R702

PERFORMANCE

- 1 Low resistance.
- 2 Low noise.

R702 / ECO



PCR

RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
12	155/70R12	73	S	4.50B	365	805	300	44
13	175/70R13	82	T	5.00B	475	1047	300	44
14	165/55R14	72	H	5J	355	783	300	44
	175/65R14	82	T	5J	475	1047	300	44
	185/60R14	82	H	5 1/2J	475	1047	300	44
15	195/55R15	85	H	6J	515	1135	300	44
	195/50R15	82	H	6J	475	1047	300	44
	195/60R15	88	H	6J	560	1235	300	44

CROSSWIND R791



High Wear Resistance

PERFORMANCE

- 1 High wear resistance.
- 2 Quiet and comfort.
- 3 Specially designed for taxis.

CROSSWIND R791 / TAXI



PCR

RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
12	145/80R12	74	T	4J	375	827	300	44
13	165/80R13	83	S	4.50B	485	1069	300	44
14	175/70R14 XL	88	H	5J	560	1235	340	50
	185/60R14	82	H	5 1/2J	475	1047	300	44
	195/60R14	86	H	6J	530	1168	300	44
15	175/50R15	75	H	5 1/2J	387	853	300	44
	185/60R15	84	H	5 1/2J	500	1102	300	44
	195/60R15	88	H	6J	560	1235	300	44
	195/65R15	91	H	6J	615	1356	300	44
16	205/55R16	91	H	6 1/2J	615	1356	300	44

GRIP MASTER C/S



KEY PRODUCTS TIRE

Good Handling and Comfortable Performance

PERFORMANCE

- 1 Excellent grip and handling performance.
- 2 Comfortable and quiet ride.
- 3 Superior wet grip and safety.

GRIP MASTER C/S / HP/UHP



RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
17	225/60R17	99	V	6 1/2J	775	1710	300	44
	225/65R17 XL	106	V	6 1/2J	950	2094	340	50
	235/60R17 XL	106	V	7J	950	2094	340	50
	235/65R17 XL	108	V	7J	1000	2205	340	50
	255/60R17	106	H	7 1/2J	950	2094	300	44
	255/65R17	110	H	7 1/2J	1060	2337	300	44
	265/65R17	112	H	8J	1120	2469	300	44
	275/55R17	109	V	8 1/2J	1030	2271	300	44
18	215/50R18	92	W	7J	630	1389	300	44
	215/55R18 XL	99	V	7J	775	1709	340	50
	225/55R18	98	V	7J	750	1653	300	44
	225/50R18 XL	99	W	7J	775	1709	340	50
	225/60R18 XL	104	V	6 1/2J	900	1984	340	50
	235/50R18	97	V	7 1/2J	730	1609	300	44
	235/55R18 XL	104	W	7 1/2J	900	1984	340	50
	235/60R18 XL	107	W	7J	975	2149	340	50
	255/40R18 XL	99	W	9J	775	1709	340	50
	255/55R18 XL	109	Y	8J	1030	2271	340	50
	255/60R18 XL	112	V	7 1/2J	1120	2469	340	50
	275/60R18	113	H	8J	1150	2535	300	44
	285/60R18	116	H	8 1/2J	1250	2756	300	44
	205/55R19 XL	97	V	6 1/2J	730	1609	340	50
19	225/55R19	99	V	7J	775	1709	300	44
	235/45R19 XL	99	V	8J	775	1709	340	50
	235/55R19 XL	105	W	7 1/2J	925	2039	340	50
	255/40R19 XL	100	W	9J	800	1764	340	50
	255/45R19 XL	104	W	8 1/2J	900	1984	340	50
	255/50R19 XL	107	W	8J	975	2149	340	50
	255/55R19 XL	111	W	8J	1090	2403	340	50
	265/50R19 XL	110	V	8 1/2J	1060	2337	340	50
	285/45R19 XL	111	W	9 1/2J	1090	2403	340	50
	195/55R20 XL	95	H	6J	690	1521	340	50
20	235/45R20 XL	100	W	8J	800	1764	340	50
	245/45R20 XL	103	W	8J	875	1929	340	50
	255/40R20 XL	101	W	9J	825	1819	340	50
	255/45R20 XL	105	Y	8 1/2J	925	2039	340	50
	255/50R20 XL	109	V	8J	1030	2271	340	50
	265/45R20 XL	108	Y	9J	1000	2205	340	50
	265/50R20 XL	111	W	8 1/2J	1090	2403	340	50
	275/40R20 XL	106	V	9 1/2J	950	2094	340	50
	275/45R20 XL	110	W	9J	1060	2337	340	50
	285/50R20 XL	116	W	9J	1250	2756	340	50
	315/35R20 XL	110	Y	11J	1060	2337	340	50
	245/40R21 XL	100	W	8 1/2J	800	1764	340	50
	255/40R21 XL	102	W	9J	850	1874	340	50
21	275/45R21 XL	110	W	9J	1060	2337	340	50
	275/50R21 XL	113	V	8 1/2J	1150	2535	340	50
	285/45R21	109	W	9 1/2J	1030	2271	300	44
	295/40R21 XL	111	W	10 1/2J	1090	2403	340	50

GRIP MASTER C/S / HP/UHP



RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
15	205/70R15	96	H	6J	710	1565	300	44
	215/70R15	98	H	6 1/2J	750	1653	300	44
16	215/65R16 XL	102	H	6 1/2J	850	1874	340	50
	215/70R16	100	H	6 1/2J	800	1764	300	44
	225/65R16	100	H	6 1/2J	800	1764	300	44
	225/70R16	103	H	6 1/2J	875	1929	300	44
	225/75R16	104	H	6J	900	1984	300	44
	235/60R16	100	H	7J	800	1764	300	44
	235/70R16	106	H	7J	950	2094	300	44
	245/70R16 XL	111	H	7J	1090	2403	340	50
	255/70R16	111	H	7 1/2J	1090	2403	300	44
	265/70R16	112	H	8J	1120	2469	300	44
	275/70R16	114	H	8J	1180	2601	300	44
17	215/55R17 XL	98	V	7J	750	1653	340	50
	215/60R17	96	H	6 1/2J	710	1565	300	44
	215/65R17 XL	103	V	6 1/2J	875	1929	340	50
	225/55R17 XL	101	V	7J	825	1819	340	50

GREEN-MAX 4X4 HP



SUV tires for urban highway use,
with good handling and low noise

PERFORMANCE

- 1 Excellent handling performance.
- 2 Enhanced drainage performance to effectively reduce risk of hydroplaning.
- 3 Superior longitudinal stability for more comfortable ride.
- 4 Low noise to offer a quiet ride.

GREEN-MAX 4X4 HP / HP/UHP



RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
15	205/70R15	96	H	6J	710	1565	300	44
16	215/65R16 XL	102	H	6 1/2J	850	1874	340	50
	215/70R16	100	H	6 1/2J	800	1764	300	44
	225/65R16	100	H	6 1/2J	800	1764	300	44
	225/75R16	104	H	6J	900	1984	300	44
	235/60R16	100	H	7J	800	1764	300	44
	235/70R16	106	H	7J	950	2094	300	44
	245/70R16 XL	111	H	7J	1090	2403	340	50
	265/70R16	112	H	8J	1120	2469	300	44
17	275/70R16	114	H	8J	1180	2601	300	44
	215/60R17	96	H	6 1/2J	710	1565	300	44
	215/65R17 XL	103	V	6 1/2J	875	1929	340	50
	225/55R17 XL	101	V	7J	825	1819	340	50
	225/65R17	102	H	6 1/2J	850	1874	300	44
	225/60R17	99	V	6 1/2J	775	1709	300	44
	235/55R17 XL	103	V	7 1/2J	875	1929	340	50
	235/60R17 XL	106	V	7J	950	2094	340	50
	235/65R17 XL	108	V	7J	1000	2205	340	50
	245/65R17 XL	111	H	7J	1090	2403	340	50
	255/60R17	106	H	7 1/2J	950	2094	300	44
	255/65R17	110	H	7 1/2J	1060	2337	300	44
18	265/65R17	112	H	8J	1120	2469	300	44
	275/55R17	109	V	8 1/2J	1030	2271	300	44
	215/55R18 XL	99	V	7J	775	1709	340	50
	215/55R18	95	V	7J	690	1521	300	44
	225/55R18	98	V	7J	750	1653	300	44
	225/60R18	100	H	6 1/2J	800	1764	300	44
	235/50R18	97	V	7 1/2J	730	1609	300	44
	235/55R18 XL	104	V	7 1/2J	900	1984	340	50
	235/60R18 XL	107	V	7J	975	2149	340	50
	255/55R18 XL	109	V/W	8J	1030	2271	340	50
	255/60R18 XL	112	V	7 1/2J	1120	2469	340	50
	265/60R18	110	H	8J	1060	2337	300	44
19	275/60R18	113	H	8J	1150	2535	300	44
	225/55R19	99	V	7J	775	1709	300	44
	255/50R19 XL	107	W	8J	975	2149	340	50
	255/55R19 XL	111	V	8J	1090	2403	340	50
	265/50R19 XL	110	W	8 1/2J	1060	2337	340	50
	265/50R20 XL	111	V	8 1/2J	1090	2403	340	50
20	275/40R22 XL	106	V	9 1/2J	950	2094	340	50
	275/45R20 XL	110	V	9J	1060	2337	340	50
	315/35R20 XL	110	W	11J	1060	2337	340	50
	295/35R21 XL	107	W	10 1/2J	975	2149	340	50
21	275/40R22 XL	107	W	9 1/2J	975	2149	340	50
22	285/35R22 XL	106	V	10J	950	2094	340	50

LL700



Good drainage,
low noise

PERFORMANCE

- 1 Excellent wet handling performance.
- 2 Good driving stability.

LL700 / HP



RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
13	175/70R13	82	T	5.00B	475	1047	300	44
	185/70R13	86	T	5.50B	530	1168	300	44
14	175/70R14	84	T	5J	500	1102	300	44
	185/70R14	88	T	5 1/2J	560	1235	300	44
	195/70R14	91	T	6J	615	1356	300	44
	205/70R14	95	T	6J	690	1521	300	44
15	205/70R15	96	H	6J	710	1565	300	44
	215/70R15	98	T	6 1/2J	750	1653	300	44

GREEN-MAX VAN HP



Commercial tire with high
grip performance

PERFORMANCE

- 1 Better grip performance.
- 2 Low rolling resistance for high energy efficiency.

GREEN-MAX VAN HP



RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure		Overall Diameter		Overall Width		Tread Depth	
						kg	lbs	kPa	psi	mm	in	mm	in	mm	32nds
14	175/65R14C	6PR	90/88	T	5J	475	1045	375	54	584	22.99	177	6.97	7.6	9.57
15	215/65R15C	6PR	104/102	T	6 1/2J	975	2150	375	54	661	26.02	221	8.70	9	11.34
	225/75R15C	8PR	116/114	Q	6J	1000	2205	475	69	719	28.31	223	8.78	9.3	11.72
16	195/65R16C	8PR	104/102	R	6J	650	1435	475	65	660	25.98	201	7.91	7.8	9.83
	205/65R16C	8PR	107/105	R	6J	690	1520	475	69	672	26.46	209	8.23	9	11.34
	215/60R16C	6PR	103/101	T	6 1/2J	690	1520	375	54	664	26.14	221	8.70	9	11.34
	215/65R16C	8PR	109/107	R	6 1/2J	1030	2270	475	69	686	27.01	221	8.70	9	11.34
	225/65R16C	8PR	112/110	R	6 1/2J	775	1710	475	69	698	27.48	228	8.98	9	11.34
	235/65R16C	8PR	115/113	R	7J	1000	2205	475	69	712	28.03	240	9.45	9	11.34

GREEN-MAX VAN



Commercial tire with high grip performance

PERFORMANCE

- 1 Better grip performance.
- 2 Low rolling resistance for high energy efficiency.

GREEN-MAX VAN



RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
12	5.00R12LT	10PR	88/86	P	3.50B	D 530 S 560	D 1168 S 1235	550	80
	155R12C	8PR	88/86	N	4.50B	D 530 S 560	D 1168 S 1235	450	65
13	155R13C	8PR	91/89	P	4 1/2J	D 580 S 615	D 1279 S 1356	450	65
	165R13C	8PR	94/93	R	4 1/2J	D 650 S 670	D 1433 S 1477	450	65
	165/70R13LT	8PR	88/85	S	5.00B	D 515 S 560	D 1135 S 1235	450	65
	175R13C	8PR	97/95	Q	5.00B	D 690 S 730	D 1521 S 1609	450	65
14	165/70R14 XL	-	85	H	5J	515	1135	340	50
	185/65R14 XL	-	90	H	5 1/2J	600	1323	340	50
	185/70R14 XL	-	92	H	5 1/2J	630	1389	340	50
	165/70R14C	6PR	89/87	R	5J	D 545 S 580	D 1201 S 1279	375	54
	175R14LT	8PR	99/97	R	5J	D 730 S 775	D 1609 S 1709	450	65
	175/70R14C	6PR	95/93	T	5J	D 650 S 690	D 1433 S 1521	375	54
	175/75R14LT	8PR	94/91	S	5J	D 615 S 670	D 1356 S 1477	450	65
	185R14C	8PR	102/100	R	5 1/2J	D 800 S 850	D 1764 S 1874	450	65
	195R14C	8PR	106/104	P	5 1/2J	D 900 S 950	D 1984 S 2094	450	65
	205R14C	8PR	109/107	R	6J	D 975 S 1030	D 2149 S 2271	450	65
15	185R15LT	8PR	103/102	R	5 1/2J	D 850 S 875	D 1874 S 1929	450	65
	195R15C	8PR	106/104	R	5 1/2J	D 900 S 950	D 1984 S 2094	450	65
	195/70R15C	8PR	104/102	R	6J	D 850 S 900	D 1874 S 1984	450	65
	205/70R15C	8PR	106/104	S	6J	D 900 S 950	D 1984 S 2094	450	65
	215/70R15C	8PR	109/107	R	6 1/2J	D 975 S 1030	D 2149 S 2271	450	65
	225/70R15C	8PR	112/110	R	6 1/2J	D 1060 S 1120	D 2337 S 2469	450	65
	255/70R15C	6PR	112/110	S	7 1/2J	D 1060 S 1120	D 2337 S 2469	375	54
16	185/75R16C	8PR	104/102	R	5J	D 850 S 900	D 1874 S 1984	475	69
	195/75R16C	8PR	107/105	R	5 1/2J	D 925 S 975	D 2039 S 2149	475	69
	205/75R16C	8PR	110/108	R	5 1/2J	D 1000 S 1060	D 2205 S 2337	475	69
	215/70R16C	6PR	108/106	T	6 1/2J	D 950 S 1000	D 2094 S 2205	375	54
	215/75R16C	8PR	113/111	R	6J	D 1090 S 1150	D 2403 S 2535	475	69
	225/75R16C	10PR	121/120	R	6J	D 1400 S 1450	D 3086 S 3197	575	83
	225/75R16LT	12PR	119/116	R	6J	D 1250 S 1360	D 2756 S 2998	650	94

GREEN-MAX VAN PLUS



Commercial tire with high grip performance

PERFORMANCE

- 1 Better grip performance.
- 2 Low rolling resistance for higher energy efficiency.
- 3 Excellent wear resistance performance.

GREEN-MAX VAN PLUS / HIGH LOAD



RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
12	145R12C	8PR	86/84	Q	4.00B	D 500 S 530	D 1100 S 1170	450	65
13	165R13C	8PR	94/93	R	4 1/2J	D 650 S 670	D 1433 S 1477	450	65
14	195R14C	8PR	106/104	P	5 1/2J	D 900 S 950	D 1984 S 2094	450	65
15	205/70R15C	8PR	106/104	S	6J	D 900 S 950	D 1984 S 2094	450	65
	215/70R15C	8PR	109/107	R	6 1/2J	D 975 S 1030	D 2149 S 2271	450	65



ALL SEASON & ALL WEATHER



CROSSWIND ULTRA SPORT+ | **CROSSWIND** | **HP818 PLUS** | **CROSSWIND HP818** | **CROSSWIND ECOTOURING**
P 39 | P 40 | P 42 | P 43 | P 45



CROSSWIND 4X4 HP | **CROSSWIND HT2** | **CROSSWIND H/T**
P 46 | P 47 | P 48



CROSSWIND TRAILTRAXX | **CROSSWIND AT-2** | **CROSSWIND A/T** | **CROSSWIND RUGGED TRAXX** | **CROSSWIND M/T**
P 49 | P 50 | P 51 | P 53 | P 54



RADIAL666 | **LMC5** | **LMC7** | **LMC4**
P 56 | P 57 | P 57 | P 58



RADIAL R781 | **CROSSWIND R781**
P 59 | P 60



GRIP MASTER 4S | **GREEN-MAX ALL SEASON** | **CROSSWIND A/T188** | **GREEN-MAX VAN 4S**
P 61 | P 63 | P 65 | P 66

CROSSWIND ULTRA SPORT+



KEY PRODUCTS TIRE

Excellent handling control
Excellent safety on dry and wet roads

PERFORMANCE

- 1 New generation of asymmetric ultra high performance tyre for summer. Make the tires have superior grip and braking performance and better handling.
- 2 BPT Technology--improve the actual contact area for better the handling performance.
- 3 3D sipes improves the stiffness of block, enabling better wet performance and snow performance.

CROSSWIND



Ultra high performance

PERFORMANCE

- 1 Directional tread pattern design.
- 2 Excellent handling performance.
- 3 Low noise.

CROSSWIND | UHP



RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
13	175/50R13 XL	76	V	5.50B	400	882	340	50
14	185/50R14	77	V	6J	412	908	300	44
15	195/50R15	82	V	6J	475	1047	300	44
	195/55R15	85	H	6J	515	1135	300	44
16	195/45R16 XL	84	V	6 1/2J	500	1102	340	50
	205/45R16 XL	87	W	7J	545	1201	340	50
	205/50R16	87	V	6 1/2J	545	1201	300	44
	205/50R16	87	W	6 1/2J	545	1201	300	44
	205/55R16 XL	94	W	6 1/2J	670	1477	340	50
	215/40R16 XL	86	W	7 1/2J	530	1168	340	50
	215/55R16 XL	97	W	7J	730	1609	340	50
	225/50R16 XL	96	V	7J	710	1565	340	50
17	205/40R17 XL	84	W	7 1/2J	500	1102	340	50
	205/45R17 XL	88	W	7J	560	1235	340	50
	205/50R17 XL	93	W	6 1/2J	650	1433	340	50
	215/40R17 XL	87	W	7 1/2J	545	1201	340	50
	215/45R17 XL	91	W	7J	615	1356	340	50
	215/50R17	91	V	7J	615	1356	300	44
	215/50R17 XL	95	W	7J	690	1521	340	50
	215/55R17 XL	98	W	7J	750	1653	340	50
	225/45R17 XL	94	W	7 1/2J	670	1477	340	50
	225/50R17 XL	98	W	7J	750	1653	340	50
	225/55R17 XL	101	W	7J	825	1819	340	50
	235/45R17 XL	97	W	8J	730	1609	340	50
	235/55R17 XL	103	W	7 1/2J	875	1929	340	50
	245/40R17 XL	95	W	8 1/2J	690	1521	340	50
18	245/45R17 XL	99	W	8J	775	1709	340	50
	215/35R18 XL	84	W	7 1/2J	500	1102	340	50
	225/40R18 XL	92	W	8J	630	1389	340	50
	225/45R18 XL	95	W	7 1/2J	690	1521	340	50
	225/50R18	95	V	7J	690	1521	300	44
	235/40R18 XL	95	W	8 1/2J	690	1521	340	50

CROSSWIND ULTRA SPORT+ | UHP



RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
20	275/40R20	106	W	9 1/2J	950	2094	340	50



CROSSWIND | UHP



RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
18	235/45R18	94	W	8J	670	1477	300	44
	235/50R18 XL	101	W	7 1/2J	825	1819	340	50
	245/40R18 XL	97	W	8 1/2J	730	1609	340	50
	245/45R18 XL	100	W	8J	800	1765	340	50
	255/45R18 XL	103	W	8 1/2J	875	1929	340	50
	265/35R18 XL	97	H	9 1/2J	730	1609	340	50
	265/60R18 XL	114	H	8J	1180	2601	340	50
19	225/35R19 XL	88	W	8J	560	1235	340	50
	235/35R19 XL	91	W	8 1/2J	615	1356	340	50
	235/40R19 XL	96	V	8 1/2J	710	1565	340	50
	235/55R19 XL	105	W	7 1/2J	925	2039	340	50
	245/40R19 XL	98	W	8 1/2J	750	1653	340	50
	255/35R19 XL	96	W	9J	710	1565	340	50
	265/30R19 XL	93	W	9 1/2J	650	1433	340	50
20	225/35R20 XL	90	W	8J	600	1323	340	50
	235/30R20 XL	88	Y	8 1/2J	560	1235	340	50
	235/45R20 XL	100	W	8J	800	1765	340	50
	245/35R20 XL	95	W	8 1/2J	690	1521	340	50
	245/45R20 XL	103	W	8J	875	1929	340	50
	245/50R20	102	V	7 1/2J	850	1874	300	44
	255/35R20 XL	97	W	9J	730	1609	340	50
	265/45R20	104	W	9J	900	1984	300	44
	265/50R20 XL	111	V	8 1/2J	1090	2403	340	50
	275/40R20 XL	106	W	9 1/2J	950	2094	340	50
	275/45R20 XL	110	V	9J	1060	2337	340	50
	275/50R20 XL	113	W	8 1/2J	1150	2535	340	50
	275/55R20 XL	117	W	8 1/2J	1285	2833	340	50
	275/55R20 XL	117	W	8 1/2J	1285	2833	340	50
22	235/30R22 XL	90	W	8 1/2J	600	1323	340	50
	245/30R22 XL	92	W	8 1/2J	630	1389	340	50
	255/30R22 XL	95	V	9J	730	1609	340	50
	265/35R22 XL	102	W	9 1/2J	850	1874	340	50
	305/40R22 XL	114	V	11J	1180	2601	340	50
	305/45R22 XL	118	V	10J	1320	2910	340	50
24	305/35R24 XL	112	V	11J	1120	2469	340	50
26	305/30R26 XL	109	W	11J	1030	2271	340	50

HP010 PLUS



PCR tire with high grip performance

PERFORMANCE

- 1 Adopt 3D steel sheet design to improve grip performance.
- 2 Groove depth design with reasonable patterns increases tire wear mileage.
- 3 The small vertical pattern design on the shoulder enhances drainage performance.

HP010 PLUS | HP



RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
14	175/65R14	82	H	5J	475	1047	300	44
	185/65R14	86	H	5 1/2J	530	1168	300	44
	185/70R14	88	T	5 1/2J	560	1235	300	44
	195/70R14	91	T	6J	615	1356	300	44
15	185/60R15	84	H	5 1/2J	500	1102	300	44
	185/65R15	88	H	5 1/2J	560	1235	300	44
	195/60R15	88	H	6J	560	1235	300	44
	195/65R15	91	H	6J	615	1356	300	44
	205/60R15	91	H	6J	615	1356	300	44
	205/65R15	94	H	6J	670	1477	300	44
16	215/70R15	98	T	6 1/2J	750	1653	300	44
	195/55R16	87	H	6J	545	1201	300	44
	205/55R16	91	H	6 1/2J	615	1356	300	44
	205/60R16	92	H	6J	630	1389	300	44
	215/55R16	93	H	7J	650	1433	300	44
	215/60R16	95	V	6 1/2J	690	1521	300	44
	215/65R16	98	H	6 1/2J	750	1653	300	44
	215/70R16	100	T	6 1/2J	800	1764	300	44
	225/65R16	100	H	6 1/2J	800	1764	300	44
	225/60R16	98	H	6 1/2J	750	1653	300	44
	235/60R16	100	H	7J	800	1764	300	44
	235/65R16	103	H	7J	875	1929	300	44
17	215/45R17 XL	91	W	7J	615	1356	340	50
	215/50R17	91	V	7J	615	1356	300	44
	215/55R17	94	V	7J	670	1477	300	44
	215/60R17	96	H	6 1/2J	710	1565	300	44
	215/65R17	99	H	6 1/2J	775	1709	300	44
	225/45R17 XL	94	W	7 1/2J	670	1477	340	50
	225/50R17 XL	98	V	7J	750	1653	340	50
	225/55R17	97	V	7J	730	1609	300	44
	225/60R17	99	H	6 1/2J	775	1709	300	44
	225/65R17	102	H	6 1/2J	850	1874	300	44

HP⁸¹⁸ PLUS / HP



RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
17	235/45R17 XL	97	V	8J	730	1609	340	50
	235/55R17	99	V	7 1/2J	775	1709	300	44
	235/60R17	102	H	7J	850	1874	300	44
	235/65R17	104	H	7J	900	1984	300	44
18	215/55R18 XL	99	H	7J	775	1709	340	50
	225/40R18 XL	92	W	8J	630	1389	340	50
	225/45R18 XL	95	W	7 1/2J	690	1521	340	50
	225/50R18	95	W	7J	690	1521	300	44
	225/55R18	98	H	7J	750	1653	300	44
	225/60R18	100	H	6 1/2J	800	1764	300	44
	235/50R18	97	W	7 1/2J	730	1609	300	44
	235/55R18 XL	104	V	7 1/2J	900	1984	340	50
	235/60R18	103	H	7J	875	1929	300	44
	235/65R18	106	H	7J	950	2094	300	44
	245/40R18 XL	97	W	8 1/2J	730	1609	340	50
	245/45R18 XL	100	W	8J	800	1764	340	50
19	245/60R18	105	H	7J	925	2039	300	44
	255/65R18	111	H	7 1/2J	1090	2403	300	44
	225/55R19	99	V	7J	775	1709	300	44
	225/45R19 XL	96	W	7 1/2J	710	1565	340	50
	235/40R19 XL	96	V	8 1/2J	710	1565	340	50
	235/55R19 XL	105	V	7 1/2J	925	2039	340	50
	245/45R19 XL	102	V	8J	850	1874	340	50
	255/45R19 XL	104	V	8 1/2J	900	1984	340	50
	255/60R19	109	H	7 1/2J	1030	2271	300	44

CROSSWIND HP⁸¹⁸



HP Tire with Excellent Handling
Perormance,High mileage and Low noise

PERFORMANCE

- 1 Comfortable and quiet ride.
- 2 Excellent handling performance.
- 3 Enhanced wet grip to effectively reduce risk of hydroplaning.

CROSSWIND HP⁸¹⁸ / HP



RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
12	155/70R12 WL	73	T	4.50B	365	805	300	44
	165/70R12 WL	77	T	5.00B	412	908	300	44
14	165/55R14	72	V	5J	355	783	300	44
	175/65R14	82	H	5J	475	1047	300	44
	175/70R14	84	T	5J	500	1102	300	44
15	175/65R15	84	H	5J	500	1102	300	44

Three Grooves

CROSSWIND HP⁸¹⁸



HP Tire with Excellent Handling
Perormance,High mileage and Low noise

PERFORMANCE

- 1 Good straight driving stability.
- 2 Comfortable and quiet ride.
- 3 Excellent handling performance.
- 4 Enhanced wet grip to effectively reduce risk of hydroplaning.

CROSSWIND HP⁸¹⁸ / HP



RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
14	185/60R14	82	H	5 1/2J	475	1047	300	44
	185/60R14	82	V	5 1/2J	475	1047	300	44
	185/65R14	86	H	5 1/2J	530	1168	300	44
	185/70R14	88	H	5 1/2J	560	1235	300	44
	185/70R14 XL	92	H	5 1/2J	630	1389	340	50
	195/70R14	91	H	6J	615	1356	300	44
	195/70R14 WL	91	H	6J	615	1356	300	44
15	185/60R15	84	H	5 1/2J	500	1102	300	44
	185/65R15	88	H	5 1/2J	560	1235	300	44
	195/50R15	82	V	6J	475	1047	300	44
	195/55R15	85	V	6J	515	1135	300	44
	195/60R15	88	H	6J	560	1235	300	44
	195/65R15	91	H	6J	615	1356	300	44
	205/60R15	91	H	6J	615	1356	300	44
	205/65R15	94	H	6J	670	1477	300	44
	215/60R15	94	H	6 1/2J	670	1477	300	44
	215/65R15	96	H	6 1/2J	710	1565	300	44
	215/65R15 XL	100	H	6 1/2J	800	1765	340	50
	255/70R15	108	S	7 1/2J	1000	2094	300	44
16	185/55R16	83	V	6J	487	1074	300	44
	195/50R16	84	V	6J	500	1102	300	44
	195/55R16	87	H	6J	545	1201	300	44
	195/60R16 XL	93	H	6J	650	1433	340	50
	205/55R16	91	H	6 1/2J	615	1356	300	44
	205/60R16	92	H	6J	630	1389	300	44
	205/60R16	92	V	6J	630	1389	300	44
	205/60R16 XL	96	H	6J	710	1565	340	50
	215/55R16	93	H	7J	650	1433	300	44
	215/55R16 XL	97	H	7J	730	1609	340	50
	215/60R16	95	H	6 1/2J	690	1521	300	44
	215/65R16	98	H	6 1/2J	750	1653	300	44
	225/55R16	95	V	7J	690	1521	300	44
	225/60R16	98	H	6 1/2J	750	1653	300	44
	225/65R16	100	H	6 1/2J	800	1765	300	44
	225/70R16	103	H	6 1/2J	875	1929	300	44
	235/60R16	100	H	7J	800	1765	300	44
17	235/65R16	103	H	7J	875	1929	300	44
	215/50R17	91	V	7J	615	1356	300	44
	215/55R17	94	V	7J	670	1477	300	44
	215/60R17	96	H	6 1/2J	710	1565	300	44
	215/65R17	99	H	6 1/2J	775	1709	300	44
	225/45R17	91	H	7 1/2J	615	1356	300	44
	225/50R17	94	V	7J	670	1477	300	44
	225/55R17	97	H	7J	730	1609	300	44
	225/60R17	99	H	6 1/2J	775	1709	300	44
	225/65R17	102	H	6 1/2J	850	1874	300	44
18	235/55R17	99	H	7 1/2J	775	1709	300	44
	235/60R17	102	H	7J	850	1874	300	44
	235/65R17	104	H	7J	900	1984	300	44
	225/55R18	98	H	7J	750	1653	300	44
	235/65R18	106	H	7J	950	2094	300	44

Four Grooves

CROSSWIND ECOTOURING



Super Wear Resistance
PERFORMANCE

- 1 Ultra mileage tire.
- 2 Low noise.
- 3 Improved water evacuation.

CROSSWIND ECOTOURING / ECO



PCR

RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
12	175/70R12	80	H	5.00B	450	992	300	44
	165/60R13	73	T	5.00B	365	805	300	44
13	175/70R13	82	T	5.00B	475	1047	300	44
	175/75R13	84	T	5J	500	1102	300	44
14	175/65R14	82	T	5J	475	1047	300	44
	175/75R14	86	T	5J	530	1168	300	44

Three Grooves

CROSSWIND ECOTOURING / ECO



PCR

RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
13	185/70R13	86	T	5.50B	530	1168	300	44
14	185/65R14	86	T	5 1/2J	530	1168	300	44
	185/70R14	88	T	5 1/2J	560	1235	300	44
	195/70R14	91	T	6J	615	1356	300	44
	185/65R15	88	T	5 1/2J	560	1235	300	44
	195/50R15	82	H	6J	475	1047	300	44
	195/60R15	88	H	6J	560	1235	300	44
	195/65R15	91	H	6J	615	1356	300	44
	205/60R15	91	H	6J	615	1356	300	44
	205/65R15	94	H	6J	670	1477	300	44
	205/70R15	96	T	6J	710	1565	300	44
	205/75R15	97	S	5 1/2J	730	1609	300	44
	215/70R15	98	T	6 1/2J	750	1653	300	44
	215/75R15	100	S	6J	800	1765	300	44
	225/70R15	100	T	6 1/2J	800	1765	300	44
	225/75R15	102	S	6J	850	1874	300	44
	235/75R15	105	S	6 1/2J	925	2039	300	44
	205/55R16	91	H	6 1/2J	615	1356	300	44
	205/60R16	92	H	6J	630	1389	300	44
	205/65R16	95	H	6J	690	1521	300	44
	215/60R16	95	H	6 1/2J	690	1521	300	44
	215/65R16	98	H	6 1/2J	750	1653	300	44
	215/70R16	100	T	6 1/2J	800	1765	300	44
	225/60R16	98	H	6 1/2J	750	1653	300	44
	225/65R16	100	H	6 1/2J	800	1765	300	44
	225/70R16 XL	107	H	6 1/2J	975	2149	340	50
	235/70R16	106	H	7J	950	2094	300	44
	245/70R16	107	H	7J	975	2149	300	44
	245/75R16	111	H	7J	1090	2403	300	44
	255/70R16	111	S	7 1/2J	1090	2403	300	44
	265/70R16	112	S	8J	1120	2469	300	44
	265/75R16	116	H	7 1/2J	1250	2756	300	44

Four Grooves

CROSSWIND 4X4 HP



SUV tire with low rolling resistance
and low noise

PERFORMANCE

- 1 Excellent handling performance.
- 2 Enhanced drainage performance to effectively reduce risk of hydroplaning.
- 3 Superior longitudinal stability for more comfortable ride.
- 4 Low noise to offer a quiet ride.

CROSSWIND 4X4 HP / HP/UHP



SUV

RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
15	205/70R15	96	H	6J	710	1565	300	44
	205/70R16	97	V	6J	730	1609	300	44
	215/65R16 XL	102	H	6 1/2J	850	1874	340	50
	215/70R16	100	H	6 1/2J	800	1764	300	44
	225/65R16	100	H	6 1/2J	800	1764	300	44
	225/75R16	104	H	6J	900	1984	300	44
	235/60R16	100	H	7J	800	1764	300	44
	235/70R16	106	H	7J	950	2094	300	44
	245/70R16 XL	111	H	7J	1090	2403	340	50
	265/70R16	112	H	8J	1120	2469	300	44
	275/70R16	114	H	8J	1180	2601	300	44
	215/60R17	96	H	6 1/2J	710	1565	300	44
	225/55R17 XL	101	V	7J	825	1819	340	50
	225/65R17	102	H	6 1/2J	850	1874	300	44
	235/55R17 XL	103	V	7 1/2J	875	1929	340	50
	235/60R17 XL	106	V	7J	950	2094	340	50
	235/65R17 XL	108	V	7J	1000	2205	340	50
	245/65R17 XL	111	H	7J	1090	2403	340	50
	255/60R17	106	H	7 1/2J	950	2094	300	44
	255/65R17	110	H	7 1/2J	1060	2337	300	44
	265/65R17	112	H	8J	1120	2469	300	44
	275/55R17	109	V	8 1/2J	1030	2271	300	44
	225/55R18	98	V	7J	750	1653	300	44
	225/60R18	100	H	6 1/2J	800	1764	300	44
	235/55R18 XL	104	V	7 1/2J	900	1984	340	50
	235/60R18 XL	107	V	7J	975	2149	340	50
	235/65R18	106	H	7J	950	2094	300	44
	245/60R18	105	V	7J	925	2039	300	44
	255/55R18 XL	109	V	8J	1030	2271	340	50
	255/60R18 XL	112	V	7 1/2J	1120	2469	340	50
	255/65R18	111	H	7 1/2J	1090	2403	300	44
	265/60R18	110	H	8J	1060	2337	300	44
	265/65R18	114	H	8J	1180	2601	300	44
	265/70R18	116	T	8J	1250	2756	300	44
	275/60R18	113	H	8J	1150	2535	300	44
	275/65R18	116	H	8J	1250	2756	300	44
	235/50R19 XL	103	V	7 1/2J	875	1929	340	50
	235/55R19 XL	105	V	7 1/2J	925	2039	340	50
	245/55R19	103	V	7 1/2J	875	1929	300	44
	255/50R19 XL	107	W	8J	975	2149	340	50
	255/55R19 XL	111	V	8J	1090	2403	340	50
	255/60R19	109	H	7 1/2J	1030	2271	300	44
	235/55R20 XL	105	V	7 1/2J	925	2039	340	50
	245/50R20	102	V	7 1/2J	850	1874	300	44
	255/50R20 XL	109	V	8J	1030	2271	340	50
	265/50R20 XL	111	V	8 1/2J	1090	2403	340	50
	275/55R20 XL	117	V	8 1/2J	1285	2833	340	50

CROSSWIND HT²



All-season Performance
Long&Regular Wear

PERFORMANCE

- 1 High performance all-season highway tire designed for North American luxury SUV.
- 2 Excellent dry and wet handling performance maintains quiet highway driving.
- 3 Multiple variable pitches design combined with optimized pitch ratio and arrangement reduce noise and enhance handling performance.

CROSSWIND HT² / HT



RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
15	235/75R15	105	T	6 1/2J	925	2039	300	44
16	215/70R16	100	H	6 1/2J	800	1764	300	44
	225/70R16	103	T	6 1/2J	875	1929	300	44
	235/70R16	106	T	7J	950	2094	300	44
	245/70R16	107	T	7J	975	2149	300	44
	255/70R16	111	T	7 1/2J	1090	2403	300	44
	265/70R16	112	T	8J	1120	2469	300	44
	265/75R16	116	T	7 1/2J	1250	2756	300	44
	245/75R16	111	T	7J	1090	2403	300	44
17	215/65R17	99	T	6 1/2J	775	1709	300	44
	225/60R17	99	H	6 1/2J	775	1709	300	44
	235/60R17 XL	106	H	7J	950	2094	340	50
	235/65R17	104	T	7J	900	1984	300	44
	235/70R17	107	T	7J	975	2149	300	44
	245/65R17	107	T	7J	975	2149	300	44
	245/70R17	110	T	7J	1060	2337	300	44
	255/65R17	110	T	7 1/2J	1060	2337	300	44
	265/65R17	112	T	8J	1120	2469	300	44
18	225/55R18	98	H	7J	750	1653	300	44
	235/55R18 XL	104	H	7 1/2J	900	1984	340	50
	235/60R18 XL	107	H	7J	975	2149	340	50
	235/65R18	106	H	7J	950	2094	300	44
	245/60R18	105	H	7J	925	2039	300	44
	255/55R18	105	H	8J	925	2039	300	44
	255/65R18	111	T	7 1/2J	1090	2403	300	44
	255/70R18	113	T	7 1/2J	1150	2535	300	44
	265/65R18	114	T	8J	1180	2601	300	44
	265/70R18	116	T	8J	1250	2756	300	44
	275/65R18	116	T	8J	1250	2756	300	44
	235/55R19	101	H	7 1/2J	825	1819	300	44
19	245/55R19	103	H	7 1/2J	875	1929	300	44
	255/50R19 XL	107	H	8J	975	2149	340	50
	255/60R19	109	H	7 1/2J	1030	2271	300	44
	235/55R20	102	H	7 1/2J	850	1874	300	44
20	245/60R20	107	H	7J	975	2149	300	44
	245/50R20	102	H	7 1/2J	850	1874	300	44
	255/50R20 XL	109	H	8J	1030	2271	340	50
	255/60R20 XL	113	T	8J	1150	2535	340	50
	265/50R20	107	H	8 1/2J	975	2149	300	44
	275/55R20	113	H	8 1/2J	1150	2535	300	44
	275/60R20	115	T	8J	1215	2679	300	44
22	285/45R22	110	H	9 1/2J	1060	2337	300	44

CROSSWIND H/T



Suv Tire For Highway-terrain
With Low Noise And Good Dry/wet
Performance.

PERFORMANCE

- 1 High drainage capability.
- 2 High comfort and low noise.
- 3 Excellent handling performance.

CROSSWIND H/T / HT



RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
15	235/75R15 XL	-	109	T	6 1/2J	1030	2271	340	50
	31X10.50R15LT	6PR	109	R	8 1/2J	1030	2270	350	50
	31X10.50R15LT	6PR	109	Q	8 1/2J	1030	2270	350	50
16	215/70R16	-	100	T	6 1/2J	800	1764	300	44
	225/70R16	-	103	T	6 1/2J	875	1929	300	44
	225/70R16 XL	-	107	T	6 1/2J	975	2149	340	50
	235/70R16	-	106	T	7J	950	2094	300	44
	245/70R16	-	107	T	7J	975	2149	300	44
	245/75R16	-	111	T	7J	1090	2403	300	44
	255/70R16	-	111	T	7 1/2J	1090	2403	300	44
	265/70R16	-	112	T	8J	1120	2469	300	44
	265/75R16	-	116	T	7 1/2J	1250	2756	300	44
	LT215/85R16	10PR	115/112	S	6J	D 1120 S 1215	D 2470 S 2680	550	80
	LT215/85R16	10PR	115/112	Q	6J	D 1120 S 1215	D 2470 S 2680	550	80
	LT225/75R16	10PR	115/112	S	6J	D 1120 S 1215	D 2470 S 2680	550	80
	LT225/75R16	10PR	115/112	Q	6J	D 1120 S 1215	D 2470 S 2680	550	80
	LT235/85R16	10PR	120/116	R	6 1/2J	D 1250 S 1400	D 2755 S 3085	550	80
	LT235/85R16	10PR	120/116	Q	6 1/2J	D 1250 S 1400	D 2755 S 3085	550	80
	LT245/75R16	10PR	120/116	R	7J	D 1250 S 1400	D 2755 S 3085	550	80
	LT245/75R16	10PR	120/116	Q	7J	D 1250 S 1400	D 2755 S 3085	550	80
	LT265/75R16	10PR	123/120	R	7 1/2J	D 1400 S 1550	D 3085 S 3415	550	80
17	235/65R17	-	104	T	7J	900	1984	300	44
	245/65R17	-	107	T	7J	975	2149	300	44
	245/70R17	-	110	T	7J	1060	2337	300	44
	265/65R17	-	112	T	8J	1120	2469	300	44
	265/70R17	-	115	T	8J	1215	2679	300	44
	275/65R17	-	115	S	8J	1215	2679	300	44
	285/65R17	-	116	S	8 1/2J	1250	2756	300	44
	LT245/75R17	10PR	121/118	R	7J	D 1320 S 1450	D 2910 S 3195	550	80
	LT245/75R17	10PR	121/118	Q	7J	D 1320 S 1450	D 2910 S 3195	550	80
	LT265/70R17	10PR	121/118	R	8J	D 1320 S 1450	D 2910 S 3195	550	80
	LT265/70R17	10PR	121/118	Q	8J	D 1320 S 1450	D 2910 S 3195	550	80
18	LT265/70R18	10PR	124/121	R	8J	D 1450 S 1600	D 3195 S 3525	550	80
20	275/55R20 XL	-	117	T	8 1/2J	1285	2833	340	50

CROSSWIND TRAILTRAXX



KEY PRODUCTS TIRE

All weather applicability
All terrain durability

PERFORMANCE

- 1 Security assurance with any adventure, any terrain and in any weather.
- 2 Driving with low noise, high traction and robustness off-road, also handling snow road easily.
- 3 Outstanding mileage for heavy pickup and 4X4 vehicles.

CROSSWIND TRAILTRAXX / AT



RIM	Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
20	35X12.50R20LT	F	125	Q	10J	1650	3640	550	80
	275/60R20	-	115	T	8J	1215	2679	300	44
	LT275/65R20	E	126/123	Q	8J	1700/1550	3750/3415	550	80
	LT285/55R20	E	122/119	Q	9J	1500/1360	3305/3000	550	80
	275/55R20	-	117	S	8 1/2J	1285	2833	340	50
	LT285/60R20	E	125/122	Q	8 1/2J	1650/1500	3640/3305	550	80
22	33X12.50R20LT	F	119	Q	10J	1360	3000	550	80
	285/45R22	-	110	Q	9 1/2J	1060	2337	300	44
	35X12.50R22LT	F	121	Q	10J	1450	3195	550	80

CROSSWIND AT-2



All Terrain Tire with High
Wear Resistance

PERFORMANCE

- 1 Professional off-road tires.
- 2 High-strength sidewall for puncture resistance.
- 3 The groove bottom divider and anti-pinch rocks design provide excellent self-cleaning performance.

CROSSWIND AT-2 / AT



RIM	Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
15	31X10.50R15LT WL	6PR	109	Q	8 1/2J	1030	2270	350	50
16	265/70R16 XL WL	-	116	Q	8J	1250	2756	340	50
	245/70R16 XL WL	-	111	Q	7J	1090	2403	340	50
17	265/65R17 XL WL	-	116	Q	8J	1250	2756	340	50
18	265/60R18 XL WL	-	114	Q	8J	1180	2601	340	50
20	265/50R20 XL WL	-	111	Q	8 1/2J	1090	2403	340	50

CROSSWIND TRAILTRAXX / AT



RIM	Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
16	LT225/75R16	E	115/112	Q	6J	1215/1120	2680/2470	550	80
	LT265/75R16	E	123/120	Q	7 1/2J	1550/1400	3415/3085	550	80
	LT245/75R16	E	120/116	Q	7J	1380/1260	3042/2778	550	80
	265/75R16	-	116	S	7 1/2J	1250	2756	300	44
	235/70R16	-	106	S	7J	950	2094	300	44
	LT285/75R16	E	126/123	Q	8J	1700/1550	3750/3415	550	80
	265/70R16	-	112	S	8J	1120	2469	300	44
	245/75R16	-	111	S	7J	1090	2403	300	44
17	285/70R17	-	116	T	8 1/2J	1250	2756	300	44
	LT265/70R17	E	123/120	Q	8J	1550/1400	3415/3085	550	80
	LT245/75R17	E	121/118	Q	7J	1450/1320	3195/2910	550	80
	265/70R17	-	115	S	8J	1215	2679	300	44
	LT285/70R17	E	126/123	Q	8 1/2J	1700/1550	3750/3415	550	80
	LT315/70R17	E	126/123	Q	9 1/2J	1700/1550	3750/3415	450	65
	245/65R17	-	111	H	7J	1090	2403	340	50
	35X12.50R17LT	E	125	Q	10J	1650	3640	450	65
18	265/65R17	-	116	S	8J	1250	2756	340	50
	255/70R18	-	113	T	7 1/2J	1150	2535	300	44
	LT295/70R18	E	129/126	Q	8 1/2J	1850/1700	4080/3750	550	80
	275/65R18	-	116	T	8J	1250	2756	300	44
	265/70R18	-	116	T	8J	1250	2756	300	44
	LT275/70R18	E	125/122	Q	8J	1650/1500	3640/3305	550	80
	LT275/65R18	E	123/120	Q	8J	1550/1400	3415/3085	550	80
	265/60R18	-	110	T	8J	1060	2337	300	44
	35X12.50R18LT	F	128	Q	10J	1800	3970	550	80

CROSSWIND A/T



All Terrain Tire

PERFORMANCE

- 1 Excellent wet performance.
- 2 Large angle grooves to improve self-cleaning ability.
- 3 An optimal balance between performance on road and off road.

CROSSWIND A/T AT



RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
14	175/70R14 XL	-	88	H	5J	560	1235	340	50
	175/75R14	-	86	T	5J	530	1168	300	44
	175/80R14	-	88	T	5J	560	1235	300	44
15	205/60R15	-	91	H	6J	615	1356	300	44
	205/65R15	-	94	H	6J	670	1477	300	44
	205/70R15	-	96	T	6J	710	1565	300	44
	225/75R15	-	102	S	6J	850	1874	300	44
	235/75R15 XL	-	109	T	6 1/2J	1030	2271	340	50
	255/70R15	-	108	T	7 1/2J	1000	2205	300	44
	265/70R15	-	112	T	8J	1120	2469	300	44
	265/70R15 OWL	-	112	S	8J	1120	2469	300	44
	265/70R15 OWL	-	112	Q	8J	1120	2469	300	44
	31X10.50R15LT	6PR	109	R	8 1/2J	1030	2271	350	51
	31X10.50R15LT OWL	6PR	109	Q	8 1/2J	1030	2271	350	51
	LT215/75R15	6PR	100/97	S	6J	D 730 S 800	D 1610 S 1765	350	51
	LT215/75R15	6PR	100/97	Q	6J	D 730 S 800	D 1610 S 1765	350	51
	LT225/75R15	6PR	102/99	S	6J	D 775 S 850	D 1710 S 1875	350	51
	LT235/75R15	6PR	104/101	R/S	6 1/2J	D 825 S 900	D 1820 S 1985	350	50
16	LT235/75R15	6PR	104/101	Q	6 1/2J	D 825 S 900	D 1820 S 1985	350	50
	LT235/75R15 OWL	6PR	104/101	Q	6 1/2J	D 825 S 900	D 1819 S 1985	350	50
	LT235/75R15	10PR	116/113	S	6 1/2J	D 1150 S 1250	D 2535 S 2755	550	80
	205/60R16	-	92	H	6J	630	1389	300	44
	215/65R16	-	98	T	6 1/2J	750	1653	300	44
	215/70R16	-	100	T	6 1/2J	800	1764	300	44
	225/70R16	-	103	T	6 1/2J	875	1929	300	44
	225/70R16 XL	-	107	T	6 1/2J	975	2149	340	50
	235/70R16	-	106	T/Q	7J	950	2094	300	44
	245/70R16 XL	-	111	T	7J	1090	2403	340	50
	245/75R16	-	111	T	7J	1090	2403	300	44
	255/70R16	-	111	S	7 1/2J	1090	2403	300	44
	265/70R16 OWL	-	112	Q/T	8J	1120	2469	300	44
	265/75R16 OWL	-	116	T/Q	7 1/2J	1250	2756	300	44
	275/70R16 OWL	-	114	S	8J	1180	2601	300	44
20	275/70R16 OWL	-	114	Q	8J	1180	2601	300	44
	205R16LT	8PR	110/108	R/Q	6J	D 1000 S 1060	D 2205 S 2337	450	65
	LT215/85R16	10PR	115/112	Q	6J	D 1120S 1215	D 2470 S 2680	550	80
	LT225/75R16	10PR	115/112	Q	6J	D 1120S 1215	D 2470 S 2680	550	80
	LT235/85R16	10PR	120/116	S	6 1/2J	D 1250S 1400	D 2755 S 3085	550	80

CROSSWIND A/T AT



RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
16	LT235/85R16	10PR	120/116	Q	6 1/2J	D 1250 S 1400	D 2755 S 3085	550	80
	LT245/75R16	10PR	120/116	Q	7J	D 1260 S 1380	D 2778 S 3042	550	80
	LT265/75R16	8PR	119/116	Q	7 1/2J	D 1250 S 1360	D 2755 S 3000	450	65
	LT265/75R16	10PR	123/120	R	7 1/2J	D 1400 S 1550	D 3085 S 3415	550	80
	LT285/75R16	10PR	126/123	R	8J	D 1550 S 1700	D 3415 S 3750	550	80
	LT305/70R16	10PR	124/121	R	9J	D 1450 S 1600	D 3195 S 3525	450	65
17	225/65R17 XL WL	-	106	T	6 1/2J	950	2094	340	50
	225/65R17 XL	-	106	T	6 1/2J	950	2094	340	50
	235/65R17	-	104	T	7J	900	1984	300	44
	245/65R17 XL	-	111	T	7J	1090	2403	340	50
	245/70R17	-	110	S	7J	1060	2337	300	44
	265/65R17	-	112	T/Q	8J	1120	2469	300	44
	265/70R17	-	115	T	8J	1215	2679	300	44
	275/65R17 XL WL	-	119	T	8J	1360	2998	340	50
	P285/70R17 OWL	-	117	T	8 1/2J	1285	2833	300	44
	P285/70R17 OWL	-	117	Q	8 1/2J	1285	2833	300	44
	LT235/80R17 OWL	10PR	120/117	R	6 1/2J	D 1285 S 1400	D 2835 S 3085	550	80
	LT235/80R17 OWL	10PR	120/117	Q	6 1/2J	D 1285 S 1400	D 2835S 3085	550	80
	LT245/70R17 WL	10PR	119/116	Q	7J	D 1250 S 1360	D 2755 S 3000	550	80
	LT245/75R17 OWL	10PR	121/118	R	7J	D 1320 S 1450	D 2910 S 3195	550	80
	LT245/75R17 OWL	10PR	121/118	Q	7J	D 1320 S 1450	D 2910 S 3195	550	80
	LT265/70R17 OWL	10PR	121/118	R/Q	8J	D 1320 S 1450	D 2910 S 3195	550	80
	LT285/70R17 OWL	8PR	121/118	S	8 1/2J	D 1320 S 1450	D 2910 S 3195	450	65
	LT285/70R17 OWL	8PR	121/118	Q	8 1/2J	D 1320 S 1450	D 2910 S 3195	450	65
18	LT305/70R17 OWL	8PR	119/116	R	9J	D 1250 S 1360	D 2755 S 3000	350	51
	LT305/70R17 OWL	8PR	119/116	Q	9J	D 1250 S 1360	D 2755 S 3000	350	51
	235/60R18 XL WL	-	107	T	7J	975	2149	340	50
	255/55R18 XL WL	-	109	T	8J	1030	2271	340	50
	265/60R18	-	110	T	8J	1060	2337	300	44
	265/60R18	-	110	Q	8J	1060	2337	300	44
	265/60R18 WL	-	110	T	8J	1060	2337	300	44
	265/70R18	-	116	T	8J	1250	2756	300	44
	265/70R18 OWL	-	116	Q	8J	1250	2756	300	44
	275/65R18 OWL	-	116	T	8J	1250	2756	300	44
	275/65R18 OWL	-	116	Q	8J	1250	2756	300	44
	285/60R18	-	116	T	8 1/2J	1250	2756	300	44
20	285/60R18 WL	-	116	T	8 1/2J	1250	2756	300	44
	285/60R18	-	116	Q	8 1/2J	1250	2756	300	44
	LT265/70R18	10PR	124/121	S	8J	D 1450 S 1600	D 3195 S 3525	550	80
	LT275/65R18	10PR	123/120	S	8J	D 1400 S 1550	D 3085 S 3415	550	80
	LT275/70R18	8PR	121/118	Q	8J	D 1320 S 1450	D 2910 S 3195	450	65
	LT275/70R18	10PR	125/122	S	8J	D 1500 S 1650	D 3305 S 3640	550	80
	P275/55R20	-	111	S	8 1/2J	1090	2403	300	44
	P275/60R20	-	114	T	8J	1180	2601	300	44
	LT265/60R20 WL	10PR	121/118	R	8J	D 1320 S 1450	D 2910 S 3195	550	80
	LT265/60R20 OWL	10PR	121/118	Q	8J	D 1320 S 1450	D 2910 S 3195	550	80
20	LT275/65R20	10PR	126/123	S	8J	D 1550 S 1700	D 3415 S 3750	550	80
	LT285/55R20	10PR	122/119	S	9J	D 1360 S 1500	D 3000 S 3305	550	80
	LT285/65R20	10PR	127/124	S	8 1/2J	D 1600 S 1750	D 3525S 3860	550	80
	35X12.50R20LT	10PR	121	Q	10J	1450	3195	450	65

CROSSWIND
RUGGED TRAXX



KEY PRODUCTS TIRE

High off-road traction performance
High durability

PERFORMANCE

- 1 High floatation; High load-carrying capacity.
- 2 Aggressive tread pattern and sidewall design.
- 3 The Magic Rock blocks deal with all kinds of harsh terrain and climate.
- 4 The open shoulder grooves and large trench volume ,improve the drainage of mud and snow under bad road conditions.

CROSSWIND M/T



Mud-Terrain Tire

PERFORMANCE

- 1 High floatation.
- 2 Higher load-carrying capacity.
- 3 Excellent Self-cleaning performance.
- 4 Aggressive tread pattern and sidewall design.

CROSSWIND M/T / MT



CROSS-COUNTRY

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	1bs	kPa	psi
14	205R14C	8PR	109/107	R	6J	D 975 S 1030	D 2149 S 2271	450	65
15	30X9.50R15LT	6PR	104	Q	7 1/2J	900	1985	350	50
	31X10.50R15LT	6PR	109	Q	8 1/2J	1030	2270	350	50
	33X12.50R15LT	6PR	108	Q	10J	1000	2205	250	36
	LT215/75R15	6PR	100/97	Q	6J	D 730 S 800	D 1610 S 1765	350	50
	LT235/75R15	6PR	104/101	Q	6 1/2J	D 825 S 900	D 1820 S 1985	350	51
16	215/80R16	-	107	S	6J	975	2150	290	42
	205R16LT	8PR	110/108	Q	6J	D 1000 S 1060	D 2205 S 2337	450	65
	LT225/75R16	8PR	110/107	Q	6J	D 975 S 1060	D 2150 S 2335	450	65
	LT235/70R16	8PR	110/107	Q	7J	D 975 S 1060	D 2149 S 2337	450	65
	LT235/85R16	10PR	120/116	Q	6 1/2J	D 1260 S 1380	D 2778 S 3042	550	80
	LT245/75R16	10PR	120/116	Q	7J	D 1260 S 1380	D 2778 S 3042	550	80
	LT255/70R16	8PR	115/112	Q	7 1/2J	D 1120 S 1215	D 2470 S 2680	450	65
	LT265/70R16	6PR	110/107	Q	8J	D 975 S 1060	D 2150 S 2335	350	51
	LT265/75R16	8PR	119/116	Q	7 1/2J	D 1250 S 1360	D 2755 S 3000	450	65
	LT265/75R16	10PR	123/120	Q	7 1/2J	D 1400 S 1550	D 3085 S 3415	550	80
	LT285/75R16	6PR	116/113	Q	8J	D 1150 S 1250	D 2535 S 2755	350	50
	LT285/75R16	10PR	126/123	Q	8J	D 1550 S 1700	D 3415 S 3750	550	80
	LT305/70R16	8PR	118/115	Q	9J	D 1215 S 1320	D 2680 S 2910	350	51
	LT305/70R16	10PR	124/121	Q	9J	D 1450 S 1600	D 3195 S 3525	450	65
	LT315/75R16	8PR	121/118	Q	8 1/2J	D 1320 S 1450	D 2910 S 3195	350	51
	LT315/75R16	10PR	127/124	Q	10J	D 1600 S 1750	D 3535 S 3860	450	65
17	LT235/80R17	10PR	120/117	Q	6 1/2J	D 1285 S 1400	D 2835 S 3085	550	80
	LT255/75R17	6PR	111/108	Q	7J	D 1000 S 1090	D 2205 S 2405	350	50
	LT265/65R17	10PR	120/117	Q	8J	D 1285 S 1400	D 2835 S 3085	550	80
	LT265/70R17	10PR	121/118	Q	8J	D 1320 S 1450	D 2910 S 3195	550	80
	LT285/70R17	8PR	121/118	Q	8 1/2J	D 1320 S 1450	D 2910 S 3195	450	65
	LT285/70R17	10PR	121/118	Q	8 1/2J	D 1320 S 1450	D 2910 S 3195	550	80
	LT305/70R17	8PR	119/116	Q	9J	D 1250 S 1360	D 2755 S 3000	350	50
	35X12.50R17LT	10PR	121	Q	10J	1450	3195	450	65

CROSSWIND RUGGED TRAXX / RT



CROSS-COUNTRY

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	1bs	kPa	psi
16	265/70R16	-	112	Q	8J	1120	2469	300	44
	265/75R16	-	116	Q	7 1/2J	1250	2756	300	44
	LT245/75R16	E	120/116	Q	7J	1380/1260	3042/2778	550	80
	LT285/75R16	E	126/123	Q	8J	1700/1550	3750/3415	550	80
	LT265/75R16	E	123/120	Q	7 1/2J	1550/1400	3415/3085	550	80
17	35X12.50R17LT	F	128	Q	10J	1800	3970	550	80
	265/70R17	-	115	Q	8J	1215	2679	300	44
	265/65R17	-	112	Q	8J	1120	2469	300	44
	LT245/75R17	E	121/118	Q	7J	1450/1320	3195/2910	550	80
	LT285/70R17	E	126/123	Q	8 1/2J	1700/1550	3750/3415	550	80
	LT265/70R17	E	123/120	Q	8J	1550/1400	3415/3085	550	80
18	35X12.50R18LT	F	128	Q	10J	1800	3970	550	80
	255/70R18	-	116	T	7 1/2J	1250	2756	340	50
	275/65R18	-	116	T	8J	1250	2756	340	50
	265/60R18	-	114	Q	8J	1180	2601	340	50
	265/70R18	-	116	S	8J	1250	2756	300	44
	LT275/70R18	E	125/122	Q	8J	1650/1500	3640/3305	550	80
	LT275/65R18	E	123/120	Q	8J	1550/1400	3415/3085	550	80
20	35X12.50R20LT	F	125	Q	10J	1650	3640	550	80
	275/55R20	-	117	Q	8 1/2J	1285	2833	340	50
	275/60R20	-	116	T	8J	1250	2756	340	50
	LT305/55R20	E	121/118	Q	9 1/2J	1450/1320	3195/2910	450	65
	LT275/65R20	E	126/123	Q	8J	1700/1550	3750/3415	550	80
	LT285/60R20	E	125/122	Q	8 1/2J	1650/1500	3640/3305	550	80
22	35X12.50R22LT	F	121	Q	10J	1450	3195	550	80
	37X13.50R22LT	F	128	Q	11J	1800	3970	550	80
	285/45R22	-	114	Q	9 1/2J	1180	2601	340	50
24	35X12.50R24LT	F	116	Q	10 1/2J	1250	2755	550	80

CROSSWIND M/T/MT									
CROSS-COUNTRY									
RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
18	LT265/60R18	10PR	119/116	Q	8J	D 1250 S 1360	D 2755 S 3000	550	80
	LT275/70R18	10PR	125/122	Q	8J	D 1500 S 1650	D 3305 S 3640	550	80
	LT285/65R18	10PR	125/122	Q	8 1/2J	D 1500 S 1650	D 3305 S 3640	550	80
	33X12.50R18LT	10PR	118	Q	10J	1320	2910	450	65
	33X12.50R18LT	12PR	122	Q	10J	1500	3305	550	80
	35X12.50R18LT	10PR	123	Q	10J	1550	3415	450	65
	35X12.50R18LT	12PR	128	Q	10J	1800	3970	550	80
20	LT275/65R20	10PR	126/123	P	8J	D 1550 S 1700	D 3415 S 3750	550	80
	LT285/55R20	10PR	122/119	Q	9J	D 1360 S 1500	D 3000 S 3305	550	80
	LT285/65R20	10PR	127/124	Q	8 1/2J	D 1600 S 1750	D 3525 S 3860	550	80
	LT305/55R20	10PR	121/118	Q	9 1/2J	D 1320 S 1450	D 2910 S 3195	450	65
	33X12.50R20LT	10PR	114	Q	10J	1180	2600	450	65
	33X12.50R20LT	12PR	119	Q	10J	1360	3000	550	80
	35X12.50R20LT	10PR	121	Q	10J	1450	3195	450	65
	35X12.50R20LT	12PR	125	Q	10J	1650	3640	550	80
	37X13.50R20LT	10PR	127	Q	11J	1750	3860	450	65
	37X13.50R20LT	12PR	128	Q	10J	1800	3970	550	80
22	38X15.50R20LT	8PR	125	Q	12J	1650	3640	350	50
	33X12.50R22LT	10PR	109	Q	10J	1030	2270	450	65
	33X12.50R22LT	12PR	114	Q	10J	1180	2600	550	80
	35X12.50R22LT	10PR	117	Q	10J	1285	2835	450	65
	35X12.50R22LT	12PR	121	Q	10J	1450	3195	550	80
	37X13.50R22LT	10PR	123	Q	11J	1550	3415	450	65
	37X13.50R22LT	12PR	128	Q	11J	1800	3970	550	80
24	35X12.50R24LT	10PR	117	Q	10 1/2J	1285	2835	450	65
	37X13.50R24LT	10PR	120	Q	11J	1400	3085	450	65
26	37X13.50R26LT	10PR	117	Q	11J	1285	2835	450	65

RADIAL666



Commercial tire with Excellent wear and wet performance

- PERFORMANCE
- 1

Excellent traction.
- 2

Excellent wet braking.
- 3

High wear resistance.

RADIAL666									
VAN									
RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
12	155R12C	6PR	83/81	N	4.50B	D 462 S 487	D 1019 S 1074	350	51
	155R12LT	8PR	88/86	N	4.50B	D 530 S 560	D 1170 S 1235	450	65
13	165R13LT	8PR	94/93	S	4.50B	D 650 S 670	D 1435 S 1475	450	65
	175R13C	8PR	97/95	Q	5.00B	D 690 S 730	D 1521 S 1609	450	65
	175R13LT	8PR	97/95	Q	5.00B	D 690 S 730	D 1521 S 1609	450	65
14	165/70R14C	6PR	89/87	R	5J	D 545 S 580	D 1201 S 1279	375	54
	185R14C	8PR	102/100	R/Q	5 1/2J	D 800 S 850	D 1764 S 1874	450	65
	185R14LT	6PR	97/95	R	5 1/2J	D 690 S 730	D 1521 S 1609	350	51
	185R14LT	8PR	102/100	R	5 1/2J	D 800 S 850	D 1764 S 1874	450	65
	195R14C	8PR	106/104	P	5 1/2J	D 900 S 950	D 1984 S 2094	450	65
	195R14C WR	8PR	106/104	P	5 1/2J	D 900 S 950	D 1984 S 2094	450	65
	195/75R14C	8PR	106/104	R	5 1/2J	D 900 S 950	D 1984 S 2094	475	69
	205/75R14C	8PR	109/107	R	5 1/2J	D 975 S 1030	D 2149 S 2271	475	69
	215R14C	8PR	110/108	R	6J	D 1000 S 1060	D 2205 S 2337	450	65
	215/75R14C	8PR	112/110	R	6J	D 1060 S 1120	D 2337 S 2469	475	69
15	195R15C	8PR	106/104	R	5 1/2J	D 900 S 950	D 1984 S 2094	450	65
	195R15C WR	8PR	106/104	R	5 1/2J	D 900 S 950	D 1985 S 2095	450	65
	195/70R15C	8PR	104/102	R	6J	D 850 S 900	D 1875 S 1985	450	65
	195/70R15LT	10PR	104/102	R	6J	D 850 S 900	D 1874 S 1984	550	80
	195/70R15LT	10PR	104/101	R	6J	D 825 S 900	D 1820 S 1985	550	80
	205/70R15C	8PR	106/104	S	6J	D 900 S 950	D 1984 S 2094	450	65
	205/70R15C WR	8PR	106/104	S	6J	D 950 S 900	D 2095 S 1985	450	65
	215/70R15C	8PR	109/107	R	6 1/2J	D 975 S 1030	D 2149 S 2271	450	65
	215/70R15C WR	8PR	109/107	R	6 1/2J	D 975 S 1030	D 2150 S 2270	450	65
	225/70R15C	8PR	112/110	R	6 1/2J	D 1060 S 1120	D 2337 S 2469	450	65
16	255/70R15C	6PR	112/110	S	7 1/2J	D 1060 S 1120	D 2337 S 2469	375	54
	175/75R16C	8PR	101/99	R	5J	D 775 S 825	D 1709 S 1819	475	69
	185/75R16C	8PR	104/102	R	5J	D 850 S 900	D 1874 S 1984	475	69
	195/65R16C	8PR	104/102	R	6J	D 850 S 900	D 1874 S 1984	475	69
	195/75R16C	8PR	107/105	R	5 1/2J	D 925 S 975	D 2039 S 2149	475	69
	205/65R16C	8PR	107/105	R	6J	D 925 S 975	D 2039 S 2149	475	69
	205/75R16C	8PR	110/108	R	5 1/2J	D 1000 S 1060	D 2205 S 2337	475	69
	215/65R16C	8PR	109/107	R	6 1/2J	D 975 S 1030	D 2149 S 2271	475	69
	215/70R16C	6PR	108/106	S	6 1/2J	D 950 S 1000	D 2094 S 2205	375	54
	215/75R16C	8PR	113/111	R	6J	D 1090 S 1150	D 2403 S 2535	475	69
	225/65R16C	8PR	112/110	R	6 1/2J	D 1060 S 1120	D 2337 S 2469	475	69
	225/75R16C	10PR	121/120	R	6J	D 1400 S 1450	D 3086 S 3197	575	83
	235/65R16C	8PR	115/113	R	7J	D 1150 S 1215	D 2535 S 2679	475	69

MAX TRAC R771

High mileage and load resistance tire

PERFORMANCE

- 1 High wear resistance.
- 2 High endurance performance.
- 3 All Season Tire for light trucks.

MAX TRAC R771



RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
13	145R13LT	8PR	88/86	P	4J	D 530 S 560	D 1170 S 1235	450	65

LMC5



Increased mileage with high wear resistance

PERFORMANCE

- 1 Freight vehicles.
- 2 High mileage.

LMC5



RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
14	185R14C	8PR	102/100	Q/N	5 1/2J	D 800 S 850	D 1764 S 1874	450	65
	195R14LT	8PR	106/104	P	5 1/2J	D 900 S 950	D 1984 S 2094	450	65

LMC7



All terrain tire

PERFORMANCE

- 1 Excellent wear resistance performance.

LMC7



RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
15	195R15C	8PR	106/104	Q	5 1/2J	D 900 S 950	D 1984 S 2094	450	65
	195R15C(WHITE)	8PR	106/104	Q	5 1/2J	D 900 S 950	D 1984 S 2094	450	65

R655

Excellent steering performance

PERFORMANCE

- 1 Good drainage performance and stability.
- 2 Excellent steering performance.

R655



RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
12	5.00R12LT	8PR	83/81	N	3.50B	D 462 S 487	D 1019 S 1074	450	65

LMC4



Increased mileage with high wear resistance

PERFORMANCE

- 1 Excellent wear resistance performance.

LMC4



RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
15	6.50R15LT	8PR	101/97	N	5.50F	D 730 S 825	D 1610 S 1819	460	67
	7.00R15LT	10PR	110/105	L	5.50F	D 925 S 1060	D 2039 S 2337	560	81
16	6.50R16C	10PR	107/103	N	5.50F	D 875 S 975	D 1929 S 2149	560	81
	6.50R16C	10PR	108/107	L	5.50F	D 975 S 1000	D 2149 S 2205	500	72
	6.50R16C	12PR	110/105	M	5.50F	D 925 S 1060	D 2039 S 2337	670	97
	7.50R16LT	10PR	116/112	L	6.00G	D 1120 S 1250	D 2469 S 2756	560	81
	7.50R16LT	14PR	122/118	L	6.00G	D 1320 S 1500	D 2910 S 3307	770	111
	7.50R16LT	12PR	120/116	M	5.50F	D 1250 S 1400	D 2756 S 3086	670	97

RADIAL R781



Trailer Tire

PERFORMANCE

- 1 Low fuel consumption.

RADIAL R781



RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
10	195/55R10C	-	98/96	N	6J	D 710 S 750	D 1565 S 1655	625	91
	155/70R12	-	73	S	4.50B	365	805	300	44
	175/70R12	-	80	H	5.00B	450	992	300	44
12	155/70R12C	-	100/98	N	4 1/2J	D 750 S 800	D 1653 S 1764	650	94
	155/70R12C	-	104/102	N	4 1/2J	D 850 S 900	D 1875 S 1985	625	90
	185/60R12C	-	104/101	N	5 1/2J	D 825 S 900	D 1820 S 1985	650	94
	195/60R12C	-	104/102	N	6J	D 850 S 900	D 1875 S 1985	650	94
	135/80R13 XL	-	74	N	3.50B	375	827	340	50
13	145/70R13	-	74	N	4.50J	345	761	300	44
	145/80R13 XL	-	79	N	4.00B	437	963	340	50
	155/70R13	-	75	N	4.50B	387	853	300	44
	155/80R13 XL	-	84	N	4.50B	500	1102	340	50
	165/60R13	-	73	T	5.00B	365	805	300	44
	165/65R13	-	77	N	5.00B	412	908	300	44
	165/70R13	-	79	N	5.00B	437	963	300	44
	175/70R13	-	82	N/H	5.00B	475	1047	300	44
	175/70R13 XL	-	86	N	5.00B	530	1168	340	50
	185/70R13	-	86	N	5 1/2J	530	1168	300	44
	165R13C	8PR	94/92	N	4 1/2J	D 630 S 670	D 1390 S 1475	450	65
	165R13C	8PR	96/94	N	4 1/2J	D 670 S 710	D 1475 S 1565	450	65
	185/70R13C	-	106/104	N	5 1/2J	D 900 S 950	D 1984 S 2094	600	87
	195/50R13C	-	104/101	N	6J	D 825 S 900	D 1820 S 1985	650	94
14	165/55R14	-	72	H	5J	355	783	300	44
	175/65R14	-	82	T/H	5J	475	1047	300	44
	185/60R14	-	82	H	5 1/2J	475	1047	300	44
	185/65R14	-	86	T	5 1/2J	530	1168	300	44
	185/70R14	-	88	T	5 1/2J	560	1235	300	44
	195/70R14	-	91	T	6J	615	1356	300	44
	195/70R14 XL	-	96	N	6J	710	1565	340	50
	165R14LT	6PR	91/90	S	4 1/2J	D 600 S 615	D 1323 S 1356	350	51
	165R14LT	8PR	96/95	T	4 1/2J	D 690 S 710	D 1521 S 1565	450	65
	185R14C	8PR	102/100	N	5 1/2J	D 800 S 850	D 1764 S 1874	450	65
	185R14C	-	104/102	N	5 1/2J	D 850 S 900	D 1875 S 1985	500	73
15	195R14C	8PR	106/104	N	5J	D 900 S 950	D 1984 S 2094	450	65
	185/65R15	-	88	T	5 1/2J	560	1235	300	44
	195/50R15	-	82	H	6J	475	1047	300	44
	195/55R15	-	85	H	6J	515	1135	300	44
	195/60R15	-	88	H	6J	560	1235	300	44
	195/65R15	-	91	H	6J	615	1356	300	44
	205/60R15	-	91	H	6J	615	1356	300	44
	205/65R15	-	94	H	6J	670	1477	300	44
	205/70R15	-	96	T	6J	710	1565	300	44
16	205/75R15	-	97	S	5 1/2J	730	1609	300	44
	205/55R16	-	91	H	6 1/2J	615	1356	300	44
	205/60R16	-	92	H	6J	630	1389	300	44
	205/65R16	-	95	H	6J	690	1521	300	44

CROSSWIND R781



TRAILER TIRE

PERFORMANCE

- 1 Low fuel consumption.
- 2 Specially designed for trailer.

CROSSWIND R781



RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
13	ST175/80R13	6PR	91/87	M	5J	D 545 S 615	D 1200 S 1360	350	50
14	ST205/75R14	6PR	100/96	M	5 1/2J	D 710 S 800	D 1570 S 1760	350	50
	ST205/75R14	8PR	105/101	M	5 1/2J	D 825 S 925	D 1820 S 2040	450	65
	ST215/75R14	6PR	102/98	M	6J	D 750 S 850	D 1650 S 1870	350	50
15	ST205/75R15	8PR	107/102	M	5 1/2J	D 850 S 975	D 1870 S 2150	450	65
	ST205/75R15	6PR	101/97	M	5 1/2J	D 730 S 825	D 1610 S 1820	350	50
	ST225/75R15	8PR	113/108	M	6J	D 1000 S 1150	D 2200 S 2540	450	65
	ST225/75R15	10PR	117/112	M	6J	D 1120 S 1285	D 2470 S 2830	550	80
16	ST235/80R16	10PR	123/119	M	6 1/2J	D 1360 S 1550	D 3000 S 3420	550	80
	ST235/85R16	10PR	125/121	M	6 1/2J	D 1450 S 1650	D 3200 S 3640	550	80



GRIP MASTER 4S



KEY PRODUCTS TIRE

High Performance All Weather tyre

PERFORMANCE

- 1 Excellent wet performance which improved 20% than that of the previous generation.
- 2 Excellent grip performance ,effectively improve the safety of driving under the wet surface.
- 3 Tread compound with low temperature resistant for winter and summer conditions.

GRIP MASTER 4S | HP/UHP



RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
13	155/80R13	79	T	4.50B	437	963	300	44
	155/70R13	75	T	4.50B	387	853	300	44
	165/70R13	79	T	5.00B	437	963	300	44
14	155/65R14	75	T	4 1/2J	387	853	300	44
	165/60R14	75	H	5J	387	853	300	44
	165/65R14	79	T	5J	437	963	300	44
	165/70R14	81	T	5J	462	1019	300	44
	175/65R14	82	T	5J	475	1047	300	44
	175/70R14 XL	88	T	5J	560	1235	340	50
	185/60R14	82	H	5 1/2J	475	1047	300	44
	185/65R14	86	H	5 1/2J	530	1168	300	44
15	165/65R15	81	T	5J	462	1019	300	44
	175/65R15 XL	88	T	5J	560	1235	340	50
	185/55R15	82	H	6J	475	1047	300	44
	185/60R15 XL	88	H	5 1/2J	560	1235	340	50
	185/65R15	88	H	5 1/2J	560	1235	300	44
	195/50R15 XL	86	H	6J	530	1168	340	50
	195/55R15	85	H	6J	515	1135	300	44
	195/60R15	88	H	6J	560	1235	300	44
	195/65R15	91	H	6J	615	1356	300	44
	205/65R15	94	H	6J	670	1477	300	44

GRIP MASTER 4S | HP/UHP



RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	lbs
16	195/45R16 XL	84	V	6 1/2J	500	1102	340	50
	195/55R16	87	V	6J	545	1201	300	44
	205/55R16	91	V	6 1/2J	615	1356	300	44
	205/60R16 XL	96	V	6J	710	1565	340	50
	215/55R16 XL	97	V	7J	730	1609	340	50
	215/60R16 XL	99	V	6 1/2J	775	1709	340	50
	215/65R16 XL	102	V	6 1/2J	850	1874	340	50
	215/70R16	100	H	6 1/2J	800	1764	300	44
	245/70R16	107	H	7J	975	2149	300	44
17	205/45R17 XL	88	W	7J	560	1235	340	50
	205/50R17 XL	93	V	6 1/2J	650	1433	340	50
	205/55R17 XL	95	W	6 1/2J	690	1521	340	50
	215/40R17 XL	87	V	7 1/2J	545	1201	340	50
	215/45R17 XL	91	W	7J	615	1356	340	50
	215/50R17 XL	95	W	7J	690	1521	340	50
	215/55R17 XL	98	V	7J	750	1653	340	50
	215/60R17 XL	100	V	6 1/2J	800	1764	340	50
	225/45R17 XL	94	W	7 1/2J	670	1477	340	50
	225/50R17 XL	98	V	7J	750	1653	340	50
	225/55R17 XL	101	V	7J	825	1819	340	50
	225/60R17 XL	103	V	6 1/2J	875	1929	340	50
	225/65R17 XL	106	V	6 1/2J	950	2094	340	50
	235/45R17 XL	97	W	8J	730	1609	340	50
	235/55R17 XL	103	W	7 1/2J	875	1929	340	50
	235/65R17 XL	108	V	7J	1000	2205	340	50
	245/45R17 XL	99	W	8J	775	1709	340	50
18	215/40R18 XL	89	W	7 1/2J	580	1279	340	50
	215/50R18 XL	96	W	7J	710	1565	340	50
	215/55R18 XL	99	W	7J	775	1709	340	50
	225/40R18 XL	92	W	8J	630	1389	340	50
	225/45R18 XL	95	W	7 1/2J	690	1521	340	50
	235/45R18 XL	98	W	8J	750	1653	340	50
	235/55R18	100	W	7 1/2J	800	1764	300	44
	245/40R18 XL	97	W	8 1/2J	730	1609	340	50
19	225/35R19 XL	88	W	8J	560	1235	340	50
	225/45R19 XL	96	W	7 1/2J	710	1565	340	50
	235/35R19 XL	91	W	8 1/2J	615	1356	340	50
	245/45R19 XL	102	W	8J	850	1874	340	50

GREEN-MAX ALL SEASON



All Weather Tires

PERFORMANCE

- 1 Excellent handling.
- 2 Lower rolling resistance.
- 3 All season tire which is applicable to different weather and road conditions.

GREEN-MAX ALL SEASON / ALL SEASON



RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
13	145/70R13	71	T	4.50B	345	761	300	44
	145/80R13	75	T	4.00B	387	853	300	44
	155/65R13	73	T	4.50B	365	805	300	44
	155/70R13	75	T	4.50B	387	853	300	44
	155/80R13	79	T	4.50B	437	963	300	44
	165/70R13	79	T	5.00B	437	963	300	44
	175/65R13	80	T	5.00B	450	992	300	44
	175/70R13	82	T	5.00B	475	1047	300	44
14	155/65R14	75	T	4 1/2J	387	853	300	44
	165/60R14	75	H	5J	387	853	300	44
	165/65R14	79	T	5J	437	963	300	44
	165/70R14	81	T	5J	462	1019	300	44
	175/65R14	82	T	5J	475	1047	300	44
	175/70R14 XL	88	T	5J	560	1235	340	50
	175/80R14	88	T	5J	560	1235	300	44
	185/55R14	80	H	6J	450	992	300	44
	185/60R14	82	H	5 1/2J	475	1047	300	44
	185/65R14	86	H	5 1/2J	530	1168	300	44
	185/70R14	88	H	5 1/2J	560	1235	300	44
	195/70R14	91	T	6J	615	1356	300	44
15	165/60R15	77	H	5J	412	908	300	44
	165/65R15	81	T	5J	462	1019	300	44
	175/65R15 XL	88	T	5J	560	1235	340	50
	185/55R15	82	H	6J	475	1047	300	44
	185/60R15 XL	88	H	5 1/2J	560	1235	340	50
	185/65R15	88	H	5 1/2J	560	1235	300	44
	195/50R15 XL	86	H	6J	530	1168	340	50
	195/55R15	85	H	6J	515	1135	300	44
	195/60R15	88	H	6J	560	1235	300	44
	195/65R15	91	H	6J	615	1356	300	44
	205/65R15	94	H	6J	670	1477	300	44
	215/65R15	96	H	6 1/2J	710	1565	300	44
16	195/45R16 XL	84	H	6 1/2J	500	1102	340	50
	195/50R16 XL	88	V	6J	560	1235	340	50
	195/55R16	87	H	6J	545	1201	300	44
	205/45R16	83	V	7J	487	1074	300	44
	205/55R16	91	V	6 1/2J	615	1356	300	44

GREEN-MAX ALL SEASON / ALL SEASON



RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
16	205/60R16 XL	96	H	6J	710	1565	340	50
	215/45R16 XL	90	V	7J	600	1323	340	50
	215/55R16 XL	97	V	7J	730	1609	340	50
	215/60R16 XL	99	H	6 1/2J	775	1709	340	50
	215/65R16 XL	102	V	6 1/2J	850	1874	340	50
	215/70R16	100	H	6 1/2J	800	1764	300	44
	225/55R16 XL	99	V	7J	775	1709	340	50
17	225/60R16 XL	102	V	6 1/2J	850	1874	340	50
	205/45R17 XL	88	V	7J	560	1235	340	50
	205/50R17 XL	93	V	6 1/2J	650	1433	340	50
	205/55R17 XL	95	V	6 1/2J	690	1521	340	50
	215/40R17 XL	87	V	7 1/2J	545	1201	340	50
	215/45R17 XL	91	V	7J	615	1356	340	50
	215/50R17 XL	95	V	7J	690	1521	340	50
	215/55R17 XL	98	V	7J	750	1653	340	50
	215/60R17 XL	100	V	6 1/2J	800	1764	340	50
	225/45R17 XL	94	V	7 1/2J	670	1477	340	50
	225/50R17 XL	98	V	7J	750	1653	340	50
	225/55R17 XL	101	V	7J	825	1819	340	50
	225/60R17 XL	103	V	6 1/2J	875	1929	340	50
	225/65R17	102	H	6 1/2J	850	1874	300	44
	235/45R17 XL	97	V	8J	730	1609	340	50
18	235/55R17 XL	103	V	7 1/2J	875	1929	340	50
	235/65R17 XL	108	V	7J	1000	2205	340	50
	245/45R17 XL	99	V	8J	775	1709	340	50
	215/55R18 XL	99	V	7J	775	1709	340	50
19	225/40R18 XL	92	V	8J	630	1389	340	50
	225/45R18 XL	95	V	7 1/2J	690	1521	340	50
	245/40R18 XL	97	V	8 1/2J	730	1609	340	50
19	225/35R19 XL	88	V	8J	560	1235	340	50
	235/35R19 XL	91	V	8 1/2J	615	1356	340	50



CROSSWIND A/T¹⁸⁸



Low noise all-weather All-Terrain tire

PERFORMANCE

- 1 All Weather Capability.
- 2 Comfortable Quiet Ride.
- 3 Excellent Snow and Wet Braking.
- 4 Off-Road Traction.

CROSSWIND A/T¹⁸⁸ / AT



RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
15	205/70R15	-	96	T	6J	710	1565	300	44
	235/75R15 XL	-	109	T	6 1/2J	1030	2271	340	50
	255/70R15	-	108	T	7 1/2J	1000	2205	300	44
	265/70R15	-	112	T	8J	1120	2469	300	44
	265/70R15	-	112	T	8J	1120	2469	300	44
	31X10.50R15LT	6PR	109	R	8 1/2J	1030	2270	350	50
	31X10.50R15LT	6PR	109	R	8 1/2J	1030	2270	350	50
	LT215/75R15	6PR	100/97	S	6J	D 730 S 800	D 1610 S 1765	350	50
	LT225/75R15	6PR	102/99	S	6J	D 775 S 850	D 1710 S 1875	350	50
	LT235/75R15	6PR	104/101	S	6 1/2J	D 825 S 900	D 1820 S 1985	350	50
16	235/70R16	-	106	T	7J	950	2094	300	44
	245/70R16 XL	-	111	T	7J	1090	2403	340	50
	205R16LT	8PR	110/108	Q	6J	D 1000 S 1060	D 2205 S 2335	450	65
	LT225/75R16	10PR	115/112	Q	6J	D 1120 S 1215	D 2470 S 2680	550	80
17	245/65R17 XL	-	111	T	7J	1090	2403	340	50
	265/65R17	-	112	T	8J	1120	2469	300	44
	265/65R17	-	112	T	8J	1120	2469	300	44

GREEN-MAX
VAN 4S



For All Weather Tires commercial

PERFORMANCE

- 1 Various design of the 3D sipe, Optimization tread pattern stiffness distribution, The tire have good wet&ice road grip performance.
- 2 Application of spring hole, product with Excellent appearance.

GREEN-MAX VAN 4S



RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
14	165/70R14C	6PR	89/87	R	5J	D 545 S 580	D 1201 S 1279	375	54
	175/65R14C	6PR	90/88	T	5J	D 560 S 600	D 1235 S 1323	375	54
	175/70R14C	6PR	95/93	T	5J	D 650 S 690	D 1433 S 1521	375	54
15	195/70R15C	8PR	104/102	R	6J	D 850 S 900	D 1874 S 1984	450	65
	205/70R15C	8PR	106/104	R	6J	D 900S 950	D 1984 S 2094	450	65
	215/70R15C	8PR	109/107	R	6 1/2J	D 975S 1030	D 2149 S 2271	450	65
	225/70R15C	8PR	112/110	S	6 1/2J	D 1060S 1120	D 2337 S 2469	450	65
16	185/75R16LT	8PR	104/102	R	5J	D 850 S 900	D 1874 S 1984	475	69
	195/60R16C	6PR	99/97	R	6J	D 730 S 775	D 1609 S 1709	375	54
	195/65R16C	8PR	104/102	R	6J	D 850 S 900	D 1874 S 1984	475	69
	195/75R16C	8PR	107/105	R	5 1/2J	D 925 S 975	D 2039 S 2149	475	69
	205/65R16C	8PR	107/105	T	6J	D 925S 975	D 2039 S 2149	475	69
	205/75R16C	8PR	110/108	T	5 1/2J	D 1000 S 1060	D 2205 S 2337	475	69
	215/60R16LT	6PR	103/101	T	6 1/2J	D 825 S 875	D 1819 S 1929	375	54
	215/65R16C	8PR	109/107	T	6 1/2J	D 975S 1030	D 2149 S 2271	475	69
	215/75R16C	8PR	113/111	R	6J	D 1090S 1150	D 2403 S 2535	475	69
	225/65R16C	8PR	112/110	S	6 1/2J	D 1060S 1120	D 2337 S 2469	475	69
	225/75R16C	10PR	118/116	R	6J	D 1250S 1320	D 2756 S 2910	525	76
	235/65R16C	8PR	115/113	R	7J	D 1150S 1215	D 2535 S 2679	475	69
17	215/60R17C	8PR	109/107	T	6 1/2J	D 975S 1030	D 2150 S 2271	475	69

WINTER



**GRIP MASTER
WINTER**

P 69

**GREEN-MAX
WINTER HP**

P 71

**GREEN-MAX
WINTER UHP**

P 71

**GREEN-MAX
WINTER VAN**

P 72



KEY PRODUCTS TIRE

**NORD
MASTER**

P 73

**GREEN-MAX
WINTER ICE 1-15**

P 75

**GREEN-MAX
WINTER ICE 1-15 SUV**

P 75



**GREEN-MAX
WINTER GRIP 2**

P 77

**GREEN-MAX
WINTER GRIP**

P 79

**GREEN-MAX
WINTER GRIP^{SUV}**

P 79

**GREEN-MAX
WINTER GRIP VAN²**

P 80

GRIP MASTER WINTER



KEY PRODUCTS TIRE

Snow tires with superior wet performance and precise handling

PERFORMANCE

- 1 The deep V-shaped groove design facilitates snow drainage and provides superior snow handling.
- 2 Wet road conditions offer shorter braking distances and more precise handling.

GRIP MASTER WINTER / HP/UHP



RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
14	165/70R14XL	85	T	5J	515	1135	340	50
	175/65R14XL	86	H	5J	475/530	1047/1168	300/340	44/50
	175/65R14	82	T	5J	475/530	1047/1168	300/340	44/50
15	175/65R15XL	88	H	5J	560	1235	340	50
	185/55R15XL	86	V	6J	530	1168	340	50
	185/60R15XL	88	V	5 1/2J	560	1235	340	50
	185/65R15XL	92	V	5 1/2J	560/630	1235/1389	300/340	44/50
	185/65R15	88	T	5 1/2J	560/630	1235/1389	300/340	44/50
	195/50R15XL	86	V	6J	530	1168	340	50
	195/60R15XL	92	H	6J	630	1389	340	50
	195/65R15XL	95	V	6J	615/690	1356/1521	300/340	44/50
	195/65R15	91	T	6J	615/690	1356/1521	300/340	44/50
16	195/45R16XL	84	H	6 1/2J	500	1102	340	50
	195/50R16XL	88	H	6J	560	1235	340	50
	195/55R16	87	H	6J	545	1201	350	51
	205/45R16XL	87	H	7J	545	1201	340	50
	205/55R16XL	94	V	6 1/2J	615/670	1356/1477	350/340	51/50
	205/55R16	91	H	6 1/2J	615/670	1356/1477	350/340	51/50
	205/60R16XL	96	V	6J	630/710	1389/1565	300/340	44/50
	205/60R16	92	H	6J	630/710	1389/1565	300/340	44/50
	205/65R16	95	H	6J	690	1521	350	51

GRIP MASTER WINTER / HP/UHP



RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	1bs
16	215/45R16XL	90	V	7J	600	1323	340	50
	215/55R16XL	97	V	7J	730	1609	340	50
	215/60R16XL	99	V	6 1/2J	775	1709	340	50
	215/65R16XL	102	H	6 1/2J	850	1874	340	50
	215/70R16XL	104	H	6 1/2J	900	1984	340	50
	225/75R16XL	108	H	6J	1000	2205	340	50
17	205/45R17XL	88	V	7J	560	1235	340	50
	205/50R17XL	93	V	6 1/2J	650	1433	340	50
	205/55R17XL	95	V	6 1/2J	690	1521	340	50
	205/60R17	93	H	6J	650	1433	350	51
	215/45R17XL	91	V	7J	615	1356	340	50
	215/50R17XL	95	V	7J	690	1521	340	50
	215/55R17	98	V	7J	750	1653	340	50
	215/60R17	96	H	6 1/2J	710	1565	350	51
	215/65R17XL	103	V	6 1/2J	875	1929	340	50
	225/45R17XL	94	W	7 1/2J	670	1477	340	50
	225/50R17XL	98	V	7J	750	1653	340	50
	225/55R17XL	101	V	7J	825	1819	340	50
	225/60R17XL	103	V	6 1/2J	875	1929	340	50
	225/65R17XL	106	V	6 1/2J	950	2094	340	50
	235/45R17XL	97	H	8J	730	1609	340	50
	235/55R17XL	103	V	7 1/2J	875	1929	340	50
	235/65R17XL	108	H	7J	1000	2205	340	50
	245/45R17XL	99	V	8J	775	1709	340	50
	245/65R17XL	111	V	7J	1090	2403	340	50
	265/65R17XL	116	H	8J	1250	2756	340	50
18	195/60R18XL	96	H	6J	710	1565	340	50
	215/55R18XL	99	V	7J	775	1709	340	50
	225/40R18XL	92	W	8J	630	1389	340	50
	225/45R18XL	95	W	7 1/2J	690	1521	340	50
	225/50R18XL	99	V	7J	775	1709	340	50
	225/55R18XL	102	V	7J	850	1874	340	50
	235/45R18XL	98	V	8J	750	1653	340	50
	235/55R18XL	104	V	7 1/2J	900	1984	340	50
	235/60R18XL	107	H	7J	975	2149	340	50
	245/40R18XL	97	V	8 1/2J	730	1609	340	50
19	245/45R18XL	100	W	8J	800	1764	340	50
	235/55R19XL	105	V	7 1/2J	925	2039	340	50
	245/40R19XL	98	V	8 1/2J	750	1653	340	50
	245/45R19XL	102	V	8J	850	1874	340	50
	255/35R19XL	96	V	9J	710	1565	340	50
	255/40R19XL	100	V	9J	800	1764	340	50
	255/45R19XL	104	H	8 1/2J	900	1984	340	50
	255/50R19XL	107	V	8J	975	2149	340	50
20	275/40R19XL	105	V	9 1/2J	925	2039	340	50
	245/45R20XL	103	H	8J	875	1929	340	50
	255/35R20XL	97	V	9J	730	1609	340	50
	275/40R20XL	106	V	9 1/2J	950	2094	340	50
	315/35R20XL	110	V	11J	1060	2337	340	50

GREEN-MAX WINTER HP



High performance snow tires with excellent braking performance

PERFORMANCE

- 1 Excellent snow braking performance.
- 2 Comfortably snow driving.

GREEN-MAX WINTER HP / HP



RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
13	155/70R13	75	T	4.50B	387	853	300	44
	155/80R13	79	T	4.50B	437	963	300	44
	165/70R13	79	T	5.00B	437	963	300	44
	175/70R13	82	T	5.00B	475	1047	300	44
14	155/65R14	75	T	4 1/2J	387	853	300	44
	165/65R14	79	T	5J	437	963	300	44
	165/70R14	81	T	5J	462	1019	300	44
	175/65R14 XL	86	H	5J	530	1168	340	50
	175/70R14	84	T	5J	500	1102	300	44
	185/60R14	82	T	5 1/2J	475	1047	300	44
	185/65R14	86	T	5 1/2J	530	1168	300	44
15	175/65R15 XL	88	H	5J	560	1235	340	50
	185/60R15 XL	88	H	5 1/2J	560	1235	340	50
	185/65R15 XL	92	H	5 1/2J	630	1389	340	50
	195/60R15 XL	92	H	6J	630	1389	340	50
	195/65R15 XL	95	T	6J	690	1521	340	50
	205/65R15 XL	99	H	6J	775	1709	340	50
	205/70R15	96	T	6J	710	1565	300	44
16	205/55R16 XL	94	H	6 1/2J	670	1477	340	50
	205/60R16 XL	96	H	6J	710	1565	340	50
	215/55R16 XL	97	H	7J	730	1609	340	50
	215/60R16 XL	99	H	6 1/2J	775	1709	340	50
	215/65R16	98	H	6 1/2J	750	1653	300	44

GREEN-MAX WINTER UHP



Ultra High performance snow tires

PERFORMANCE

- 1 Excellent snow handling performance.

GREEN-MAX WINTER UHP / UHP



Size	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
15	185/55R15 XL	86	H	6J	530	1168	340	50
	195/50R15	82	H	6J	475	1047	300	44
	195/55R15	85	H	6J	515	1135	300	44

GREEN-MAX WINTER UHP / UHP



RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
16	195/55R16 XL	91	H	6J	615	1356	340	50
	225/55R16 XL	99	H	7J	775	1709	340	50
	225/60R16 XL	102	H	6 1/2J	850	1874	340	50
17	205/45R17 XL	88	V	7J	560	1235	340	50
	205/50R17 XL	93	V	6 1/2J	650	1433	340	50
	215/45R17 XL	91	V	7J	615	1356	340	50
	215/50R17 XL	95	V	7J	690	1521	340	50
	215/55R17	94	V	7J	670	1477	300	44
	215/60R17	96	H	6 1/2J	710	1565	300	44
	225/45R17 XL	94	V	7 1/2J	670	1477	340	50
	225/50R17 XL	98	V	7J	750	1653	340	50
	225/55R17 XL	101	V	7J	825	1819	340	50
	235/45R17 XL	97	H	8J	730	1565	340	50
	235/55R17 XL	103	V	7 1/2J	875	1929	340	50
18	225/40R18 XL	92	V	8J	630	1389	340	50
	225/45R18 XL	95	H	7 1/2J	690	1521	340	50
	235/45R18 XL	98	V	8J	750	1653	340	50
	235/55R18 XL	104	H	7 1/2J	900	1984	340	50
	235/60R18 XL	107	H	7J	975	2149	340	50
	245/40R18 XL	97	V	8 1/2J	730	1609	340	50
	245/45R18 XL	100	H	8J	800	1764	340	50
19	235/55R19 XL	105	V	7 1/2J	925	2039	340	50
	245/40R19 XL	98	V	8 1/2J	750	1653	340	50
	245/45R19 XL	102	V	8J	850	1874	340	50
	255/35R19 XL	96	V	9J	710	1565	340	50
	255/40R19 XL	100	V	9J	800	1764	340	50
	255/45R19 XL	104	H	8 1/2J	900	1984	340	50
	255/50R19 XL	107	V	8J	975	2149	340	50
	255/55R19 XL	111	H	8J	1090	2403	340	50
20	275/40R19 XL	105	V	9 1/2J	925	2039	340	50
	245/45R20 XL	103	H	8J	875	1929	340	50
	255/35R20 XL	97	V	9J	730	1609	340	50
	275/40R20 XL	106	V	9 1/2J	950	2094	340	50
	275/45R20 XL	110	H	9J	1060	2337	340	50
	315/35R20 XL	110	V	11J	1060	2337	340	50

GREEN-MAX WINTER VAN



Excellent snow traction performance

PERFORMANCE

- 1 Excellent snow traction performance.
- 2 Focus on driving safety of vehicles in winter.

GREEN-MAX WINTER VAN



Size	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
13	165R13C	6PR	89/88	Q	4.50B	D 560 S 580	D 1235 S 1279	350	51
14	175R14C	6PR	94/92	Q	5J	D 630 S 670	D 1389 S 1477	350	51
	185R14C	8PR	102/100	Q	6J	D 800 S 850	D 1764 S 1874	450	65
15	195R14C	8PR	106/104	P	5 1/2J	D 900 S 950	D 1984 S 2094	450	65
	195/70R15C	8PR	104/102	R	6J	D 850 S 900	D 1874 S 1984	450	65
	225/70R15LT	8PR	106/103	R	6 1/2J	D 875 S 950	D 1929 S 2094	450	65
	225/70R15C	8PR	112/110	R	6 1/2J	D 1060 S 1120	D 2337 S 2469	450	65
	175/75R16C	8PR	101/99	R	5J	D 775 S 825	D 1709 S 1819	475	69
16	185/75R16C	8PR	104/102	R	5J	D 850 S 900	D 1874 S 1984	475	69
	195/75R16C	8PR	107/105	R	5 1/2J	D 925 S 975	D 2039 S 2149	475	69
	205/75R16C	8PR	110/108	R	5 1/2J	D 1000 S 1060	D 2205 S 2337	475	69
	215/75R16C	8PR	113/111	R	6J	D 1090 S 1150	D 2403 S 2535	475	69
	225/65R16C	8PR	112/110	R	6 1/2J	D 1060 S 1120	D 2337 S 2469	475	69
	225/75R16C	10PR	121/120	R	6J	D 1400 S 1450	D 3086 S 3197	575	83
	235/65R16C	10PR	121/119	R	7J	D 1360 S 1450	D 3000 S 3195	575	83

NORD MASTER



KEY PRODUCTS TIRE

Excellent snow handling and ice braking&acceleration

PERFORMANCE

- 1 Directional grooves design for evacuate snow and mud.
- 2 Complex soft tread compound and 3D sipes technology to promote handling performance on ice and snow condition.

NORD MASTER | HP/UHP



RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
14	185/65R14 XL	90	T	5 1/2J	600	1323	340	50
15	185/65R15 XL	92	T	5 1/2J	630	1389	340	50
	195/65R15 XL	95	T	6J	690	1521	340	50
16	205/55R16 XL	94	T	6 1/2J	670	1477	340	50
	205/60R16 XL	96	T	6J	710	1565	340	50
	215/65R16 XL	102	T	6 1/2J	850	1874	340	50
17	205/40R17 XL	84	T	7 1/2J	500	1102	340	50
	205/45R17 XL	88	T	7J	560	1235	340	50
	205/55R17 XL	95	T	6 1/2J	690	1521	340	50
	215/40R17 XL	87	T	7 1/2J	545	1201	340	50
	215/50R17 XL	95	T	7J	690	1521	340	50
	215/55R17 XL	98	T	7J	750	1653	340	50
	225/45R17 XL	94	T	7 1/2J	670	1477	340	50
	225/50R17 XL	98	T	7J	750	1653	340	50
	225/55R17 XL	101	T	7J	825	1819	340	50

NORD MASTER | HP/UHP



RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	lbs
17	245/40R17 XL	95	T	8 1/2J	690	1521	340	50
18	215/40R18 XL	89	T	7 1/2J	580	1279	340	50
	225/40R18 XL	92	T	8J	630	1389	340	50
	225/45R18 XL	95	T	7 1/2J	690	1521	340	50
	235/45R18 XL	98	T	8J	750	1653	340	50
	255/35R18 XL	94	T	9J	670	1477	340	50
	265/35R18 XL	97	T	9 1/2J	730	1609	340	50
19	215/35R19 XL	85	T	7 1/2J	515	1135	340	50
	225/35R19 XL	88	T	8J	560	1235	340	50
	225/45R19 XL	96	T	7 1/2J	710	1565	340	50
	235/35R19 XL	91	T	8 1/2J	615	1356	340	50
	245/35R19 XL	93	T	8 1/2J	650	1433	340	50
	245/40R19 XL	98	T	8 1/2J	750	1653	340	50
	255/35R19 XL	96	T	9J	710	1565	340	50
20	235/35R20 XL	92	T	8 1/2J	630	1389	340	50
	255/35R20 XL	97	T	9J	730	1609	340	50
	275/35R20 XL	102	T	9 1/2J	850	1874	340	50
	275/50R20 XL	113	T	8 1/2J	1150	2535	340	50

GREEN-MAX WINTER ICE I-15



Outstanding handling performance

PERFORMANCE

- 1 Direction tread pattern design providing excellent handling performance.
- 2 Directional grooves to help evacuate snow and mud.

GREEN-MAX WINTER ICE I-15 / HP/UHP



RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
14	175/65R14 XL	86	T	5J	530	1168	340	50
	185/60R15 XL	88	T	5 1/2J	560	1235	340	50
15	185/65R15 XL	92	T	5 1/2J	630	1389	340	50
	195/65R15 XL	95	T	6J	690	1521	340	50
16	195/55R16 XL	91	T	6J	615	1356	340	50
	205/55R16 XL	94	T	6 1/2J	670	1477	340	50
	205/60R16 XL	96	T	6J	710	1565	340	50
	215/55R16 XL	97	T	7J	730	1609	340	50
	215/60R16 XL	99	T	6 1/2J	775	1709	340	50
	215/65R16 XL	102	T	6 1/2J	850	1874	340	50
	225/55R16 XL	99	T	7J	775	1709	340	50
17	205/50R17 XL	93	T	6 1/2J	650	1433	340	50
	225/45R17 XL	94	T	7 1/2J	670	1477	340	50
	225/50R17 XL	98	T	7J	750	1653	340	50
	225/55R17 XL	101	T	7J	825	1819	340	50
	235/45R17 XL	97	T	8J	730	1609	340	50

GREEN-MAX WINTER ICE I-15 SUV



Outstanding handling performance

PERFORMANCE

- 1 Directional grooves design for evacuate snow and mud.
- 2 Complex soft tread compound and 3D sipes technology to promote handling performance on ice and snow condition.

GREEN-MAX WINTER ICE I-15 SUV / HP/UHP



RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
15	205/70R15	96	T	6J	710	1565	300	44
	215/75R15	100	T	6J	800	1764	300	44
	235/75R15	105	T	6 1/2J	925	2039	300	44
16	215/65R16	98	T	6 1/2J	750	1653	300	44
	225/60R16	98	T	6 1/2J	750	1653	300	44
	235/70R16	106	T	7J	950	2094	300	44
	245/70R16	107	H	7J	975	2149	300	44
	275/70R16	114	T	8J	1180	2601	300	44

GREEN-MAX WINTER ICE I-15 SUV / HP/UHP



RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
17	215/60R17	96	T	6 1/2J	710	1565	300	44
	225/60R17	99	T	6 1/2J	775	1709	300	44
	225/65R17	102	T	6 1/2J	850	1874	300	44
	225/65R17 XL	106	T	6 1/2J	950	2094	340	50
	235/55R17	99	T	7 1/2J	775	1709	300	44
	235/65R17 XL	108	T	7J	1000	2205	340	50
	235/50R17	96	T	7 1/2J	710	1565	300	44
	245/45R17	95	T	8J	690	1521	300	44
	245/65R17	107	T	7J	975	2149	300	44
	255/45R17	98	T	8 1/2J	750	1653	300	44
	255/60R17	106	T	7 1/2J	950	2094	300	44
	265/65R17	112	T	8J	1120	2469	300	44
	275/65R17	115	T	8J	1215	2679	300	44
	225/50R18	95	T	7J	690	1521	300	44
18	225/55R18	98	T	7J	750	1653	300	44
	225/60R18	100	T	6 1/2J	800	1764	300	44
	235/50R18	97	T	7 1/2J	730	1609	300	44
	235/55R18	100	T	7 1/2J	800	1764	300	44
	235/60R18	103	T	7J	875	1929	300	44
	235/60R18 XL	107	T	7J	975	2149	340	50
	235/65R18	106	T	7J	950	2094	300	44
	245/40R18	93	T	8 1/2J	650	1433	300	44
	245/45R18	96	T	8J	710	1565	300	44
	245/50R18	100	T	7 1/2J	800	1764	300	44
	245/60R18	105	T	7J	925	2039	300	44
	255/40R18	95	T	9J	690	1521	300	44
	255/45R18	99	T	8 1/2J	775	1709	300	44
	255/55R18	105	T	8J	925	2039	300	44
	255/60R18 XL	112	H	7 1/2J	1120	2469	340	50
	265/60R18	110	T	8J	1060	2337	300	44
19	285/60R18	116	T	8 1/2J	1250	2756	300	44
	225/55R19	99	T	7J	775	1709	300	44
	235/50R19	99	T	7 1/2J	775	1709	300	44
	235/55R19 XL	105	H	7 1/2J	925	2039	340	50
	245/40R19 XL	98	S	8 1/2J	750	1653	340	50
	245/45R19	98	T	8J	750	1653	300	44
	245/55R19	103	T	7 1/2J	875	1929	300	44
	255/40R19	96	T	9J	710	1565	300	44
	255/45R19	100	T	8 1/2J	800	1764	300	44
	255/50R19	103	T	8J	875	1929	300	44
	255/55R19	107	T	8J	975	2149	300	44
	265/50R19	106	T	8 1/2J	950	2094	300	44
	275/35R19	96	T	9 1/2J	710	1565	300	44
	275/40R19	101	T	9 1/2J	825	1819	300	44
	275/55R19	111	T	8 1/2J	1090	2403	300	44
	285/45R19	107	T	9 1/2J	975	2149	300	44
20	245/40R20	95	T	8 1/2J	690	1521	300	44
	245/45R20	99	T	8J	775	1709	300	44
	245/50R20	102	T	7 1/2J	850	1874	300	44
	255/45R20	101	T	8 1/2J	825	1819	300	44
	255/50R20 XL	109	H	8J	1030	2271	340	50
	255/55R20 XL	110	T	8J	1060	2337	340	50
	265/45R20	104	T	9J	900	1984	300	44
	265/50R20	107	T	8 1/2J	975	2149	300	44
	275/40R20	102	T	9 1/2J	850	1874	300	44
	275/45R20 XL	110	T	9J	1060	2337	340	50
	275/55R20	113	T	8 1/2J	1150	2535	300	44
	285/35R20	100	T	10J	800	1764	300	44
	285/45R20	108	T	9 1/2J	1000	2205	300	44
	285/50R20	112	T	9J	1120	2469	300	44
	315/35R20	106	T	11J	950	2094	300	44
21	265/45R21	104	T	9J	900	1984	300	44
	275/45R21	107	T	9J	975	2149	300	44
	275/50R21 XL	113	T	8 1/2J	1150	2535	340	50
	285/45R21	109	T	9 1/2J	1030	2271	300	44
	295/40R21	107	T	10 1/2J	975	2149	300	44

GREEN-MAX WINTER GRIP 2



The Second generation studdable snow tire with outstanding braking performance on ice&snow condition

PERFORMANCE

- 1 Designed for ice and snow surface.
- 2 Directional tread pattern design for excellent snow traction performance.
- 3 Great grip and handling performance on ice and snow surface.

GREEN-MAX WINTER GRIP 2 / HP/UHP



RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
14	165/65R14	79	T	5J	437	963	300	44
	165/70R14	81	T	5J	462	1019	300	44
	175/65R14 XL	86	T	5J	530	1168	340	50
15	175/65R15	84	T	5J	500	1102	300	44
	185/60R15	84	T	5 1/2J	500	1102	300	44
	185/65R15	88	T	5 1/2J	560	1235	300	44
	195/55R15 XL	89	T	6J	580	1279	340	50
	195/65R15 XL	95	T	6J	690	1521	340	50
16	195/45R16 XL	84	T	6 1/2J	500	1102	340	50
	195/60R16 XL	93	T	6J	650	1433	340	50
	205/45R16 XL	87	T	7J	545	1201	340	50
	205/55R16 XL	94	T	6 1/2J	670	1477	340	50
	205/60R16 XL	96	T	6J	710	1565	340	50
	215/60R16	95	T	6 1/2J	690	1521	300	44
	215/65R16	98	T	6 1/2J	750	1653	300	44
	215/70R16	100	T	6 1/2J	800	1764	300	44
	225/55R16 XL	99	T	7J	775	1709	340	50
	245/70R16 XL	111	T	7J	1090	2403	340	50
17	265/70R16	112	T	8J	1120	2469	300	44
	205/45R17 XL	88	T	7J	560	1235	340	50
	205/50R17 XL	93	T	6 1/2J	650	1433	340	50
	205/55R17 XL	95	T	6 1/2J	690	1521	340	50
	215/40R17 XL	87	T	7 1/2J	545	1201	340	50
	215/55R17 XL	98	T	7J	750	1653	340	50
	215/60R17 XL	100	T	6 1/2J	800	1764	340	50
	215/65R17 XL	103	T	6 1/2J	875	1929	340	50
	225/45R17 XL	94	T	7 1/2J	670	1477	340	50
	225/50R17 XL	98	T	7J	750	1653	340	50

GREEN-MAX WINTER GRIP 2 / HP/UHP



RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
17	225/55R17	97	T	7J	730	1609	300	44
	225/60R17 XL	103	T	6 1/2J	875	1929	340	50
	235/55R17 XL	103	T	7 1/2J	875	1929	340	50
	225/65R17 XL	106	T	6 1/2J	950	2094	340	50
	235/65R17 XL	108	T	7J	1000	2205	340	50
18	215/40R18 XL	89	T	7 1/2J	580	1279	340	50
	225/40R18 XL	92	T	8J	630	1389	340	50
	225/45R18 XL	95	T	7 1/2J	690	1521	340	50
	235/50R18 XL	101	T	7 1/2J	825	1819	340	50
	235/60R18 XL	107	T	7J	975	2149	340	50
	245/40R18 XL	97	T	8 1/2J	730	1609	340	50
	245/50R18 XL	104	T	7 1/2J	900	1984	340	50
19	255/60R18 XL	112	T	7 1/2J	1120	2469	340	50
	225/35R19 XL	88	T	8J	560	1235	340	50
	235/40R19 XL	96	T	8 1/2J	710	1565	340	50
	245/35R19 XL	93	T	8 1/2J	650	1433	340	50
	245/40R19 XL	98	T	8 1/2J	750	1653	340	50
	245/45R19 XL	102	T	8J	850	1874	340	50
	255/40R19 XL	100	T	9J	800	1764	340	50
	255/45R19 XL	104	T	8 1/2J	900	1984	340	50
20	255/55R19 XL	111	T	8J	1090	2403	340	50
	245/40R20 XL	99	T	8 1/2J	775	1709	340	50
	245/45R20 XL	103	T	8J	875	1929	340	50
	255/35R20 XL	97	T	9J	730	1609	340	50
	255/50R20 XL	109	T	8J	1030	2271	340	50
	265/50R20 XL	111	T	8 1/2J	1090	2403	340	50

GREEN-MAX WINTER GRIP



Studdable snow tire with outstanding braking performance on ice&snow condition

PERFORMANCE

- 1 Designed for ice and snow surface.
- 2 Directional tread pattern design for excellent snow traction performance.
- 3 Great grip and handling performance on ice and snow surface.

GREEN-MAX WINTER GRIP / HP/UHP



RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
13	155/70R13	75	T	4.50B	387	853	300	44
	155/80R13	79	T	4.50B	437	963	300	44
	165/70R13	79	Q	5.00B	437	963	300	44
	175/70R13	82	T	5.00B	475	1047	300	44
14	175/65R14 XL	86	T	5J	530	1168	340	50
	185/60R14	82	T	5 1/2J	475	1047	300	44
	185/65R14 XL	90	T	5 1/2J	600	1323	340	50
	185/70R14 XL	92	T	5 1/2J	630	1389	340	50
15	185/55R15 XL	86	T	6J	530	1168	340	50
	185/65R15	88	T	5 1/2J	560	1235	300	44
	195/60R15 XL	92	T	6J	630	1389	340	50
	195/65R15 XL	95	T	6J	690	1521	340	50
	205/65R15 XL	99	T	6J	775	1709	340	50
16	205/55R16 XL	94	T	6 1/2J	670	1477	340	50
	205/60R16 XL	96	T	6J	710	1565	340	50
	215/55R16 XL	97	T	7J	730	1609	340	50
	215/60R16	95	T	6 1/2J	690	1521	300	44
	215/65R16	98	T	6 1/2J	750	1653	300	44
	215/70R16 XL	104	T	6 1/2J	900	1984	340	50
17	215/50R17 XL	95	T	7J	690	1521	340	50
	215/55R17 XL	98	T	7J	750	1653	340	50
	225/45R17 XL	94	T	7 1/2J	670	1477	340	50
	225/55R17	97	T	7J	730	1609	300	44

GREEN-MAX WINTER GRIP SUV



Studdable snow tire with outstanding braking performance on ice&snow condition

PERFORMANCE

- 1 Designed for ice and snow surface.
- 2 Excellent snow traction performance with directional tread pattern design.
- 3 Great grip and handling performance on ice and snow surface.
- 4 Designed for SUVs.

GREEN-MAX WINTER GRIP SUV / HP/UHP



RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
17	225/65R17 XL	106	T	6 1/2J	950	2094	340	50
	235/60R17 XL	106	T	7J	950	2094	340	50
	235/65R17 XL	108	T	7J	1000	2205	340	50

GREEN-MAX WINTER GRIP SUV / HP/UHP



RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
17	265/70R17	115	T	8J	1215	2679	300	44
18	225/55R18	98	T	7J	750	1653	300	44
	255/55R18 XL	109	T	8J	1030	2271	340	50
	275/60R18 XL	117	T	8J	1285	2833	340	50
20	275/45R20 XL	110	T	9J	1060	2337	340	50
	275/55R20 XL	117	T	8 1/2J	1285	2833	340	50

GREEN-MAX WINTER GRIP VAN 2



Studdable snow commercial tire

PERFORMANCE

- 1 Designed for ice and snow surface.
- 2 Great grip and handling performance on ice and snow surface.

GREEN-MAX WINTER GRIP VAN 2



RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
10	195/55R10C	-	98/96	N	6.00B	D 710 S 750	D 1565 S 1655	625	90
13	155R13C	8PR	90/88	R	4.50B	D 560 S 600	D 1235 S 1325	450	65
	155R13C	-	91/89	N	4.50B	D 580 S 615	D 1280 S 1355	450	65
	165R13C	-	96/94	N	4.50B	D 670 S 710	D 1475 S 1565	450	65
	175R13C	8PR	97/95	Q	5.00B	D 690 S 730	D 1520 S 1610	450	65
	195/50R13C	-	104/101	N	6.00B	D 825 S 900	D 1820 S 1985	650	94
14	185R14C	8PR	102/100	R	5 1/2J	D 800 S 850	D 1765 S 1875	450	65
	185R14C	-	102/100	N	5 1/2J	D 800 S 850	D 1765 S 1875	450	65
15	195/70R15C	8PR	104/102	R	6J	D 850 S 900	D 1875 S 1985	450	65
	215/70R15C	8PR	109/107	R	6 1/2J	D 975 S 1030	D 2150 S 2270	450	65
	225/70R15C	8PR	112/110	R	6 1/2J	D 1060 S 1120	D 2335 S 2470	450	65
16	185/75R16C	8PR	104/102	R	5J	D 850 S 900	D 1875 S 1985	475	69
	195/75R16C	8PR	107/105	R	5 1/2J	D 925 S 975	D 2040 S 2150	475	69
	205/65R16C	8PR	107/105	R	6J	D 925 S 975	D 2040 S 2150	475	69
	215/65R16C	8PR	109/107	R	6 1/2J	D 975 S 1030	D 2150 S 2270	475	69
	205/75R16C	8PR	110/108	R	5 1/2J	D 1000 S 1060	D 2205 S 2335	475	69
	215/75R16C	10PR	116/114	R	6J	D 1180 S 1250	D 2600 S 2755	525	76
	225/65R16C	8PR	112/110	R	6 1/2J	D 1060 S 1120	D 2335 S 2470	475	69
	225/75R16C	10PR	121/120	R	6J	D 1400 S 1450	D 3085 S 3195	575	83
	235/65R16C	10PR	121/119	R	7J	D 1360 S 1450	D 3000 S 3195	575	83
	215/60R17C	8PR	109/107	R	6 1/2J	D 975 S 1030	D 2150 S 2270	475	69
17	235/60R17C	10PR	117/115	Q	7J	D 1215 S 1285	D 2680 S 2835	525	76